

Product brief

MOTIX™ Motor Driver IC TLE9410EQW

3-Phase universal BLDC Motor Driver IC for diverse voltage applications ranging from 8~72 V

The TLE9140EQW is a 3-phase gate driver IC that can operate between 8 V to 72 V battery voltage. This new innovative IC perfectly complements MOTIX™ MCU devices allowing a scalable inverter solution from 8~72 V to maximize HW and SW re-use. The device is also compatible with diverse other Infineon or open market MCU products enabling a flexible application design.

This device is available in a TSDSO-32 (8.65 x 3.9 mm) package.

Key benefits

- In conjunction with MOTIX™ MCU
  - Easy approach and scaling for 24/48 V battery voltage applications
  - Optimized 24 V/48 V chipset comprising of MOTIX™ MCU and discrete motor driver IC using the supervision and protection functions from the SOC solution
  - Input pin is high voltage compatible which allows the device to be controlled by the output of the MOTIX™ MCU, hence additional GPIO Pins are made available for other functions
  - Maximize re-use of MOTIX™ MCU motor control software for faster time-to-market
- Product also allows for flexible MCU selection for increased flexible application design
- Max junction temp of 175°C to support challenging mission profiles
- Configurable low side freewheeling features protects the 48 V system from overvoltage damage
- Small packaging design TSDSO-32 saving space and weight (8.65 x 3.9 mm @ body size, 52 mm^2 PCB footprint)
- Development acc. to ISO 26262 achieving ASIL B


Key features

- High voltage capability/robustness up to 110 V
- Gate driving capability: ~230 µC/MOSFET up to 25 kHz
- Gate-shaping feature
- Active LS freewheeling during VSM OV
- Drain-source monitoring
- BEMF comparator
- Timeout-watchdog
- Overvoltage & undervoltage protection
- Cross-current protection
- Overtemperature protection
- Off-state diagnostics
- SPI communication
- Safe switch off path fulfilling ASIL B metric

Key applications


- BLDC Motor Control
  - Engine cooling fan
  - Water pump
  - Oil pump
  - eCompressor
  - eBike/eScooter
  - CAV/Truck
  - eTruck

PRO SIL ISO 26262 compliant



www.infineon.com/bldc-motor-driver-ics

Application diagram – MOTIX™ TLE9140EQW for BLDC motor control



Product table

Product variant	VSM [V]	Grade level	ASIL	SPI	Package	Driver
MOTIX™ TLE9140EQW	8 ... 72	0	B	✓	TSDSO-32	3x half-bridges (10 max 480 mA)

www.infineon.com

Published by
Infineon Technologies AG
Am Campeon 1-15, 85579 Neubiberg
Germany

© 2022 Infineon Technologies AG
All rights reserved.

Date: 08 / 2022

Please note!
This Document is for information purposes only and any information given herein shall in no event be regarded as a warranty, guarantee or description of any functionality, conditions and/or quality of our products or any suitability for a particular purpose. With regard to the technical specifications of our products, we kindly ask you to refer to the relevant product data sheets provided by us. Our customers and their technical departments are required to evaluate the suitability of our products for the intended application.

We reserve the right to change this document and/or the information given herein at any time.

Additional information
For further information on technologies, our products, the application of our products, delivery terms and conditions and/or prices, please contact your nearest Infineon Technologies office (www.infineon.com).

Warnings
Due to technical requirements, our products may contain dangerous substances. For information on the types in question, please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by us in a written document signed by authorized representatives of Infineon Technologies, our products may not be used in any life-endangering applications, including but not limited to medical, nuclear, military, life-critical or any other applications where a failure of the product or any consequences of the use thereof can result in personal injury.