RELEASE NOTES

==========

Product Name : **DAvE XC22xxL_Series**
Release Version : **1.0**
Type of Release : **Release Candidate (RC)**

Important Notice:
The delivery is **not** intended to be used for production code

==========

Name of the Supplier : **Infineon Technologies**
Date of Release : **16.12.2010**

==========

List of Released Items:

Released Item	Filename	Version	Updated
DAvE DIP	XC22xxL_Series_v1_0.dip	1.0	
Software Release Notes	DAvE_XC22xxL_Series_Release_Notes_v1_0.pdf	1.0	
Installation Procedure	DAvE_XC22xxL_Series_Dip_Installation_Procedure_v1_0.pdf	1.0	

Customer Contact:

If you need any support for the software or documentation, contact Infineon Technologies AG by electronic mail:

dave@Infineon.com

System Requirements:

This release is intended to be used with

- DAvE Mother System version 2.1r22 and above
- Tasking Viper v2.4r2
- Tasking Classic v8.8r1
- Keil v4.00a

Installation Instructions:

Installation instructions for installing XC22xxL_Series_v1.0 dip is provided in "DAvE_XC22xxL_Series_Dip_Installation_Procedure_v1_0.pdf"

Changes from the previous Release Version v0.1:

List of new Features:

- Enhancements:

ID	Description	Status
AI00058019	Selection of protocol version is provided for each node.	Done
AI00058021	Lin - Static signal API is supported for signal size being maximum 16 bits & out of byte boundary.	Done

List of fixed Bugs:

ID	Description	Status
AI00058025	In SCU-ESR Page pins that are not available in LE/ULE dips are disabled with a tool tip.	Fixed

List of Limitations (incl. Workarounds):

Limitations:

- LIN support is only available for Tasking Viper.
- LIN baud rate has to be in the range of 5k to 20k.
- The LDF reader is designed to read LDF files based upon Lin specification versions 2.0 and 2.1 only. In addition, it supports reading of LDF file without comments.

Note / Application Hints:

1. Supports latest LIN driver release V1.4 Beta. Please refer to the driver release notes/user manual for driver details.
2. While using the static signals for master requests and slave responses care should be taken to declare the required variables as “extern”
   Ex:
   ```
   extern uint8 Lin_DiagTxFifo[_DGNSTC_TBUFF_SZ][LIN_DIAG_FRM_LEN];
   extern uint8 Lin_DiagRxFifo[_DGNSTC_RBUFF_SZ][LIN_DIAG_FRM_LEN];
   extern uint8 Lin_DiagRxFifoRdIdx;
   extern uint8 Lin_DiagTxFifoWrIdx;
   ```
3. While using DAvE option “Internal Buffer Management” for transport protocol, the diagnostic buffers are not defined to be used external to the driver.
4. DAvE LDF parser is not taking any action on the section “Node Composition definition” in ldf file, since this is not required by the driver.

Notes on Release v0.1

List of Features:

- Following devices are supported
  a. XC2224L
  b. XC2234L
- Following Compilers are supported
  a. Tasking Viper v2.4r2
  b. Tasking Classic v8.8r1
  c. Keil v4.00a
- Following System Units & Peripheral Units can be configured through DAvE
  a. Main (Project Settings)
  b. Ports
  c. Interrupt
  d. SCU
  e. WDT
  f. USICx
  g. GPTx
  h. RTC
  i. ADCx
  j. CC2
  k. CCU6x
  l. MultiCAN
- Lin Configuration for USIC Peripheral is supported

List of Limitations (incl. Workarounds):

Limitations:

- LIN support is only available for Tasking Viper.
- LIN baud rate has to be in the range of 5k to 20k.
- If static signal API option is selected, signal size should be less than 8 bits & should fall in byte boundary.
- The LDF reader is designed to read LDF files based upon Lin specification versions 2.0 and 2.1 only. In addition, it supports reading of LDF file without comments.

Note / Application Hints:

1. Supports latest LIN driver release V1.4 Beta. Please refer to the driver release notes/user manual for driver details.
2. While using the static signals for master requests and slave responses care should be taken to declare the required variables as “extern”
   Ex:
   ```
   extern uint8 Lin_DiagTxFifo[_DGNSTC_TBUFF_SZ][LIN_DIAG_FRM_LEN];
   extern uint8 Lin_DiagRxFifo[_DGNSTC_RBUFF_SZ][LIN_DIAG_FRM_LEN];
   extern uint8 Lin_DiagRxFifoRdIdx;
   extern uint8 Lin_DiagTxFifoWrIdx;
   ```
3. While using DAvE option “Internal Buffer Management” for transport protocol, the diagnostic buffers are not defined to be used external to the driver.
4. DAvE LDF parser is not taking any action on the section “Node Composition definition” in ldf file, since this is not required by the driver.