


Automotive CoolSiC™ Gen2pE MOSFET

Quality Requirement Category: Automotive

Features

- Blocking voltage 1200V (rated)
- Low $R_{DS(ON)}$
- Low switching losses
- Low Q_G and C_{RSS}
- Extended operation at 200°C up to 100h
- Integrated gate resistor
- Easy paralleling of MOSFET
- Short circuit rugged technology



Applications

- Motor drive traction inverter

Description

- Recommended for power modules

Product Validation

- Technology qualified for automotive applications. Product validation according to AEC-Q101.

Key Performance Parameters

Chip Type	V_{DSS}	I_{Dc}	$R_{DS(on)}$	Die Size (total)
AIMC120R008D22M2P1	1200V	136A ^a	8.4mΩ	32mm ²

^a Chip capability with appropriate assembly. Calculated based on theoretical $R_{thJC} = 0.4$ [K/W]

Table of Contents

Features	1
Applications.....	1
Description	1
Product Validation.....	1
Key Performance Parameters	1
Table of Contents	2
1 Maximum Ratings	3
2 Recommended Values.....	3
3 Electrical Characteristics	4
4 Body Diode Characteristics.....	6
5 Mechanical Parameters.....	7
6 Die Drawing	8
7 Bare Die Product Specifics.....	9
Revision History	9

1 Maximum Ratings ^b

Parameter	Symbol	Conditions	Value	Unit
Drain-source voltage	V_{DSS}	$-40^{\circ}\text{C} \leq T_{vj} \leq 200^{\circ}\text{C}$	1200	V
Continuous DC drain current, limited by $T_{vj\max}$	I_{DDC}	$V_{GS} = 18\text{V}$, $T_c = 25^{\circ}\text{C}$	106 ^c 136 ^d	A
Peak reverse drain current	I_{SM}	$V_{GS} = -3\text{V}$, $T_c = 25^{\circ}\text{C}$, $T_{\text{pulse}} = 2\mu\text{s}$	230	A
Maximum gate-source voltage	V_{GS}		-10 ... +23	V
Operating virtual junction temperature	T_{vj}	over lifetime	-40 ... +185	$^{\circ}\text{C}$
		100 hours	+185 ... +200	$^{\circ}\text{C}$

2 Recommended Values

Parameter	Symbol	Conditions	Value	Unit
Recommended turn-on gate voltage	$V_{GS(on)}$		18	V
Recommended turn-off gate voltage	$V_{GS(off)}$		-3	V

^b Not subject to production test, verified by design/characterization.

^c Chip capability with appropriate assembly. Calculated based on theoretical $R_{thJC} = 0.66$ [K/W].

^d Chip capability with appropriate assembly. Calculated based on theoretical $R_{thJC} = 0.4$ [K/W].

3 Electrical Characteristics

Specification limits valid over product lifetime if not stated otherwise.

Parameter	Symbol	Conditions		Value			Unit
				min.	typ.	max.	
Drain-source breakdown voltage	$V_{(BR)DSS}$	$I_D = 1\text{mA}$	$T_{vj} = -40^{\circ}\text{C}^{\text{e}}$	1200	-	-	V
			$T_{vj} = 25^{\circ}\text{C}$	1200	-	-	
			$T_{vj} = 200^{\circ}\text{C}^{\text{e}}$	1200	-	-	
Gate-source threshold voltage ^f (tested after 1ms pulse at $V_{GS} = +20\text{V}$)	$V_{GS(th)}$	$I_D = 26\text{mA}, V_{GS} = V_{DS}$	$T_{vj} = 25^{\circ}\text{C}$	4.49	5.09	5.69	V
			$T_{vj} = 175^{\circ}\text{C}^{\text{e}}$	3.29	3.89	4.49	
			$T_{vj} = 185^{\circ}\text{C}^{\text{e}}$	3.24	3.84	4.44	
			$T_{vj} = 200^{\circ}\text{C}^{\text{e}}$	-	3.79	-	
Drain-source resistance	$R_{DS(on)}$	$V_{GS} = 18\text{V}, I_D = 95\text{A}$	$T_{vj} = 25^{\circ}\text{C}$	-	8.4	10.6 ^f	mΩ
						11.0	
			$T_{vj} = 175^{\circ}\text{C}^{\text{e}}$	-	16.4	20.3 ^f	
						20.5	
			$T_{vj} = 185^{\circ}\text{C}^{\text{e}}$	-	17.3	21.5 ^f	
						21.7	
			$T_{vj} = 200^{\circ}\text{C}^{\text{e}}$	-	18.7	23.0 ^f	
						23.3	
Source-drain resistance	$R_{SD(on)}$	$V_{GS} = 18\text{V}, I_D = -95\text{A}$	$T_{vj} = 25^{\circ}\text{C}^{\text{e}}$	-	7.9	-	mΩ
			$T_{vj} = 175^{\circ}\text{C}^{\text{e}}$	-	16.1	-	
			$T_{vj} = 185^{\circ}\text{C}^{\text{e}}$	-	17.0	-	
			$T_{vj} = 200^{\circ}\text{C}^{\text{e}}$	-	18.3	-	
Zero gate-voltage drain current	I_{DSS}	$V_{DS} = 1200\text{V}, V_{GS} = 0\text{V}$	$T_{vj} = 25^{\circ}\text{C}$	-	2	50	μA
			$T_{vj} = 175^{\circ}\text{C}^{\text{e}}$	-	17	100	
			$T_{vj} = 185^{\circ}\text{C}^{\text{e}}$	-	21	100	
			$T_{vj} = 200^{\circ}\text{C}^{\text{e}}$	-	24	-	
Positive gate-source leakage current	I_{GSS+}	$V_{DS} = 0\text{V}, V_{GS} = 23\text{V}$	$T_{vj} = 25^{\circ}\text{C}$	-	1	200	nA
			$T_{vj} = 175^{\circ}\text{C}^{\text{e}}$	-	4	400	
			$T_{vj} = 185^{\circ}\text{C}^{\text{e}}$	-	8	400	
			$T_{vj} = 200^{\circ}\text{C}^{\text{e}}$	-	11	-	

^e Not subject to production test, verified by design/characterization.

^f Values specified for zero hour not according to AEC-Q101.

Parameter	Symbol	Conditions		Value			Unit
				min.	typ.	max.	
Negative gate-source leakage current	I_{GSS-}	$V_{DS} = 0V, V_{GS} = -10V$	$T_{vj} = 25^{\circ}C$	-	0.1	100	nA
			$T_{vj} = 175^{\circ}C^g$	-	0.4	100	
			$T_{vj} = 185^{\circ}C^g$	-	0.8	100	
			$T_{vj} = 200^{\circ}C^g$	-	1.1	-	
Internal gate resistor ^{g, h}	$R_{G,int}$	$f = 100kHz, dV = 25mV, T_{vj} = 25^{\circ}C$		-	1.7	-	Ω
Forward transconductance ^g	g_{fs}	$V_{DS} = 20V, I_D = 95A, T_{vj} = 25^{\circ}C$		-	80	-	S
Input capacitance ^g	C_{iss}	$V_{DS} = 800V, f = 100kHz, dV = 25mV, T_{vj} = 25^{\circ}C$		-	7200	-	pF
Output capacitance ^g	C_{oss}			-	270	-	
Reverse transfer capacitance ^g	C_{rss}			-	20	-	
Gate charge ^g	Q_G	$V_{DS} = 800V, I_D = 95A, V_{GS(on)} = 18V, V_{GS(off)} = -3V, T_{vj} = 25^{\circ}C$		-	245	-	nC
Gate-to-source charge ^g	Q_{GS}			-	91	-	
Gate-to-drain charge ^g	Q_{GD}			-	51	-	
Turn-on energy ^{i, j}	E_{on}	$V_{DS} = 800V, I_D = 95A, V_{GS(on)} = 18V, V_{GS(off)} = -3V, L_s = 20nH, dV_{DS}/dt = 20V/ns, T_{vj} = 25^{\circ}C$		-	1.93	-	mJ
Turn-off energy ⁱ	E_{off}			-	1.81	-	

^g Not subject to production test, verified by design/characterization.

^h The internal gate resistor includes the implemented and layout dependent gate resistance.

ⁱ Not subject to production test, characterized in TO-247-4 package on a reference test setup.

^j Body diode E_{rec} included.

4 Body Diode Characteristics


Specification limits valid over product lifetime if not stated otherwise.

Parameter	Symbol	Conditions		Value			Unit
				min.	typ.	max.	
Drain-source reverse voltage	V_{SD}	$I_F = 95A$, $V_{GS} = -3V$	$T_{vj} = 25^{\circ}C$	3.9	4.7	5.5	V
			$T_{vj} = 175^{\circ}C^k$	3.45	4.25	5.05	
			$T_{vj} = 185^{\circ}C^k$	3.4	4.2	5.0	
			$T_{vj} = 200^{\circ}C^k$	-	4.15	-	
Reverse recovery charge ^k	Q_{rr}	$V_{DS} = 800V$, $I_D = 95A$, $V_{GS(on)} = 18V$, $V_{GS(off)} = -3V$, $di/dt = 1kA/\mu s$, $T_{vj} = 25^{\circ}C$		-	217	-	nC
Reverse recovery time ^k	t_{rr}			-	25	-	ns
Peak reverse recovery current ^k	I_{rm}			-	15	-	A

5 Mechanical Parameters

Chip size after sawing	x = 6.37mm, y = 4.97mm	
Raster size	x = 6.40mm, y = 5.00mm	
Area total	32	mm ²
Source pad size	See die drawing	
Gate pad size	See die drawing	
SiC thickness	110	μm
Chip thickness (incl. Imide)	130	μm
Passivation front side	Photoimide	
Pad metal	NiP/Pd	
Backside metal	Ni/Ag - system	
Storage environment (<6 months) for original and sealed MBB bags	Ambient atmosphere air, temperature 17°C – 25°C	
Storage environment (<6 months) for open MBB bags	Acc. IEC 62258-3; Section 9.4 Storage Environment	

6 Die Drawing



Legend:

- S = Source
- G = Gate
- K = Kelvin pad

7 Bare Die Product Specifics

Note: The MOSFET wafer level test cannot cover the full range of customer application conditions. Therefore it is the responsibility of the customer to test all performance characteristics, which are relevant for their specific application, at the package level.

Description

- AQL 0.1 for visual inspection according to failure catalogue

Revision History

Document version	Date of release	Description of changes
V1.0	2025-12-05	Initial Data Sheet
V1.1	2026-02-23	Typo in mechanical parameters corrected.

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2026-02-23

Published by

Infineon Technologies AG

81726 München, Germany

© 2026 Infineon Technologies AG.

All Rights Reserved.

Do you have a question about this document?

Email: erratum@infineon.com

Document reference

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology delivery terms and conditions and prices please contact your nearest Infineon Technologies office (www.infineon.com).

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.