CY7C106D
CY7C1006D

1-Mbit (256 K × 4) Static RAM

Features

- Pin- and function-compatible with CY7C106B/CY7C1006B
- High speed
  - t_{AA} = 10 ns
- Low active power
  - I_{CC} = 80 mA @ 10 ns
- Low CMOS standby power
  - I_{SB2} = 3.0 mA
- 2.0 V Data Retention
- Automatic power-down when deselected
- CMOS for optimum speed/power
- TTL-compatible inputs and outputs
- CY7C106D available in Pb-free 28-pin 400-Mil wide Molded SOJ package. CY7C1006D available in Pb-free 28-pin 300-Mil wide Molded SOJ package

Functional Description

The CY7C106D [1] and CY7C1006D [1] are high-performance CMOS static RAMs organized as 262,144 words by 4 bits. Easy memory expansion is provided by an active LOW Chip Enable ($\overline{CE}$), an active LOW Output Enable ($\overline{OE}$), and tri-state drivers. These devices have an automatic power-down feature that reduces power consumption by more than 65% when the devices are deselected. The four input and output pins (IO_0 through IO_3) are placed in a high-impedance state when:

- Deselected ($\overline{CE}$ HIGH)
- Outputs are disabled ($\overline{OE}$ HIGH)
- When the write operation is active ($\overline{CE}$ and $\overline{WE}$ LOW)


Write to the device by taking Chip Enable ($\overline{CE}$) and Write Enable ($\overline{WE}$) inputs LOW. Data on the four IO pins (IO_0 through IO_3) is then written into the location specified on the address pins (A_0 through A_{17}).

Read from the device by taking Chip Enable ($\overline{CE}$) and Output Enable ($\overline{OE}$) LOW while forcing Write Enable ($\overline{WE}$) HIGH. Under these conditions, the contents of the memory location specified by the address pins appears on the four IO pins.

Both CY7C106D and CY7C1006D devices are suitable for interfacing with processors that have TTL I/P levels. They are not suitable for processors that require CMOS I/P levels. Please see Electrical Characteristics on page 4 for more details and suggested alternatives.

For a complete list of related documentation, click here.

Logic Block Diagram




Note
1. For guidelines on SRAM system design, please refer to the 'System Design Guidelines' Cypress application note, available on the internet at www.cypress.com.

Contents

Pin Configurations **3**
Selection Guide **3**
Maximum Ratings **4**
Operating Range **4**
Electrical Characteristics **4**
Capacitance **5**
Thermal Resistance **5**
AC Test Loads and Waveforms **5**
Data Retention Characteristics **6**
Data Retention Waveform **6**
Switching Characteristics **7**
Switching Waveforms **8**
Truth Table **11**
Ordering Information **11**
Ordering Code Definitions 11
Package Diagrams **12**
Acronyms **14**
Document Conventions **14**
Units of Measure 14
Document History Page **15**
Sales, Solutions and Legal Information **16**
Worldwide Sales and Design Support 16
Products 16
PSoC® Solutions 16
Cypress Developer Community 16
Technical Support 16

Pin Configurations

Figure 1. 28-pin SOJ pinout (Top View) [2]



Selection Guide

Description	CY7C106D-10 CY7C1006D-10	Unit
Maximum Access Time	10	ns
Maximum Operating Current	80	mA
Maximum Standby Current	3	mA

Note
2. NC pins are not connected on the die.

Maximum Ratings

Exceeding the maximum ratings may impair the useful life of the device. These user guidelines are not tested.

Storage Temperature ..... –65 °C to +150 °C

Ambient Temperature with Power Applied ..... –55 °C to +125 °C

Supply Voltage on V_{CC} Relative to GND [3] .....–0.5 V to +6.0 V

DC Voltage Applied to Outputs in High Z State [3] ..... –0.5 V to V_{CC} + 0.5 V

DC Input Voltage [3] ..... –0.5 V to V_{CC} + 0.5 V

Current into Outputs (LOW) ..... 20 mA

Static Discharge Voltage (per MIL-STD-883, Method 3015) ..... > 2001 V

Latch-up Current ..... > 200 mA

Operating Range

Range	Ambient Temperature	V_{CC}	Speed
Industrial	–40 °C to +85 °C	5 V ± 0.5 V	10 ns

Electrical Characteristics

Over the Operating Range

Parameter	Description	Test Conditions		7C106D-10 7C1006D-10		Unit
				Min	Max	
V_{OH}	Output HIGH Voltage	I_{OH} = –4.0 mA		2.4	–	V
		I_{OH} = –0.1 mA		–	3.4 [4]	
V_{OL}	Output LOW Voltage	I_{OL} = 8.0 mA		–	0.4	V
V_{IH}	Input HIGH Voltage			2.2	V_{CC} + 0.5	V
V_{IL}	Input LOW Voltage [3]			–0.5	0.8	V
I_{IX}	Input Leakage Current	GND ≤ V_I ≤ V_{CC}		–1	+1	µA
I_{OZ}	Output Leakage Current	GND ≤ V_I ≤ V_{CC}, Output Disabled		–1	+1	µA
I_{CC}	V_{CC} Operating Supply Current	V_{CC} = Max, I_{OUT} = 0 mA, f = f_{max} = $1/t_{RC}$	100 MHz	–	80	mA
			83 MHz	–	72	mA
			66 MHz	–	58	mA
			40 MHz	–	37	mA
I_{SB1}	Automatic CE Power-Down Current — TTL Inputs	Max V_{CC}, $\overline{CE}$ ≥ V_{IH}, V_{IN} ≥ V_{IH} or V_{IN} ≤ V_{IL}, f = f_{max}		–	10	mA
I_{SB2}	Automatic CE Power-Down Current — CMOS Inputs	Max V_{CC}, $\overline{CE}$ ≥ V_{CC} – 0.3 V, V_{IN} ≥ V_{CC} – 0.3 V or V_{IN} ≤ 0.3 V, f = 0		–	3	mA

Note
3. V_{IL} (min) = –2.0 V and V_{IH}(max) = V_{CC} + 1 V for pulse durations of less than 5 ns.
4. Please note that the maximum V_{OH} limit does not exceed minimum CMOS V_{IH} of 3.5 V. If you are interfacing this SRAM with 5 V legacy processors that require a minimum V_{IH} of 3.5 V, please refer to Application Note AN6081 for technical details and options you may consider.

Capacitance


Parameter [5]	Description	Test Conditions	Max	Unit
C_{IN}: Addresses	Input capacitance	T_A = 25 °C, f = 1 MHz, V_{CC} = 5.0 V	7	pF
C_{IN}: Controls			10	pF
C_{OUT}	Output capacitance		10	pF

Thermal Resistance

Parameter [5]	Description	Test Conditions	300-Mil Wide SOJ	400-Mil Wide SOJ	Unit
Θ_{JA}	Thermal resistance (junction to ambient)	Still Air, soldered on a 3 × 4.5 inch, four-layer printed circuit board	59.16	58.76	°C/W
Θ_{JC}	Thermal resistance (junction to case)		40.84	40.54	°C/W

AC Test Loads and Waveforms

Figure 2. AC Test Loads and Waveforms [6]



Notes
5. Tested initially and after any design or process changes that may affect these parameters.
6. AC characteristics (except High Z) are tested using the load conditions shown in part (a) of Figure 2. High Z characteristics are tested for all speeds using the test load shown in part (c) of Figure 2.


Data Retention Characteristics

Over the Operating Range

Parameter	Description	Conditions	Min	Max	Unit
V_{DR}	V_{CC} for Data Retention		2.0	–	V
I_{CCDR}	Data Retention Current	$V_{CC} = V_{DR} = 2.0$ V, $\overline{CE} \geq V_{CC} - 0.3$ V, $V_{IN} \geq V_{CC} - 0.3$ V or $V_{IN} \leq 0.3$ V	–	3	mA
t_{CDR} [7]	Chip Deselect to Data Retention Time		0	–	ns
t_R [8, 9]	Operation Recovery Time		t_{RC}	–	ns

Data Retention Waveform

Figure 3. Data Retention Waveform



Notes
7. Tested initially and after any design or process changes that may affect these parameters.
8. Full device operation requires linear V_{CC} ramp from V_{DR} to $V_{CC(min)} \geq 50$ µs or stable at $V_{CC(min)} \geq 50$ µs.
9. $t_r \leq 3$ ns for all speeds.

Switching Characteristics

Over the Operating Range

Parameter [10]	Description	7C106D-10 7C1006D-10		Unit
		Min	Max	
Read Cycle				
t_{power} [11]	V_{CC}(typical) to the first access	100	–	µs
t_{RC}	Read Cycle Time	10	–	ns
t_{AA}	Address to Data Valid	–	10	ns
t_{OHA}	Data Hold from Address Change	3	–	ns
t_{ACE}	$\overline{CE}$ LOW to Data Valid	–	10	ns
t_{DOE}	$\overline{OE}$ LOW to Data Valid	–	5	ns
t_{LZOE}	$\overline{OE}$ LOW to Low Z	0	–	ns
t_{HZOE}	$\overline{OE}$ HIGH to High Z [12, 13]	–	5	ns
t_{LZCE}	$\overline{CE}$ LOW to Low Z [13]	3	–	ns
t_{HZCE}	$\overline{CE}$ HIGH to High Z [12, 13]	–	5	ns
t_{PU} [14]	$\overline{CE}$ LOW to Power-Up	0	–	ns
t_{PD} [14]	$\overline{CE}$ HIGH to Power-Down	–	10	ns
Write Cycle [15, 16]				
t_{WC}	Write Cycle Time	10	–	ns
t_{SCE}	$\overline{CE}$ LOW to Write End	7	–	ns
t_{AW}	Address Set-Up to Write End	7	–	ns
t_{HA}	Address Hold from Write End	0	–	ns
t_{SA}	Address Set-Up to Write Start	0	–	ns
t_{PWE}	$\overline{WE}$ Pulse Width	7	–	ns
t_{SD}	Data Set-Up to Write End	6	–	ns
t_{HD}	Data Hold from Write End	0	–	ns
t_{LZWE}	$\overline{WE}$ HIGH to Low Z [13]	3	–	ns
t_{HZWE}	$\overline{WE}$ LOW to High Z [12, 13]	–	5	ns

Notes

10. Test conditions assume signal transition time of 3 ns or less, timing reference levels of 1.5 V, input pulse levels of 0 to 3.0 V, and output loading of the specified I_{OL}/I_{OH} and 30-pF load capacitance.
11. t_{POWER} gives the minimum amount of time that the power supply should be at typical V_{CC} values until the first memory access can be performed.
12. t_{HZOE}, t_{HZCE}, and t_{HZWE} are specified with a load capacitance of 5 pF as in part (c) of Figure 2 on page 5. Transition is measured when the outputs enter a high impedance state.
13. At any given temperature and voltage condition, t_{HZCE} is less than t_{LZCE}, t_{HZOE} is less than t_{LZOE}, and t_{HZWE} is less than t_{LZWE} for any given device.
14. This parameter is guaranteed by design and is not tested.
15. The internal write time of the memory is defined by the overlap of $\overline{CE}$ and $\overline{WE}$ LOW. $\overline{CE}$ and $\overline{WE}$ must be LOW to initiate a write, and the transition of either of these signals can terminate the write. The input data set-up and hold timing should be referenced to the leading edge of the signal that terminates the write.
16. The minimum write cycle time for Write Cycle No. 3 ($\overline{WE}$ controlled, $\overline{OE}$ LOW) is the sum of t_{HZWE} and t_{SD}.

Switching Waveforms

Figure 4. Read Cycle No.1 (Address Transition Controlled) [17, 18]





Figure 5. Read Cycle No. 2 ($\overline{OE}$ Controlled) [18, 19]



Notes
17. Device is continuously selected, $\overline{OE}$ and $\overline{CE}$ = V_{IL}.
18. $\overline{WE}$ is HIGH for read cycle.
19. Address valid prior to or coincident with $\overline{CE}$ transition LOW.

Switching Waveforms (continued)

Figure 6. Write Cycle No. 1 ($\overline{CE}$ Controlled) [20, 21]






Figure 7. Write Cycle No. 2 ($\overline{WE}$ Controlled, $\overline{OE}$ HIGH During Write) [20, 21]



Notes
20. If $\overline{CE}$ goes HIGH simultaneously with $\overline{WE}$ going HIGH, the output remains in a high-impedance state.
21. Data IO is high impedance if $\overline{OE} = V_{IH}$.

Switching Waveforms (continued)

Figure 8. Write Cycle No. 3 ($\overline{WE}$ Controlled, $\overline{OE}$ LOW) [22, 23]



Notes
22. The minimum write cycle time for Write Cycle No. 3 ($\overline{WE}$ controlled, $\overline{OE}$ LOW) is the sum of t_{HZWE} and t_{SD}.
23. Data IO is high impedance if $\overline{OE} = V_{IH}$.

Truth Table


$\overline{CE}$	$\overline{OE}$	$\overline{WE}$	Input/Output	Mode	Power
H	X	X	High Z	Power-Down	Standby (I_{SB})
L	L	H	Data Out	Read	Active (I_{CC})
L	X	L	Data In	Write	Active (I_{CC})
L	H	H	High Z	Selected, Outputs Disabled	Active (I_{CC})

Ordering Information

Speed (ns)	Ordering Code	Package Diagram	Package Type	Operating Range
10	CY7C106D-10VXI	51-85032	28-pin SOJ (400 Mils) Pb-free	Industrial


Please contact your local Cypress sales representative for availability of these parts.

Ordering Code Definitions




Package Diagrams

Figure 9. 28-pin SOJ (300 Mils) V28.3 (Molded SOJ V21) Package Outline, 51-85031



Package Diagrams (continued)

Figure 10. 28-pin (400 Mils) V28.4 (Molded SOJ V28) Package Outline, 51-85032



51-85032 *F

Acronyms

Acronym	Description
$\overline{CE}$	Chip Enable
CMOS	Complementary Metal-Oxide Semiconductor
I/O	Input/Output
$\overline{OE}$	Output Enable
SOJ	Small Outline J-lead
SRAM	Static Random Access Memory
TTL	Transistor-Transistor Logic
$\overline{WE}$	Write Enable

Document Conventions

Units of Measure

Symbol	Unit of Measure
°C	degree Celsius
MHz	megahertz
µA	microampere
µs	microsecond
mA	milliampere
ns	nanosecond
Ω	ohm
%	percent
pF	picofarad
V	volt
W	watt

Document History Page

Document Title: CY7C106D/CY7C1006D, 1-Mbit (256 K × 4) Static RAM Document Number: 38-05459				
Rev.	**ECN No.**	**Issue Date**	**Orig. of Change**	**Description of Change**
**	201560	See ECN	SWI	Advance information data sheet for C9 IPP
*A	233693	See ECN	RKF	I_{CC},I_{SB1},I_{SB2} Specs are modified as per EROS (Spec # 01-2165) Pb-free offering in the 'ordering information'
*B	262950	See ECN	RKF	Added T_{power} Spec in Switching Characteristics table Shaded 'Ordering Information'
*C	See ECN	See ECN	RKF	Reduced Speed bins to -10 and -12 ns
*D	560995	See ECN	VKN	Converted from Preliminary to Final Removed Commercial Operating range Removed 12 ns speed bin Added I_{CC} values for the frequencies 83MHz, 66MHz and 40MHz Updated Thermal Resistance table Updated Ordering Information table Changed Overshoot spec from V_{CC}+2V to V_{CC}+1V in footnote #3
*E	802877	See ECN	VKN	Changed I_{CC} spec from 60 mA to 80 mA for 100 MHz, 55 mA to 72 mA for 83 MHz, 45 mA to 58 mA for 66 MHz, 30 mA to 37 mA for 40 MHz
*F	2898399	03/24/2010	AJU	Updated Package Diagrams.
*G	3104943	12/08/2010	AJU	Added Ordering Code Definitions.
*H	3244490	04/29/2011	PRAS	Updated Package Diagrams. Added Acronyms and Units of Measure. Updated in new template.
*I	4033580	06/19/2013	MEMJ	Updated Functional Description. Updated Electrical Characteristics: Added one more Test Condition "I_{OH} = –0.1 mA" for V_{OH} parameter and added maximum value corresponding to that Test Condition. Added Note 4 and referred the same note in maximum value for V_{OH} parameter corresponding to Test Condition "I_{OH} = –0.1 mA". Updated Package Diagrams: spec 51-85031 – Changed revision from *D to *E.
*J	4385788	05/21/2014	MEMJ	Updated Package Diagrams: spec 51-85032 – Changed revision from *E to *F. Completing Sunset.Review.
*K	4579569	11/26/2014	MEMJ	Added related documentation hyperlink in page 1. Removed the prune part number CY7C1006D-10VXI in Ordering Information.

Sales, Solutions and Legal Information

Worldwide Sales and Design Support

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives, and distributors. To find the office closest to you, visit us at Cypress Locations.

Products

Automotive	cypress.com/go/automotive
Clocks & Buffers	cypress.com/go/clocks
Interface	cypress.com/go/interface
Lighting & Power Control	cypress.com/go/powerpsoc cypress.com/go/plc
Memory	cypress.com/go/memory
PSoC	cypress.com/go/psoc
Touch Sensing	cypress.com/go/touch
USB Controllers	cypress.com/go/USB
Wireless/RF	cypress.com/go/wireless

PSoC® Solutions

psoc.cypress.com/solutions

PSoC 1 | PSoC 3 | PSoC 4 | PSoC 5LP

Cypress Developer Community

Community | Forums | Blogs | Video | Training

Technical Support

cypress.com/go/support

© Cypress Semiconductor Corporation, 2004-2014. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Any Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.

All products and company names mentioned in this document may be the trademarks of their respective holders.