

Evaluation board EVAL-ISSI20R02HTS

EVAL-ISSI20R02HTS







Technical & product details

Parameter	Value
Load Voltage	60 VDC / 48 VAC
Load Current	10 A DC / 6.5 A AC
Input Voltage	2.85 - 3.5V
Package	DSO8 - 1.27 mm pitch, 300 mil
Isolation	5.7 kVrms, 8 kVpk
Certifications	UL1577, IEC 60747-17

Learn More	
Sales name	EVAL-ISSI20R02HTS
SAP mat number	SP006046641
Infineon order code	EVALISSI20R02HTSTOBO1
IFX Components	ISC035N10NM5LF, ISSI20R02H
Focus applications	AI Server BBU, BMS, Smart Home and Building, Industrial Automation PLC, SSR

Features

- Evaluation board with ISSI20R02H and two OptiMOS™ ISC035N10NM5LF MOSFETs in an AC switch configuration
- Over-temperature protection with PTC resistor
- Standard turn-on
- Fast turn-off after overcurrent and over-temperature protection
- Dynamic Miller clamping

Benefits

- Low-loss OptiMOS™ enables efficient AC switching
- PTC sensing and fast turn-off reduce thermal stress and load damage
- Miller clamping prevents parasitic turn-on

Copyright © Infineon Technologies AG 2026. All rights reserved.