Final datasheet

英飞凌 CoolSiC™ 1200 V SiC MOSFET G2：采用 .XT 互连技术的碳化硅 MOSFET

特性



- T_{vj} = 25°C 时 V_{DSS} = 1200 V
- T_c = 25 °C 时 I_{DDC} = 142 A
- $R_{DS(on)}$ = 7.5 mΩ（V_{GS} = 18 V, T_{vj} = 25°C 时）
- 开关损耗非常低
- 过载运行最高结温可达 T_{vj} = 200°C
- 基准栅极阈值电压，$V_{GS(th)}$ = 4.2 V
- 具有抗寄生导通能力，可应用 0 V 关断栅极电压
- 坚固的体二极管，适用于硬换向
- .XT 互连技术，实现行业领先的热性能
- 合适的英飞凌栅极驱动器可在 https://www.infineon.com/gdfinder 找到

Halogen-free

Green

Lead-free

RoHS

潜在应用

- 通用驱动器（GPD）
- 在线式UPS/工业UPS

产品验证


- 符合 JEDEC47/20/22 相关测试的工业应用要求

描述

引脚定义：

- 引脚 1 – 漏极
- 引脚 2 – 源极
- 引脚 3 – 开尔文检测触点
- 引脚 4 – 栅极

注：源极引脚和检测引脚不可互换，互换可能会导致故障



Type	Package	Marking
IMZC120R007M2H	PG-TO247-4-U07	12M2H007

本数据手册的原文使用英文撰写。为方便起见，英飞凌提供了译文；由于翻译过程中可能使用了自动化工具，英飞凌不保证译文的准确性。为确认准确性，请务必访问 infineon.com 参考最新的英文版本（控制文档）。

目录

描述 1
特性 1
潜在应用 1
产品验证 1
目录 2
1 封装 3
2 MOSFET 3
3 体二极管（MOSFET） 6
4 特征图 8
5 封装外形 15
6 测试条件 16
修订记录 17
免责声明 18

1 封装

表 1 特征值

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Storage temperature	T_{stg}		-55		150	°C
Soldering temperature	T_{sold}	Wave soldering 1.6 mm (0.063 in.) from case for 10 s			260	°C
Mounting torque	M	M3 screw, Maximum of mounting processes: 3			0.6	Nm
Thermal resistance, junction-ambient	$R_{th(j-a)}$				62	K/W
MOSFET/body diode thermal resistance, junction-case	$R_{th(j-c)}$			0.16	0.21	K/W

2 MOSFET

表 2 最大额定值

Parameter	Symbol	Note or test condition		Values	Unit
Drain-source voltage	V_{DSS}	$T_{vj} \geq 25$ °C		1200	V
Continuous DC drain current for $R_{th(j-c,max)}$, limited by $T_{vj(max)}$	I_{DDC}	$V_{GS} = 18$ V	$T_c = 25$ °C	201	A
			$T_c = 100$ °C	142	
Peak drain current, t_p limited by $T_{vj(max)}$ 1)	I_{DM}	$V_{GS} = 18$ V		710	A
Gate-source voltage, max. transient voltage	V_{GS}	$t_p \leq 0.5$ µs, $D < 0.01$		-10...25	V
Gate-source voltage, max. static voltage2)	V_{GS}			-7...23	V
Avalanche energy, single pulse	E_{AS}	$I_D = 93$ A, $V_{DD} = 50$ V, $L = 0.24$ mH, $T_{vj(start)} = 25$ °C		1036	mJ
Avalanche energy, repetitive	E_{AR}	$I_D = 93$ A, $V_{DD} = 50$ V, $L = 1.2$ µH, $T_{vj(start)} = 25$ °C		5.18	mJ
Power dissipation, limited by $T_{vj(max)}$	P_{tot}		$T_c = 25$ °C	711	W
			$T_c = 100$ °C	355	

1) 已通过设计/特性分析验证。
2) 应用设计中的最大栅源电压应符合IPC-9592B的规定。

表 3　　推荐值

Parameter	Symbol	Note or test condition	Values	Unit
Recommended turn-on gate voltage	$V_{GS(on)}$		15...18	V
Recommended turn-off gate voltage	$V_{GS(off)}$		-5...0	V

表 4　　特征值

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Drain-source on-state resistance	$R_{DS(on)}$	I_D = 93 A	T_{vj} = 25 °C, $V_{GS(on)}$ = 18 V		7.5		mΩ
			T_{vj} = 25 °C, $V_{GS(on)}$ = 15 V		9.34		
			T_{vj} = 150 °C, $V_{GS(on)}$ = 18 V		15.3	20	
			T_{vj} = 175 °C, $V_{GS(on)}$ = 18 V		17.7		
Gate-source threshold voltage	$V_{GS(th)}$	I_D = 29.1 mA, V_{DS} = V_{GS} (tested after 1 ms pulse at V_{GS} = 20 V)	T_{vj} = 25 °C	3.5	4.2	5.1	V
			T_{vj} = 175 °C		3.2		
Zero gate-voltage drain current	I_{DSS}	V_{DS} = 1200 V, V_{GS} = 0 V	T_{vj} = 25 °C			46	µA
			T_{vj} = 175 °C		13.6		
Gate leakage current	I_{GSS}	V_{DS} = 0 V	V_{GS} = -10 V			-120	nA
			V_{GS} = 23 V			120	
Forward transconductance	g_{fs}	I_D = 93 A, V_{DS} = 20 V			60		S
Internal gate resistance	$R_{G,int}$	f = 1 MHz, V_{AC} = 25 mV			1.8		Ω
Input capacitance	C_{iss}	V_{DS} = 800 V, V_{GS} = 0 V, f = 100 kHz, V_{AC} = 25 mV			6570		pF
Output capacitance	C_{oss}	V_{DS} = 800 V, V_{GS} = 0 V, f = 100 kHz, V_{AC} = 25 mV			287		pF
Reverse transfer capacitance	C_{rss}	V_{DS} = 800 V, V_{GS} = 0 V, f = 100 kHz, V_{AC} = 25 mV			25		pF
C_{oss} stored energy	E_{oss}	Calculated based on C_{oss} = f(V_{DD})			121		µJ
Output charge	Q_{oss}	Calculated based on C_{oss} = f(V_{DD})			449		nC
Effective output capacitance, energy related	$C_{o(er)}$	V_{DS} = 0...800 V, V_{GS} = 0 V, Calculated based on E_{oss}			378		pF
Effective output capacitance, time related	$C_{o(tr)}$	I_D = constant, V_{DS} = 0...800 V, V_{GS} = 0 V, Calculated based on Q_{oss}			562		pF
Total gate charge	Q_G	V_{DD} = 800 V, I_D = 93 A, V_{GS} = 0/18 V, turn-on pulse			176		nC

（表格续下页……）

表 4　　（续）特征值

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Plateau gate charge	$Q_{GS(pl)}$	V_{DD} = 800 V, I_D = 93 A, V_{GS} = 0/18 V, turn-on pulse			39		nC
Gate-drain charge	Q_{GD}	V_{DD} = 800 V, I_D = 93 A, V_{GS} = 0/18 V, turn-on pulse			43		nC
Turn-on delay time	$t_{d(on)}$	V_{DD} = 800 V, I_D = 93 A, V_{GS} = 0/18 V, $R_{G,ext}$ = 2.3 Ω, L_σ = 12 nH, diode: body diode at V_{GS} = 0 V	T_{vj} = 25 °C		20.9		ns
			T_{vj} = 175 °C		15.9		
Rise time	t_r	V_{DD} = 800 V, I_D = 93 A, V_{GS} = 0/18 V, $R_{G,ext}$ = 2.3 Ω, L_σ = 12 nH, diode: body diode at V_{GS} = 0 V	T_{vj} = 25 °C		13.9		ns
			T_{vj} = 175 °C		12.3		
Turn-off delay time	$t_{d(off)}$	V_{DD} = 800 V, I_D = 93 A, V_{GS} = 0/18 V, $R_{G,ext}$ = 2.3 Ω, L_σ = 12 nH, diode: body diode at V_{GS} = 0 V	T_{vj} = 25 °C		42		ns
			T_{vj} = 175 °C		49.1		
Fall time	t_f	V_{DD} = 800 V, I_D = 93 A, V_{GS} = 0/18 V, $R_{G,ext}$ = 2.3 Ω, L_σ = 12 nH, diode: body diode at V_{GS} = 0 V	T_{vj} = 25 °C		18.4		ns
			T_{vj} = 175 °C		21.6		
Turn-on energy	E_{on}	V_{DD} = 800 V, I_D = 93 A, V_{GS} = 0/18 V, $R_{G,ext}$ = 2.3 Ω, L_σ = 12 nH, diode: body diode at V_{GS} = 0 V	T_{vj} = 25 °C		1228		µJ
			T_{vj} = 175 °C		1949		
Turn-off energy	E_{off}	V_{DD} = 800 V, I_D = 93 A, V_{GS} = 0/18 V, $R_{G,ext}$ = 2.3 Ω, L_σ = 12 nH, diode: body diode at V_{GS} = 0 V	T_{vj} = 25 °C		1013		µJ
			T_{vj} = 175 °C		1227		
Total switching energy[1)]	E_{tot}	V_{DD} = 800 V, I_D = 93 A, V_{GS} = 0/18 V, $R_{G,ext}$ = 2.3 Ω, L_σ = 12 nH, diode: body diode at V_{GS} = 0 V	T_{vj} = 25 °C		2559		µJ
			T_{vj} = 175 °C		4249		

（表格续下页……）

表 4　　（续） 特征值

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Turn-on energy at -5 V	E_{on}	V_{DD} = 800 V, I_D = 93 A, V_{GS} = -5/18 V, $R_{G,ext}$ = 2.3 Ω, L_σ = 12 nH, diode: body diode at V_{GS} = -5 V	T_{vj} = 25 °C		1228		µJ
			T_{vj} = 175 °C		1980		
Turn-off energy at -5 V	E_{off}	V_{DD} = 800 V, I_D = 93 A, V_{GS} = -5/18 V, $R_{G,ext}$ = 2.3 Ω, L_σ = 12 nH, diode: body diode at V_{GS} = -5 V	T_{vj} = 25 °C		570		µJ
			T_{vj} = 175 °C		623		
Total switching energy at -5 V 1)	E_{tot}	V_{DD} = 800 V, I_D = 93 A, V_{GS} = -5/18 V, $R_{G,ext}$ = 2.3 Ω, L_σ = 12 nH, diode: body diode at V_{GS} = -5 V	T_{vj} = 25 °C		2116		µJ
			T_{vj} = 175 °C		3705		
Virtual junction temperature	T_{vj}			-55		175	°C
Virtual junction temperature	$T_{vj(over)}$	overload, cumulative max. 100 h 2)				200	°C

1)　包括 E_{fr}
2)　最多 5000 次循环。最大ΔT 限制为 100 K。

注： *芯片技术的特征是高达200 kV/µs。测量的dV/dt 受到测量测试设置和封装的限制。*

除非另有规定，特性均在 T_{vj} = 25°C 的条件下测得。

3　体二极管（MOSFET）

表 5　　最大额定值

Parameter	Symbol	Note or test condition		Values	Unit
Drain-source voltage	V_{DSS}	T_{vj} ≥ 25 °C		1200	V
Continuous reverse drain current for $R_{th(j-c,max)}$, limited by $T_{vj(max)}$	I_{SDC}	V_{GS} = 0 V	T_c = 25 °C	137	A
			T_c = 100 °C	75	
Peak reverse drain current, t_p limited by $T_{vj(max)}$	I_{SM}	V_{GS} = 0 V		426	A

表 6　　特征值

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Drain-source reverse voltage	V_{SD}	I_{SD} = 93 A, V_{GS} = 0 V	T_{vj} = 25 °C		4.2	5.5	V
			T_{vj} = 100 °C		4.11		
			T_{vj} = 175 °C		4.05		
MOSFET forward recovery charge	Q_{fr}	V_{DD} = 800 V, I_{SD} = 93 A, V_{GS}=0 V, $R_{GS(on)}$ = 2.3 Ω, Q_{fr} includes also Q_C	T_{vj} = 25 °C		0.8		µC
			T_{vj} = 175 °C		2.5		
MOSFET peak forward recovery current	I_{frm}	V_{DD} = 800 V, I_{SD} = 93 A, V_{GS}=0 V, $R_{GS(on)}$ = 2.3 Ω, Q_{fr} includes also Q_C	T_{vj} = 25 °C		80		A
			T_{vj} = 175 °C		135		
MOSFET forward recovery energy	E_{fr}	V_{DD} = 800 V, I_{SD} = 93 A, V_{GS}=0 V, $R_{GS(on)}$ = 2.3 Ω, Q_{fr} includes also Q_C	T_{vj} = 25 °C		318		µJ
			T_{vj} = 175 °C		1073		
MOSFET forward recovery energy at -5 V	E_{fr}	V_{DD} = 800 V, I_{SD} = 93 A, V_{GS} = -5 V, $R_{GS(on)}$ = 2.3 Ω, Q_{fr} includes also Q_C	T_{vj} = 25 °C		318		µJ
			T_{vj} = 175 °C		1102		
Virtual junction temperature	T_{vj}			-55		175	°C
Virtual junction temperature	$T_{vj(over)}$	overload, cumulative max. 100 h *1)*				200	°C


1)　最多 5000 次循环。最大ΔT 限制为 100 K。

4 特性图

Safe operating area (SOA)


$I_D = f(V_{DS})$

$T_{vj} \leq 175\ °C$, $T_c = 25\ °C$




Power dissipation as a function of case temperature

$P_{tot} = f(T_c)$



Maximum DC drain to source current as a function of case temperature limited by bond wire


$I_D = f(T_c)$



Maximum source to drain current as a function of case temperature limited by bond wire

$I_{SD} = f(T_c)$

$V_{GS} = 0\ V$




4 特性图

Typical transfer characteristic

$I_D = f(V_{GS})$


$V_{DS} = 20$ V, $t_p = 20$ µs



Typical gate-source threshold voltage as a function of junction temperature

$V_{GS(th)} = f(T_{vj})$


$I_D = 29.1$ mA



Typical output characteristic, V_{GS} as a parameter

$I_D = f(V_{DS})$


$T_{vj} = 25$ °C, $t_p = 20$ µs



Typical output characteristic, V_{GS} as a parameter

$I_D = f(V_{DS})$

$T_{vj} = 175$ °C, $t_p = 20$ µs




4 特性图

Typical on-state resistance as a function of junction temperature

$R_{DS(on)} = f(T_{vj})$


$I_D = 93$ A



Typical gate charge

$V_{GS} = f(Q_G)$


$I_D = 93$ A, $V_{DS} = 800$ V



Typical capacitance as a function of drain-source voltage

$C = f(V_{DS})$


$f = 100$ kHz, $V_{GS} = 0$ V



Typical reverse drain voltage as a function of junction temperature

$V_{SD} = f(T_{vj})$


$I_{SD} = 93$ A, $V_{GS} = 0$ V



Typical reverse drain current as a function of reverse drain voltage, V_{GS} as a parameter

$I_{SD} = f(V_{SD})$


$T_{vj} = 25\ °C$, $t_p = 20\ µs$



Typical reverse drain current as a function of reverse drain voltage, V_{GS} as a parameter

$I_{SD} = f(V_{SD})$


$T_{vj} = 175\ °C$, $t_p = 20\ µs$



Typical switching energy as a function of junction temperature, test circuit in Fig. F, 2nd device own body diode: V_{GS} = 0 V

$E = f(T_{vj})$


$V_{GS} = 0/18\ V$, $I_D = 93\ A$, $R_{G,ext} = 2.3\ Ω$, $V_{DD} = 800\ V$



Typical switching energy as a function of junction temperature, test circuit in Fig. F, 2nd device own body diode: V_{GS} = -5 V

$E = f(T_{vj})$


$V_{GS} = -5/18\ V$, $I_D = 93\ A$, $R_{G,ext} = 2.3\ Ω$, $V_{DD} = 800\ V$



Typical switching energy as a function of drain current, test circuit in Fig. F, 2nd device own body diode: V_{GS} = 0 V

$E = f(I_D)$


V_{GS} = 0/18 V, T_{vj} = 175 °C, $R_{G,ext}$ = 2.3 Ω, V_{DD} = 800 V



Typical switching energy as a function of drain current, test circuit in Fig. F, 2nd device own body diode: V_{GS} = -5 V

$E = f(I_D)$


V_{GS} = -5/18 V, T_{vj} = 175 °C, $R_{G,ext}$ = 2.3 Ω, V_{DD} = 800 V



Typical switching energy as a function of gate resistance, test circuit in Fig. F, 2nd device own body diode: V_{GS} = 0 V

$E = f(R_{G,ext})$


V_{GS} = 0/18 V, I_D = 93 A, T_{vj} = 175 °C, V_{DD} = 800 V



Typical switching energy as a function of gate resistance, test circuit in Fig. F, 2nd device own body diode: V_{GS} = -5 V

$E = f(R_{G,ext})$

V_{GS} = -5/18 V, I_D = 93 A, T_{vj} = 175 °C, V_{DD} = 800 V




4 特性图

Typical switching energy as a function of DC link voltage, test circuit in Fig. F, 2nd device own body diode: V_{GS} = 0 V

E = f(V_{DD})


V_{GS} = 0/18 V, I_D = 93 A, T_{vj} = 175 °C, $R_{G,ext}$ = 2.3 Ω



Typical switching energy as a function of DC link voltage, test circuit in Fig. F, 2nd device own body diode: V_{GS} = -5 V

E = f(V_{DD})


V_{GS} = -5/18 V, I_D = 93 A, T_{vj} = 175 °C, $R_{G,ext}$ = 2.3 Ω



Typical switching times as a function of gate resistance, test circuit in Fig. F, 2nd device own body diode: V_{GS} = 0 V

t = f($R_{G,ext}$)


V_{GS} = 0/18 V, I_D = 93 A, T_{vj} = 175 °C, V_{DD} = 800 V



Typical reverse recovery charge as a function of reverse drain current slope, test circuit in Fig. F, 2nd device own body diode: V_{GS} = 0 V

Q_{fr} = f(-di_{SD}/dt)


V_{GS} = 0/18 V, I_{SD} = 93 A, V_{DD} = 800 V



Typical reverse recovery current as a function of reverse drain current slope, test circuit in Fig. F, 2nd device own body diode: V_{GS} = 0 V

$I_{frm} = f(-di_{SD}/dt)$


V_{GS} = 0/18 V, I_{SD} = 93 A, V_{DD} = 800 V



Typical switching energy as a function of dead time / blanking time, test circuit in Fig. F, 2nd device own body diode: V_{GS} = 0 V

$E = f(t_{dead})$


I_D = 93 A, V_{GS} = 0/18 V, T_{vj} = 175 °C, $R_{G,ext}$ = 2.3 Ω V_{DD} = 800 V




Max. transient thermal impedance (MOSFET/diode)

$Z_{th(j-c),max} = f(t_p)$

$D = t_p/T$



5 封装外形



PACKAGE - GROUP NUMBER:	PG-TO247-4-U07				
DIMENSIONS	MILLIMETERS		DIMENSIONS	MILLIMETERS	
	MIN.	MAX.		MIN.	MAX.
A	4.90	5.10	E	15.60	16.00
A1	1.90	2.10	E1	13.10	13.50
A2	1.50	1.70	E2	0.60	1.20
A3	2.16	2.36	E3	2.48	2.68
A4	2.31	2.51	E4	9.05	9.25
b	0.60	0.80	E5	3.97	4.17
b1	1.10	1.30	E6	1.80	2.20
b2	---	0.15	e	5.08	
b3	1.10	1.30	e1	2.79	
b4	1.90	2.10	e2	2.54	
c	0.50	0.70	K	3.50	---
D	23.10	23.50	L	17.50	17.80
D1	16.25	16.85	L1	2.61	2.91
D2	0.97	1.37	N	4	
D3	6.00	6.30	ØP1	7.00	7.40
D4	2.50	2.70	ØP	3.50	3.70
D5	2.30	2.70	ØU	1.40	1.80

NOTES: DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSION OR GATE BURRS
N IS THE NUMBER OF LEADS

图 1

6 测试条件




Figure A. **Definition of switching times**




Figure B. **Definition of body diode switching characteristics**




Figure C. **Definition of switching losses**




Figure D. **Definition of QGD**




Figure E. **Thermal equivalent circuit**




Figure F. **Dynamic test circuit**
Parasitic inductance L_σ,
Parasitic capacitor C_σ,

图 2

修订记录

Document revision	Date of release	Description of changes
0.10	2025-01-17	Preliminary datasheet
1.00	2025-04-28	Final datasheet
1.10	2025-09-22	Increased I_{DM} in Table 2 Added switching information for V_{GS} = -5/18 V in Table 4 and 6 and corresponding diagrams Added I_{SDC} in Table 5 Added SOA diagram on page 8 Added diagram E = f(V_{DD}) @ V_{GS} = 0/18 V Added diagram E = f(V_{DD}) @ V_{GS} = -5/18 V Editorial changes
1.20	2026-07-27	Correction of the internal gate resistance in Table 4 Correction of switching times and energies in Table 4 and corresponding diagrams Correction of Q_{fr}, I_{frm} and E_{fr} in Table 6 and corresponding diagrams Updated I_{DSS} max in Table 4

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2026-07-27

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2026 Infineon Technologies AG

All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference

IFX-ABL318-004

Important notice

Products which may also include samples and may be comprised of hardware or software or both ("Product(s)") are sold or provided and delivered by Infineon Technologies AG and its affiliates ("Infineon") subject to the terms and conditions of the frame supply contract or other written agreement(s) executed by a customer and Infineon or, in the absence of the foregoing, the applicable Sales Conditions of Infineon. General terms and conditions of a customer or deviations from applicable Sales Conditions of Infineon shall only be binding for Infineon if and to the extent Infineon has given its express written consent.

For the avoidance of doubt, Infineon disclaims all warranties of non-infringement of third-party rights and implied warranties such as warranties of fitness for a specific use/purpose or merchantability. Infineon shall not be responsible for any information with respect to samples, the application or customer's specific use of any Product or for any examples or typical values given in this document.

If this document is marked as 'Preliminary', 'Target', 'Draft' or 'Proposal', Infineon reserves the right to change all information given in this document at any time without notice. Subject to the development and release of a Product for series supply by Infineon, the technical specifications of the Product are set forth in the relevant datasheet provided by Infineon without such marking.

The data contained in this document is exclusively intended for technically qualified and skilled customer representatives. It is the responsibility of the customer to evaluate the suitability of the Product for the intended application and the customer's specific use and to verify all relevant technical data contained in this document in the intended application and the customer's specific use. The customer is responsible for properly designing, programming, and testing the functionality and safety of the intended application, as well as complying with any legal requirements related to its use.

Unless otherwise explicitly approved by Infineon, Products may not be used in any application where a failure of the Products or any consequences of the use thereof can reasonably be expected to result in personal injury.

However, the foregoing shall not prevent the customer from using any Product in such fields of use that Infineon has explicitly designed and sold it for, provided that the overall responsibility for the application lies with the customer. Infineon expressly reserves the right to use its content for commercial text and data mining (TDM) according to applicable laws, e.g. Section 44b of the German Copyright Act (UrhG). If the Product includes security features:

Because no computing device can be absolutely secure, and despite security measures implemented in the Product, Infineon does not guarantee that the Product will be free from intrusion, data theft or loss, or other breaches ("Security Breaches"), and Infineon shall have no liability arising out of any Security Breaches.

If this document includes or references software: The software is owned by Infineon under the intellectual property laws and treaties of the United States, Germany, and other countries worldwide. All Rights Reserved. Therefore, you may use the software only as provided in the software license agreement accompanying the software.

If no software license agreement applies, Infineon hereby grants you a personal, non-exclusive, non-transferable license (without the right to sublicense) under its intellectual property rights in the software (a) for software provided in source code form, to modify and reproduce the software solely for use with Infineon hardware products, only internally within your organization, and (b) to distribute the software in binary code form externally to end users, solely for use on Infineon hardware products. Any other use, reproduction, modification, translation, or compilation of the software is prohibited.

For further information on the Product, technology, delivery terms and conditions, and prices, please contact your nearest Infineon office or visit www.infineon.com.

免责声明

请注意，本文件的原文使用英文撰写，为方便客户浏览英飞凌提供了中文译文。该中文译文仅供参考，并不可作为任何论点之依据。
由于翻译过程中可能使用了自动化程序，以及语言翻译和转换过程中的差异，最后的中文译文与最新的英文版本原文含义可能存在不尽相同之处。
因此，我们同时提供该中文译文版本的最新英文原文供您阅读，请参见 http://www.infineon.com
英文原文和中文译文版本之间若存有任何歧异，以最新的英文版本为准，并且仅认可英文版本为正式文件。
您如果使用本文件，即表示您同意并理解上述说明。英飞凌不对因翻译过程中可能存在的任何不完整或不准确信息而产生的任何直接或间接损失或损害负责。英飞凌不承担中文译文版本的完整性和准确性责任。如果您不同意上述说明，请不要使用本文件。

Trademarks
All referenced product or service names and trademarks are the property of their respective owners.

版本 **2026-09-28**

Infineon Technologies AG 出版，
德国 **Neubiberg 85579**

版权 © **2026 Infineon Technologies AG**
及其关联公司。
保留所有权利。

Do you have a question about this document?

Email:

erratum@infineon.com

重要通知

Infineon Technologies AG 及其关联公司（以下简称 "英飞凌"）销售或提供和交付的产品（可能也包括样品，且可能由硬件或软件或两者组成）（以下简称 "产品"），应遵守客户与英飞凌签订的框架供应合同或其他书面协议的条款和条件，如无上述合同或其他书面协议，则应遵守适用的英飞凌销售条件。只有在英飞凌明确书面同意的情况下，客户的一般条款和条件或对适用的英飞凌销售条件的偏离才对英飞凌具有约束力。

为避免疑义，英飞凌不承担不侵犯第三方权利的所有保证和默示保证，例如对特定用途/目的的适用性或适销性的保证。

英飞凌对与样品、应用或客户对任何产品的具体使用有关的任何信息或本文档中给出的任何示例或典型值概不负责。

本文件中包含的数据仅供具有技术资格和技能的客户代表使用。客户有责任评估产品对预期应用和客户特定用途的适用性，并在预期应用和客户特定用途中验证本文件中包含的所有相关技术数据。客户有责任正确设计、编程和测试预期应用的功能性和安全性，并遵守与其使用相关的法律要求。

除非英飞凌另行明确批准，否则产品不得用于任何因产品故障或使用产品的任何后果可合理预期会导致人身伤害的应用。但是，上述规定并不妨碍客户在英飞凌明确设计和销售的使用领域中使用任何产品，但是客户对应用负有全部责任。

英飞凌明确保留根据适用法律，如《德国版权法》（UrhG）第 44b 条，将其内容用于商业资料和数据探勘（TDM）的权利。

如果产品包含安全功能：
由于任何计算设备都不可能绝对安全，尽管产品采取了安全措施，但英飞凌不保证产品不会被入侵、数据不会被盗或遗失，或不会发生其他漏洞（以下简称"安全漏洞"），英飞凌对任何安全漏洞不承担任何责任。

如果本文档包含或引用软件：
根据美国、德国和世界其他国家的知识产权法律和条约，该软件归英飞凌所有。英飞凌保留所有权利。因此，您只能按照软件附带的软件授权协议的规定使用本软件。

如果没有适用的软件授权协议，英飞凌特此授予您个人的、非排他性的、不可转让的软件知识产权授权（无权转授权）：(a) 对于以源代码形式提供的软件，仅在贵组织内部修改和复制该软件用于英飞凌硬件产品；及 (b) 对于以二进制代码(binary code)形式对外向终端用户分发该软件，仅得用于英飞凌硬件产品。禁止对本软件进行任何其他使用、复制、修改、翻译或编译。有关产品、技术、交货条款和条件以及价格的详细信息，请联系离您最近的英飞凌办公室或访问 **https://www.infineon.com**。