
Bauteilname/Part Name:	***5808 EXT-Bat D01***			
Artikelnummer/Part Number:	-			
Author: Autor:	*SteffenKurmis*	Date of last revision: Datum der letzten Revision:	*25. 05. 2019*	*SK*
Release: Freigabe:		Date: Datum:		
Revision:	*D01*			
Confidentiality: Vertraulichkeit:	confidential			
Related documents:				
Mitgeltende Dokumente:				

Document History/ Dokumentenhistorie:			
Revision (R) Draft (D)	Modification / Änderung	Date Datum	Author Autor
D01	***5808 EXT-Bat D01***	*25. 05. 2019*	*SK*

1. Image of an example



2. Material

Magnetic Core:	Toroid Core 20,5x11,5x29mm Z=132Ohm
Core material:	Würth Elektronik 74270056
Conductor material:	Ölflex Heat 180SiF 6mm^2 black
Coil form:	
Isolation:	

3. Isolation Requirements

Creepage distance:	
Temperature class IEC85:	class B
Approval of the materials as „UL recognized component“:	
Inflammability of plastic parts:	UL-V1 or better
Comparative Tracking Index (CTI):	group III or better


4. Windings/ Construction

4.1. Winding table:

Pin		Number of turns	Z [Ohm]	Conductor	Winding	Comment
Start	End					
PCB-X8	Front Panel Bat-	1	132	Ölflex Heat 180SiF 6mm^2 black	P1	Single layer
PCB-X9	Front Panel Bat+	1	132	Ölflex Heat 180SiF 6mm^2 black	P2	Single layer

4.2. Sketch of Windings: n.a.

4.3. Sketch of Pin-Layout:



5. Checks

Inductance: yes [@10kHz], Tolerance: +/-25%
Turns ratio:
Test voltage: