Release Notes

MCE Software Package

MCE Software V1.03.01 for IMC102T-F064
iMOTION ™ Platform Turnkey Software

Summary

Product Name	MCE_IMC102T-F064_V1.03.01.zip
Release Version	V1.03.01
Type Of Release	Release Candidate
Name of the Supplier	Infineon Technologies
Mode of Release	Infineon Server (http://www.infineon.com/iMOTION)
Date of Release	2020-04-16
Previous Versions	- V1.02.01 - V1.01.05 - V1.01.00 - V1.00.00 -

Table of contents

Summary . . . 1

Table of contents . . . 1

1 Released Items . . . 2

1.1 Artifacts . . . 2

1.2 Test Environment . . . 3

1.3 Changes and Enhancements . . . 3

1.4 Limitations and Deviations . . . 3

2 Supported Tools and Packages . . . 4

2.1 Tools . . . 4

3 Revision History . . . 4

3.1 Revision V1.02.01 . . . 4

3.2 Revision V1.01.05 . . . 4

3.3 Revision V1.01.00 . . . 5

3.4 Revision V1.00.00 . . . 5

Disclaimer . . . 6

1 Released Items

This chapter lists the artifacts, the items of the test package and the test environment. It also presents the changes in the current version, the limitations and deviations as well as the known issues.

The iMOTION2.0 MCE addressing 3-phase Permanent Magnet Synchronous Motor (PMSM) control using Sensorless/Hall sensor based Field Oriented Control (FOC) schemes and Power Factor Correction (PFC). This software is primarily targeted for end applications of industrial/consumer drives, pumps, and compressors.

List of Features

- PFC: Cycle-by-Cycle over-current protection for boost mode PFC and Vac peak detection
- Interface: Scripting based configurable UART driver
- Motor Control: Motor peak current tracking for single shunt configuration when phase shift window is set to zero
- Analog Hall: ArcTan based rotor angle estimation added
- Motor Control: Duty Control scheme has been removed. Duty control mode can be realized using scripting function
- System: CPU Internal oscillator calibration at runtime based on internal temperature sensor
- Motor Control: Hall sensor support : 3/2 Digital hall and 2 Analog hall
- Motor Control: Low noise phase shift PWM for single shunt motor current measurement
- System: IEC/UL60730-1 ClassB support
- Scripting: Scripting language support
- Sensorless FOC control: High performance sensorless Field Oriented Control (FOC) of Permanent Magnet Synchronous Motor.
- Sensorless FOC control: Angle sensing for initial rotor angle detection.
- Sensorless FOC control: Startup schemes: Parking, Open loop and Catch-Spin free running motor.
- Motor Control: Single shunt or leg shunt motor current sensing.
- Motor Control: Support 3ph and 2ph PWM modulation.
- PFC Control: Supports Boost Mode and Totem-Pole Power Factor Correction (PFC).

1.1 Artifacts

This release V1.03.01 consists of the following artifacts:

Artifact	Description
IMC102T_F064_A_V1.03.01.ldf	Encrypted binary file for IMC102T-F064 device.
IMC102T_V1.03.01.irc	MCEDesigner project file. MCEDesigner tool is used to program binary file and control parameter configuration.
IMC102T-F064_Parameter.txt	Sample parameter file, generated from MCEWizard.
IMC102T-F064_V1.03.01_Default.map	Default MCEDesigner map file, to reset the Design_ID value
iMOTION_Software_License_Agreement.pdf	License agreement document.
IMC102T-F064_V1.03.01_ReleaseNotes.pdf	This release note.
Readme.txt	Readme file brief description of how to use tools.

1.2 Test Environment

The MCE software was tested, using the following environment.

- Control Board: EVAL-M3-102T
- Power Board: Eval-M3-CM615PN
- Motor Specification: 8Pole, 0.4A R=38.5ohm, Lq= 196mH, Ld=196mH, Ke= 36V, 2730 RPM

1.3 Changes and Enhancements

The following items have been changed in release V1.03.01. Please refer to the ***revision history*** for previous versions.

Features

- PFC: Cycle-by-Cycle over-current protection for boost mode PFC and Vac peak detection
- Interface: Scripting based configurable UART driver
- Motor Control: Motor peak current tracking for single shunt configuration when phase shift window is set to zero
- Analog Hall: ArcTan based rotor angle estimation added
- Motor Control: Duty Control scheme has been removed. Duty control mode can be realized using scripting function
- System: CPU Internal oscillator calibration at runtime based on internal temperature sensor

Enhancements

- Hall Support: PLL based rotor angle estimation for hall sensor has been added.
- Scripting: Read and write rate of user GPIO via scripting has been changed from 10ms to 1ms.
- Scripting: Access rate of user analog input via scripting has been changed from 10ms to 1ms
- Motor Control: Control input (Frequency/duty cycle) values are accessed from scripting

Bug Fixes

- Interface: User UART command3 issue fixed. Command #3 set motor start command if TargetSpeed value is non zero value and set motor stop command if TargetSpeed value is zero.
- Motor Control: IPM motor control, Id reference value. generation issue has been fixed. Id reference value is generated based on “AngDel” parameter value.
- Motor Control: Over modulation issue for leg shunt configuration has been fixed.
- Motor Control: Unwanted active vector PWM after BTS charge has been fixed.

1.4 Limitations and Deviations

This section lists features that are missing or were incompletely implemented in the current release, but may be provided in future releases.

- Sensorless FOC: Limited up to 150% rated speed field weakening and requires further tuning for higher operation
- FOC: 2Phase modulation only Type3 is supported
- PFC: Tracking mode PFC is not supported
- Hall Support: Analog Hall is not supported for leg shunt configuration
- Analog Hall: Only 2 Analog Hall interface is supported
- Control Input: Control Input via Frequency or Duty control input is not supported in case of Hall sensor or Hybrid mode

- FOC: Angle sensing startup method can't be used when Low noise phase shift PWM for single shunt motor current measurement is enbled
- System: Revised Class B certification is pending

2 Supported Tools and Packages

The following items are compatible with the current release.

2.1 Tools

Tool	Description
MCEWizard (V2.3.0.0)	MCEWizard is an interactive design tool that calculates control IC parameters in digital counts based on the system specifications expressed in engineering units.
MCEDesigner (V2.3.0.0)	MCEDesigner is the drive evaluation software that communicates with the digital IC and allows on the fly tuning of drive parameters.

3 Revision History

This chapter lists the changes and enhancements of the previous releases.

3.1 Revision V1.02.01

Features

- Motor Control: Hall sensor support : 3/2 Digital hall and 2 Analog hall
- Motor Control: Low noise phase shift PWM for single shunt motor current measurement

Enhancements

- Interface: Lock/unlock mechanism to update STATIC parameters from MCEDesigner
- System: CPU load peak value capture function

Bug Fixes

- Motor Control: Sensorless FOC: Flux estimator angle compensation problem has been fixed. No need to double the "ATanTau" parameter for those who had manually adjusted it before.

3.2 Revision V1.01.05

Bug Fixes

- Motor Control: System went into failsafe mode with Class B enabled or flagged execution fault with Class B disabled when configured PWM frequency is more than 20 kHz. This issue has been fixed.
- Motor Control: Current offset calculation was performed every time when motor enters into stop state. This doesn’t allow to perform multiple startup in a very short time interval. This issue has been fixed. Current offset calculation is performed once after power on reset.
- Motor Control: Zero vector PWM is applied after BTS charging instead of switch on low side switch.

- Motor Control: It was not possible to set negative value to “OpenLoopAngle” variable and “ParkAngle” parameter from MCEDesigner/Scripting. This issue has been fixed. These registers input range is updated [-32768 : 32767] as per MCE Software reference manual.
- PFC: Overcurrent condition was not detected when over current occurs during startup time. This issue has been fixed
- Scripting: Coherent update of variables index values more than 127 was not working. This issue has been fixed.
- .irc File: Parameters and variables names in read group are updated as per MCE Software Reference manual.

3.3 Revision V1.01.00

Features

- System: IEC/UL60730-1 ClassB support
- Scripting: Scripting language support

3.4 Revision V1.00.00

Features

- Sensorless FOC control: High performance sensorless Field Oriented Control (FOC) of Permanent Magnet Synchronous Motor.
- Sensorless FOC control: Angle sensing for initial rotor angle detection.
- Sensorless FOC control: Startup schemes: Parking, Open loop and Catch-Spin free running motor.
- Motor Control: Single shunt or leg shunt motor current sensing.
- Motor Control: Support 3ph and 2ph PWM modulation.
- PFC Control: Supports Boost Mode and Totem-Pole Power Factor Correction (PFC).

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2020-04-16

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2020 Infineon Technologies AG

All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference
IFX-iMOTION-mce4.600r017RN

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”) .

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer’s compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer’s products and any use of the product of Infineon Technologies in customer’s applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer’s technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies’ products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury