NRG™ SLE 66R35E7 with 7-byte UID

Features

- Intelligent 1 KB memory chip with NRG™ (ISO/IEC 14443-3 Type A with CRYPTO1) compatibility and 7-byte unique identification number
- Physical interface and anticollision compliant to ISO/IEC 14443-2 and -3 Type A
  - Operation frequency 13.56 MHz; data rate 106 kbit/s
  - Contactless transmission of data and supply energy
  - Anticollision logic: several cards may be operated in the field simultaneously
  - Features Short-Cut Anticollision scheme to realize backward compatibility to installed infrastructures supporting 4-byte single size UIDs only
- Read and write distance up to 10 cm and more (influenced by external circuitry that is reader and inlay design)
- Short transaction times: typical ticketing transaction <100 ms; transaction possible when card is moving

Applications

- Weekly or seasonal cards for automatic fare collection (AFC)
- Event ticketing
- Access Control
- Micropayment

1 System overview

The system consists of a host system, which is a contactless Read/Write Device connected to a background system, the antenna and one or more NRG™ SLE 66R35E7 based tags or other ISO/IEC 14443-3 Type A compliant cards.




Figure 1 System overview

1.1 Description

The system consists of a smart card and a card reader together with an antenna. The card's antenna consists of a simple coil with a few turns embedded in plastic. The operating distance between card and reader antenna is up to 10 cm and more (influenced by external circuitry i.e. reader-antenna configuration).

The RF communication interface transmits at 106 kbit/s resulting in short transaction times, the effect being that a card user can move freely through a reader gate with minimum disruption. A typical ticketing transaction can be handled in less than 100 ms. Robust contactless transmission means that the card with NRG™ SLE 66R35E7 may also remain in the wallet of the user even if there are coins in it.

An intelligent anticollision function based on the chip single size identifier (uid0 – uid3) enables more than one card in the field to operate simultaneously. The anticollision algorithm selects each card individually and ensures that the execution of a transaction with a selected card is performed correctly without data corruption resulting from other cards in the field.

The NRG™ SLE 66R35E7 is designed to operate in an NRG™ (ISO/IEC 14443-3 Type A with CRYPTO1) system. Each data transmission is enciphered. Protection from misuse is done by configurable access conditions that are protected by secret keys used for memory operations such as read or write.

Parametrics

Product name	NRG™ SLE 66R35E7
Product description	Intelligent 1 kByte Memory Chip with NRG™ (ISO/IEC 14443-3 Type A with CRYPTO1) compatibility
Interfaces	ISO/IEC 14443-3 Type A
Symmetrical cryptography	Mutual three-pass authentication between card and reader for basic security
Ambient temperature	-25 ... +70°C for the chip
System features	NRG™ (ISO/IEC 14443-3 Type A with CRYPTO1)
Delivery forms	Sawn wafer 120 or 150 µm, NiAu bump 20 µm MCC8-2-6 MCC2-2-1
Typical applications	Transport ticketing, Access Control systems, Automatic Fare Collection (AFC) systems and other smart card security applications

For further information on technology, delivery forms and conditions please contact your nearest Infineon Technologies sales representative (www.infineon.com)

Published by
Infineon Technologies AG
Am Campeon 1-15, 85579 Neubiberg
Germany

© 2025 Infineon Technologies AG
All rights reserved.

Public

Date: 07/2025

Please note!
This Document is for information purposes only and any information given herein shall in no event be regarded as a warranty, guarantee or description of any functionality, conditions and/or quality of our products or any suitability for a particular purpose. With regard to the technical specifications of our products, we kindly ask you to refer to the relevant product data sheets provided by us. Our customers and their technical departments are required to evaluate the suitability of our products for the intended application.

We reserve the right to change this document and/or the information given herein at any time.

Additional information
For further information on technologies, our products, the application of our products, delivery terms and conditions and/or prices, please contact your nearest Infineon Technologies office (www.infineon.com).

Warnings
Due to technical requirements, our products may contain dangerous substances. For information on the types in question, please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by us in a written document signed by authorized representatives of Infineon Technologies, our products may not be used in any life-endangering applications, including but not limited to medical, nuclear, military, life-critical or any other applications where a failure of the product or any consequences of the use thereof can result in personal injury.

Scan QR code and explore offering
www.infineon.com