TEGRION™ SLC27TDx for transport applications

SOLID FLASH™

Description

The TEGRION™ SLC27TDx products are high-performance dual interface security crypto controllers optimized for the Transport Ticketing use cases. They offer state-of-the-art CPU architecture featuring 32-bit Arm® v8-M based core and the Integrity Guard 32 dual CPU, allowing rapid communication and ultra-low power consumption. The family concept enables asset re-use, a faster time-to-market and innovative delivery forms.

Features

- High-performance 32-bit CPU based on Arm® v8-M with Main Extension and Security Extension (Arm® TrustZone for Arm v8-M)
- Integrity Guard 32 security is an architectural concept based on the Arm® v8-M instruction set, enhanced by Infineon's security technology
- SOLID FLASH™ NVM Technology with strong IP protection and EEPROM emulation support
- Cryptographic support:
  - High-speed coprocessors for symmetric (AES and 3-DES) and asymmetric cryptography (RSA and ECC) including certified libraries
  - Random Number Generator (RNG) supporting true random number generation according to the BSI AIS20/31 for class PTG.2 and PTG.3
  - Strong integrity support by mathematically modelled techniques
  - Strong confidentiality support by sophisticated cryptographic techniques, including extensive protection for the memory, caches, buses and registers
- Supported interfaces: Contact base interface UART acc. to ISO/IEC 7816-3 and contactless interface (RFI)
- Support of contactless protocols: ISO/IEC 14443 Type A/B with HBR and optionally NRG™ (ISO/IEC 14443-3 Type A with CRYPTO1 and Type B)
- Cryptographic support: RSA, ECC, AES, DES, RNG
- 200 KB user SOLID FLASH™ NVM and 20 KB RAM
- 4 KB instruction cache, 1 KB data cache
- Certification level: CC EAL6+

Applications

- Transport and Ticketing applications
- Global Platform / Java Card / Native
- ePurse
- New form factors like passive wearables devices

Parametrics

Product name	TEGRION™ SLC27TDx200AT / SLC27TDx200AS
Product description	TEGRION™ SLC27TDx security crypto controller for transport ticketing applications. TEGRION™ SLC27TDx[1]200AT (27 pF) / SLC27TDx[1]200AS (56 pF): [1]L with NRG; A no NRG
Interfaces and protocols	ISO/IEC 7816, ISO/IEC 14443 A/B, ISO/IEC 18092 (NFC passive mode) Optionally NRG™ (ISO/IEC 14443-3 type A/B with CRYPTO1)
Memory	200 KB SOLID FLASH™; 20 KB RAM
Symmetrical cryptography	DES, 3DES, AES up to 256-bit
Asymmetrical cryptography	RSA up to a bit length of 4096, ECC up to a bit length of 521
Ambient temperature	-25°C to +85°C
Delivery forms	Wafer, dual interface and contactless modules
Typical applications	Transport, ticketing and access applications, also for new form factors like passive wearables devices
Certification level	CC EAL6+

For further information on technology, delivery forms and conditions please contact your nearest Infineon Technologies sales representative (www.infineon.com)

Published by
Infineon Technologies AG
Am Campeon 1-15, 85579 Neubiberg
Germany

© 2026 Infineon Technologies AG
All rights reserved.

Public

Date: 01/2026

Please note!
This Document is for information purposes only and any information given herein shall in no event be regarded as a warranty, guarantee or description of any functionality, conditions and/or quality of our products or any suitability for a particular purpose. With regard to the technical specifications of our products, we kindly ask you to refer to the relevant product data sheets provided by us. Our customers and their technical departments are required to evaluate the suitability of our products for the intended application.

We reserve the right to change this document and/or the information given herein at any time.

Additional information
For further information on technologies, our products, the application of our products, delivery terms and conditions and/or prices, please contact your nearest Infineon Technologies office (www.infineon.com).

Warnings
Due to technical requirements, our products may contain dangerous substances. For information on the types in question, please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by us in a written document signed by authorized representatives of Infineon Technologies, our products may not be used in any life-endangering applications, including but not limited to medical, nuclear, military, life-critical or any other applications where a failure of the product or any consequences of the use thereof can result in personal injury.

Scan QR code and explore offering
www.infineon.com