

CYW955913EVK-01 Evaluation Kit release notes

About this document

Scope and purpose

Thank you for your interest in the CYW955913EVK-01 CYW55913 Evaluation Kit. This document lists kit contents, installation requirements, kit documentation, and limitations.

Intended audience

This evaluation board is designed for technical specialists familiar with connectivity and is intended for use under laboratory conditions.



Table of contents

Table of contents

About this document 1

Table of contents 2

1 Release contents 3

1.1 Kit contents 3

2 Tool information 4

2.1 Software and tools 4

2.2 Code examples and kit collateral 4

2.3 Installation 4

2.4 Kit revision 4

2.5 Limitations 4

2.6 Documentation 4

2.7 Technical support 4

2.8 Additional information 5

Trademarks 6

Disclaimer 7

1 Release contents

1 Release contents

1.1 Kit contents

The CYW955913EVK-01 CYW55913 Evaluation Kit box includes the following:

1. CYW55913 Evaluation Board (CYW9CPM2BASE1 + CYW955913SDCM2WLIPA)
2. USB Type-C to Type-C cable
3. Two triband PCB antenna
4. Quick start guide

2 Tool information

2 Tool information

2.1 Software and tools

- Code examples for this kit require ModusToolbox™ software 3.2 or later. This is available on the [ModusToolbox™ software](#) webpage. See the kit guide for details.
- KitProg3 firmware v2.50 or later is required to program the AIROC™ CYW55913 Wi-Fi & Bluetooth® LE combo Connected MCU device on the kit. The ModusToolbox™ installer automatically installs KitProg3 drivers.

2.2 Code examples and kit collateral

The kit [webpage](#) includes the documents and hardware files. The code examples are available on the Infineon [GitHub repository](#).

2.3 Installation

All required software installation instructions are provided in the kit guide, which is available on the kit [webpage](#).

2.4 Kit revision

This is the initial revision (Rev. **) of the kit, including the Rev03 baseboard (CYW9CPM2BASE1, 600-60638-01) and the Rev4.1 M.2 Carrier Board (CYW955913SDCM2WLIPA, 600-90802-01).

2.5 Limitations

1. The BT_GPIO_16 and BT_GPIO_17 are used for USER_LED1, USER_LED2 and also connected to Arduino-compatible header pins J3.3 and J3.6 respectively. LEDs can be isolated from the GPIOs with switch SW5 when Arduino-compatible header pins are used.
2. LHL_GPIO_8 and LHL_GPIO_9 are connected to J2.5 and J2.7 and also to J3.4 and J3.5 respectively. Therefore, these Arduino-compatible pins cannot be used simultaneously. SW6 can be used to select between the connections. Also, Potentiometer(R1) is connected to LHL_GPIO_8 and need to be isolated using jumper configuration on the J10 header while using for other functions.
3. LHL_GPIO_2 and LHL_GPIO_3 are used for the peripheral UART and connected to the KitProg3 as a secondary UART port for logs. The same pins are also used for the Arduino-compatible header UART (J4.1 and J4.2). Select these connections by changing the tri-pad resister configurations.
See the Rework Section in the Kit User Guide for additional information.
4. Analog pins on the Arduino-compatible header J2 (A0-A3) support with only a 1.8 V level.

2.6 Documentation

The following kit documents are available on the kit [webpage](#).

- CYW955913EVK-01 CYW55913 Evaluation Kit guide
- CYW955913EVK-01 CYW55913 Evaluation Kit quick start guide
- CYW955913EVK-01 CYW55913 Evaluation Kit release notes

2.7 Technical support

For assistance, go to www.infineon.com/support. Visit community.infineon.com to ask your questions in the Infineon developer community.

2 Tool information

2.8 Additional information

- For more information about ModusToolbox™ software functionality and releases, visit the ModusToolbox™ software webpage: www.infineon.com/cms/en/design-support/tools/sdk/modustoolbox-software
- For a list of trainings on ModusToolbox™ software, visit www.github.com/Infineon/training-modustoolbox

Trademarks

Trademarks

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth® SIG, Inc., and any use of such marks by Infineon is under license.

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2026-03-24

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2026 Infineon Technologies AG

All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference

IFX-vqb1695871721273

Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.