P/N	SH	REV
610-90666-01	1	2.0

NOTES: UNLESS OTHERWISE SPECIFIED

1. SPECIFICATIONS/TOLERANCES:
   A. FABRICATE PER IPC-6012, CLASS 2, USING PROVIDED DATA FILES

   B. ALL SPECIFICATIONS USED SHALL BE PER THEIR LATEST REVISIONS.
   C. THE DIMENSIONS OF CIRCUIT FEATURES IN THE PROVIDED DATA MAY BE ADJUSTED ONLY TO COMPENSATE FOR PROCESS TOLERANCES; ADDING, REMOVING OR RELOCATING CIRCUIT FEATURES, INCLUDING NON-FUNCTIONAL PADS, IS NOT ALLOWED, AND THE DESIGN OF ALL PLANE STRUCTURES MUST BE MAINTAINED TO ENSURE PROPER ELECTRICAL PERFORMANCE.
   D. REMOVE ALL BURRS AND BREAK SHARP EDGES, .381 [.015] MAX RADIUS.
   E. PARENTHETICAL INFORMATION IS FOR REFERENCE ONLY.
   F. REPAIR OF PCB DEFECTS IS NOT PERMITTED.

2. DIELECTRIC MATERIAL:
   A. DIELECTRIC MATERIAL SHALL BE PER IPC-4101/99, /124, /126 OR /129 (RoHS COMPLIANT EPOXY-GLASS).
   B. MINIMUM DIELECTRIC THICKNESS SHALL BE .051 [.002] FOR REFERENCED STACK-UP DIMENSIONS OF.076 [.003] OR GREATER; IPC-6012 REQUIREMENTS SHALL OTHERWISE APPLY. SINGLE-PLY CONSTRUCTION IS ALLOWED.
   C. SEE LAYER STACK-UP FOR REQUIRED COPPER WEIGHTS AND THE FINISHED PCB THICKNESS. IF SPECIFIED, 1/3 OZ. STARTING FOIL MAY BE ACHIEVED BY 1/2 OZ. FOIL REDUCTION.
   D. FINISHED PCB THICKNESS SHALL BE MEASURED OVER LANDS AND/OR CONDUCTORS NOT COVERED BY SOLDER MASK.

3. DRILLING:
   A. VIA DIAMETERS (TOL. = +.051/- DRILL DIAMETER [+.0020/- DRILL DIAMETER]) SHALL BE VERIFIED BEFORE PLATING; ALL OTHER HOLE DIAMETERS SHALL BE VERIFIED AT FINAL INSPECTION.
   B. LAYER-TO-LAYER MISREGISTRATION SHALL BE .127 [.005] MAXIMUM.
   C. FILL ALL THRU VIAS AT PASTE USING NON-CONDUCTIVE EPOXY AND OVERPLATE WITH COPPER, .005 [.0002] MINIMUM THICKNESS. DIMPLE DEPTH IN BGA PADS SHALL BE .025 [.001] MAXIMUM. THE PRESENCE OF WRAP PLATING SHALL BE VISUALLY EVIDENT IN ALL QUALITY CONFORMANCE MICROSECTIONS; NO MINIMUM MEASUREMENT REQUIRED.
   D. FILL ALL MICROVIAS WITH COPPER PLATING OR NON-CONDUCTIVE EPOXY; DIMPLE DEPTH IN BGA PADS SHALL BE .025 [.001] MAXIMUM. FOR EPOXY FILL, OVERPLATE WITH COPPER, .005 [.0002] MINIMUM AND THE PRESENCE OF WRAP PLATING SHALL BE VISUALLY EVIDENT IN ALL QUALITY CONFORMANCE MICROSECTIONS; NO MINIMUM MEASUREMENT REQUIRED.
   E. FILL ALL BURIED VIAS USING NON-CONDUCTIVE EPOXY AND OVERPLATE WITH COPPER, .005 [.0002] MINIMUM THICKNESS. THE PRESENCE OF WRAP PLATING SHALL BE VISUALLY EVIDENT IN ALL QUALITY CONFORMANCE MICROSECTIONS; NO MINIMUM MEASUREMENT REQUIRED.

4. SOLDER MASK:
   A. APPLY LPI SOLDER MASK USING PROVIDED DATA.
   B. SOLDER MASK SHALL BE PER IPC-SM-840, CLASS T, COLOR GREEN.
   C. THE DIMENSIONS OF SOLDER MASK-DEFINED PADS ON PLANES AND/OR WIDE CONDUCTORS SHALL NOT BE MODIFIED.

5. MARKING:
   A. MARK PCB PER PROVIDED DATA USING SILKSCREEN OR AUTOMATED INJET PROCESSING WITH PERMANENT, NON-CONDUCTIVE INK, COLOR WHITE.
   B. SUPPLIER ID AND TRACEABILITY INFORMATION SHALL BE APPLIED USING PERMANENT, NON-CONDUCTIVE INK, COLOR WHITE.
   C. INK SHALL NOT BE APPLIED TO ANY SOLDERABLE SURFACE.

6. ELECTRICAL TEST:
   A. DESIGN VERIFICATION SHALL BE DONE PRIOR TO PCB FABRICATION USING SUPPLIED VALOR ODB++ DATABASE, OR GERBER DATA AND AN IPC-D-356 NETLIST.
   B. ALL PCBS SHALL BE 100% ELECTRICALLY TESTED FOR OPENS AND SHORTS USING PROVIDED DATA.
   C. APPLY TEST STAMP IN NON-LEGEND AREA ON REAR SIDE OF PCB; OK TO APPLY TO PANEL RAILS IF SPACE DOES NOT PERMIT.

7. FINAL FINISH:
   A. FINAL FINISH ON ALL EXPOSED CONDUCTORS SHALL BE IMMERSION SILVER PER IPC-4553, .15 - .38 MICROMETERS [6 - 15 MICROINCHES] THICK.

8. IMPEDANCE:
   A. IMPEDANCE TOLERANCE SHALL BE +/- 10%.
   B. SEE LAYER STACK-UP FOR IMPEDANCE REQUIREMENTS.

9. IF PANELIZATION SPECIFICATIONS ARE PROVIDED, THE PCBS SHALL BE DELIVERED IN PANEL FORM. HOWEVER, THESE SPECIFICATIONS MAY BE CHANGED AS REQUIRED BY THE CONTRACT MANUFACTURER TO SUPPORT VOLUME ASSEMBLY REQUIREMENTS.

REVISIONS						
ECO NO.	REV	DATE	DESCRIPTION	DRAWN	CHECKED	APPROVED
CLEU64	1.0	04/02/19	INITIAL RELEASE	YJUN	CLEU	CLEU
CLEU78	2.0	08/30/19	DESIGN UPDATE	YJUN	CLEU	CLEU



LAYER DESCRIPTION	START COPPER WT	SE IMP OHMS	SE REF LAYER	SE TRACE WIDTH	DIFF IMP OHMS	DIFF TRACE WIDTH/SPACE
L01 - TOP	3/8 OZ	50	1	.0130	90	.0055/.0140
L02 - PLANE	3/8 OZ	--	--	-----	---	----
L03 - SIGNAL	3/8 OZ	--	--	.-----	---	.-----/.-----
L04 - SIGNAL	0.5 OZ	--	--	.-----	---	.-----/.-----
L05 - SIGNAL	3/8 OZ	--	--	.-----	---	.-----/.-----
L06 - SIGNAL	0.5 OZ	--	---	.-----	---	.-----/.-----
L07 - PLANE	3/8 OZ	--	--	-----	---	----
L08 - BOTTOM	3/8 OZ	--	--	-----	90	.0055/.0140

STACK-UP

SEE BOM	SEE BOM
NEXT ASSY	USED ON
APPLICATION	

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND PROPRIETARY TO CYPRESS SEMICONDUCTOR CORPORATION AND SHALL NOT BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OR USED FOR ANY DESIGN, MANUFACTURE, OR OTHERWISE EXCEPT WHEN SUCH USER POSSESSES DIRECT, WRITTEN AUTHORIZATION FROM CYPRESS SEMICONDUCTOR CORPORATION.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN METRIC WITH INCHES IN BRACKETS
.XXX +.064 [±.005] .XX +.13 [±.01] ANGLES ±.5°

MATERIAL 2

FINISH 7

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN YJUN	08/30/19
ENGINEER CLEU	08/30/19
CHECKER CLEU	08/30/19
QA -	-
PROJ. ENG. -	-

CYPRESS

TITLE: PCB FABRICATION, CYW9BTAUDIO2

SIZE	CAGE CODE	P/N
D	-	610-90666-01

SCALE	SHEET	REV
1/1	1 OF 3	2.0

FAB NOTES REV 08/01/14

COMPUTER GENERATED DRAWING
DO NOT CHANGE MANUALLY

P/N	SH	REV
610-90666-01	2	2.0

REVISIONS

ECO NO.	REV	DATE	DESCRIPTION	DRAWN	CHECKED	APPROVED
CLEU64	1.0	04/02/19	INITIAL RELEASE	YJUN	CLEU	CLEU
CLEU78	2.0	08/30/19	DESIGN UPDATE	YJUN	CLEU	CLEU



DRILL CHART: TOP to L02_SIG
ALL UNITS ARE IN MILS

FIGURE	SIZE	TOLERANCE	PLATED	QTY
•	3.94	+1.97/-5.91	PLATED	109

DRILL CHART: L02_SIG to L03_SIG
ALL UNITS ARE IN MILS

FIGURE	SIZE	TOLERANCE	PLATED	QTY
•	3.94	+1.97/-5.91	PLATED	99

DRILL CHART: TOP to BOTTOM
ALL UNITS ARE IN MILS

FIGURE	SIZE	TOLERANCE	PLATED	QTY
•	5.91	+1.97/-5.91	PLATED	19
•	9.84	+1.97/-9.84	PLATED	445
•	39.0	+3.0/-3.0	PLATED	1
•	39.0	+3.0/-3.0	PLATED	3
▫	39.37	+2.95/-2.95	PLATED	74
◦	40.16	+3.0/-3.0	PLATED	2
○	66.9	+2.0/-2.0	NON-PLATED	4
▪	37.4x25.59	+5.0/-5.0	PLATED	2
▪	47.24x27.56	+5.0/-5.0	PLATED	2
▬	66.93x25.59	+1.97/-1.97	PLATED	4
▮	120.08x39.37	+2.95/-2.95	PLATED	1
▮	120.08x39.37	+2.95/-2.95	PLATED	1
▮	135.83x39.37	+2.95/-2.95	PLATED	1

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND PROPRIETARY TO CYPRESS SEMICONDUCTOR CORPORATION AND SHALL NOT BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OR USED FOR ANY DESIGN, MANUFACTURE, OR OTHERWISE EXCEPT WHEN SUCH USER POSSESSES DIRECT, WRITTEN AUTHORIZATION FROM CYPRESS SEMICONDUCTOR CORPORATION,

SIZE	CAGE CODE	P/N
D	-	610-90666-01
SCALE 1/1		SHEET 2 / REV 2.0

COMPUTER GENERATED DRAWING
DO NOT CHANGE MANUALLY