


Final datasheet

EconoDUAL™3 module with TRENCHSTOP™ IGBT7 and emitter controlled 7 diode and PressFIT / NTC / TIM

Features

- Electrical features
 - $V_{CES} = 1700\text{ V}$
 - $I_{C\text{ nom}} = 750\text{ A} / I_{CRM} = 1500\text{ A}$
 - Integrated temperature sensor
 - High current density
 - Low $V_{CE,sat}$
 - Overload operation up to 175°C
 - TRENCHSTOP™ IGBT7
 - $V_{CE,sat}$ with positive temperature coefficient
 - Enlarged diode for regenerative operation
 - Suitable Infineon gate drivers can be found under <https://www.infineon.com/gdfinder>
- Mechanical features
 - High power density
 - Isolated base plate
 - PressFIT contact technology
 - Standard housing
 - Pre-applied thermal interface material



Potential applications

- High-power converters
- Medium-voltage converters
- Motor drives
- Wind turbines
- Power transmission and distribution

Product validation

- Qualified for industrial applications according to the relevant tests of IEC 60747, 60749 and 60068

Description




Table of contents

	Description	1
	Features	1
	Potential applications	1
	Product validation	1
	Table of contents	2
1	Package	3
2	IGBT, Inverter	4
3	Diode, Inverter	6
4	NTC-Thermistor	7
5	Characteristics diagrams	8
6	Circuit diagram	13
7	Package outlines	14
8	Module label code	15
	Revision history	16
	Disclaimer	17

1 Package

Table 1 Insulation coordination

Parameter	Symbol	Note or test condition	Values	Unit
Isolation test voltage	V_{ISOL}	RMS, $f = 50 \text{ Hz}$, $t = 1 \text{ min}$	3.4	kV
Isolation test voltage NTC	$V_{ISOL(NTC)}$	RMS, $f = 50 \text{ Hz}$, $t = 1 \text{ min}$	3.4	kV
Material of module baseplate			Cu	
Internal isolation		basic insulation (class 1, IEC 61140)	Al_2O_3	
Creepage distance	$d_{\text{Creep nom}}$	terminal to baseplate, nom.	> 15	mm
Creepage distance	$d_{\text{Creep min}}$	terminal to baseplate, min.	14.7	mm
Creepage distance	$d_{\text{Creep nom}}$	terminal to terminal, nom.	> 19.3	mm
Creepage distance	$d_{\text{Creep min}}$	terminal to terminal, min.	19.3	mm
Clearance	$d_{\text{Clear nom}}$	terminal to baseplate, nom.	> 12.5	mm
Clearance	$d_{\text{Clear min}}$	terminal to baseplate, min.	12.5	mm
Clearance	$d_{\text{Clear nom}}$	terminal to terminal, nom.	> 10	mm
Clearance	$d_{\text{Clear min}}$	terminal to terminal, min.	9.6	mm
Comparative tracking index	CTI		> 200	
Relative thermal index (electrical)	RTI	housing	140	°C

Table 2 Characteristic values

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Stray inductance module	L_{sCE}				20		nH
Module lead resistance, terminals - chip	$R_{\text{CC'+EE'}}$	$T_{\text{H}} = 25\text{ }^{\circ}\text{C}$, per switch			0.8		mΩ
Storage temperature	T_{stg}			-40		125	°C
Maximum baseplate operation temperature	T_{BPmax}					150	°C
Mounting torque for module mounting	M	- Mounting according to valid application note	M5, Screw	3		6	Nm
Terminal connection torque	M	- Mounting according to valid application note	M6, Screw	3		6	Nm
Weight	G				345		g

Note: Storage and shipment of modules with TIM => see AN2012-07

2 IGBT, Inverter

Table 3 Maximum rated values

Parameter	Symbol	Note or test condition		Values	Unit
Collector-emitter voltage	V_{CES}		$T_{vj} = 25\text{ °C}$	1700	V
Continuous DC collector current	I_{CDC}	$T_{vj\text{ max}} = 175\text{ °C}$	$T_H = 45\text{ °C}$	650	A
Maximum RMS module DC-terminal current	I_{tRMS}		$T_{\text{Terminal}} = 90\text{ °C},$ $T_C = 90\text{ °C}$	580	A
			$T_{\text{Terminal}} = 105\text{ °C},$ $T_C = 90\text{ °C}$	565	
Repetitive peak collector current	I_{CRM}	t_p limited by $T_{vj\text{ op}}$		1500	A
Gate-emitter peak voltage	V_{GES}			±20	V

Table 4 Characteristic values

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage	$V_{CE\text{ sat}}$	$I_C = 750\text{ A}, V_{GE} = 15\text{ V}$	$T_{vj} = 25\text{ °C}$		1.70	1.85	V
			$T_{vj} = 125\text{ °C}$		1.95		
			$T_{vj} = 150\text{ °C}$		2.05		
			$T_{vj} = 175\text{ °C}$		2.10		
Gate threshold voltage	V_{GETh}	$I_C = 15.7\text{ mA}, V_{CE} = V_{GE}, T_{vj} = 25\text{ °C}$		5.15	5.80	6.45	V
Gate charge	Q_G	$V_{GE} = \pm 15\text{ V}, V_{CC} = 900\text{ V}, T_{vj} = 25\text{ °C}$			7.15		μC
Internal gate resistor	R_{Gint}	$T_{vj} = 25\text{ °C}$			0.33		Ω
Input capacitance	C_{ies}	$f = 100\text{ kHz}, T_{vj} = 25\text{ °C}, V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}$			78.1		nF
Reverse transfer capacitance	C_{res}	$f = 100\text{ kHz}, T_{vj} = 25\text{ °C}, V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}$			0.275		nF
Collector-emitter cut-off current	I_{CES}	$V_{CE} = 1700\text{ V}, V_{GE} = 0\text{ V}$	$T_{vj} = 25\text{ °C}$			5	mA
Gate-emitter leakage current	I_{GES}	$V_{CE} = 0\text{ V}, V_{GE} = 20\text{ V}, T_{vj} = 25\text{ °C}$				100	nA
Turn-on delay time (inductive load)	t_{don}	$I_C = 750\text{ A}, V_{CC} = 900\text{ V},$ $V_{GE} = \pm 15\text{ V}, R_{Gon} = 0.51\text{ Ω}$	$T_{vj} = 25\text{ °C}$		0.158		μs
			$T_{vj} = 125\text{ °C}$		0.172		
			$T_{vj} = 150\text{ °C}$		0.178		
			$T_{vj} = 175\text{ °C}$		0.184		

(table continues...)

Table 4 (continued) **Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Rise time (inductive load)	t_r	$I_C = 750 \text{ A}$, $V_{CC} = 900 \text{ V}$, $V_{GE} = \pm 15 \text{ V}$, $R_{Gon} = 0.51 \Omega$	$T_{vj} = 25 \text{ °C}$	0.046		μs
			$T_{vj} = 125 \text{ °C}$	0.053		
			$T_{vj} = 150 \text{ °C}$	0.055		
			$T_{vj} = 175 \text{ °C}$	0.057		
Turn-off delay time (inductive load)	t_{doff}	$I_C = 750 \text{ A}$, $V_{CC} = 900 \text{ V}$, $V_{GE} = \pm 15 \text{ V}$, $R_{Goff} = 2.2 \Omega$	$T_{vj} = 25 \text{ °C}$	0.536		μs
			$T_{vj} = 125 \text{ °C}$	0.613		
			$T_{vj} = 150 \text{ °C}$	0.631		
			$T_{vj} = 175 \text{ °C}$	0.648		
Fall time (inductive load)	t_f	$I_C = 750 \text{ A}$, $V_{CC} = 900 \text{ V}$, $V_{GE} = \pm 15 \text{ V}$, $R_{Goff} = 2.2 \Omega$	$T_{vj} = 25 \text{ °C}$	0.231		μs
			$T_{vj} = 125 \text{ °C}$	0.450		
			$T_{vj} = 150 \text{ °C}$	0.525		
			$T_{vj} = 175 \text{ °C}$	0.599		
Turn-on energy loss per pulse	E_{on}	$I_C = 750 \text{ A}$, $V_{CC} = 900 \text{ V}$, $L_\sigma = 25 \text{ nH}$, $V_{GE} = \pm 15 \text{ V}$, $R_{Gon} = 0.51 \Omega$, $di/dt = 11.1 \text{ kA}/\mu\text{s}$ ($T_{vj} = 175 \text{ °C}$)	$T_{vj} = 25 \text{ °C}$	74		mJ
			$T_{vj} = 125 \text{ °C}$	171		
			$T_{vj} = 150 \text{ °C}$	204		
			$T_{vj} = 175 \text{ °C}$	238		
Turn-off energy loss per pulse	E_{off}	$I_C = 750 \text{ A}$, $V_{CC} = 900 \text{ V}$, $L_\sigma = 25 \text{ nH}$, $V_{GE} = \pm 15 \text{ V}$, $R_{Goff} = 2.2 \Omega$, $dv/dt = 3600 \text{ V}/\mu\text{s}$ ($T_{vj} = 175 \text{ °C}$)	$T_{vj} = 25 \text{ °C}$	132		mJ
			$T_{vj} = 125 \text{ °C}$	208		
			$T_{vj} = 150 \text{ °C}$	224		
			$T_{vj} = 175 \text{ °C}$	239		
SC data	I_{SC}	$V_{GE} = 15 \text{ V}$, $V_{CC} = 1000 \text{ V}$, $V_{CEmax} = V_{CES} - L_{sCE} \cdot di/dt$	$t_p \leq 8 \mu\text{s}$, $T_{vj} = 150 \text{ °C}$	2600		A
			$t_p \leq 6 \mu\text{s}$, $T_{vj} = 175 \text{ °C}$	2500		
Thermal resistance, junction to heat sink	R_{thJH}	per IGBT, Valid with IFX pre-applied Thermal Interface Material			0.0935	K/W
Temperature under switching conditions	$T_{vj op}$		-40		175	°C

Note: $T_{vj op} > 150 \text{ °C}$ is only allowed for operation at overload conditions. For detailed specifications please refer to AN 2018-14.

3 Diode, Inverter

Table 5 Maximum rated values

Parameter	Symbol	Note or test condition		Values	Unit
Repetitive peak reverse voltage	V_{RRM}		$T_{vj} = 25\text{ °C}$	1700	V
Implemented forward current	I_{FN}			1200	A
Continuous DC forward current	I_F			750	A
Repetitive peak forward current	I_{FRM}	$t_P = 1\text{ ms}$		1500	A
I^2t - value	I^2t	$t_P = 10\text{ ms}, V_R = 0\text{ V}$	$T_{vj} = 125\text{ °C}$	48300	A^2s
			$T_{vj} = 175\text{ °C}$	37200	

Table 6 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	V_F	$I_F = 750\text{ A}, V_{GE} = 0\text{ V}$	$T_{vj} = 25\text{ °C}$		2.00	V
			$T_{vj} = 125\text{ °C}$		1.85	
			$T_{vj} = 150\text{ °C}$		1.80	
			$T_{vj} = 175\text{ °C}$		1.75	
Peak reverse recovery current	I_{RM}	$V_{CC} = 900\text{ V}, I_F = 750\text{ A}, V_{GE} = -15\text{ V}, -di_F/dt = 11.8\text{ kA}/\mu s (T_{vj} = 175\text{ °C})$	$T_{vj} = 25\text{ °C}$		950	A
			$T_{vj} = 125\text{ °C}$		1020	
			$T_{vj} = 150\text{ °C}$		1020	
			$T_{vj} = 175\text{ °C}$		1020	
Recovered charge	Q_r	$V_{CC} = 900\text{ V}, I_F = 750\text{ A}, V_{GE} = -15\text{ V}, -di_F/dt = 11.8\text{ kA}/\mu s (T_{vj} = 175\text{ °C})$	$T_{vj} = 25\text{ °C}$		115	μC
			$T_{vj} = 125\text{ °C}$		218	
			$T_{vj} = 150\text{ °C}$		255	
			$T_{vj} = 175\text{ °C}$		292	
Reverse recovery energy	E_{rec}	$V_{CC} = 900\text{ V}, I_F = 750\text{ A}, V_{GE} = -15\text{ V}, -di_F/dt = 11.8\text{ kA}/\mu s (T_{vj} = 175\text{ °C})$	$T_{vj} = 25\text{ °C}$		76	mJ
			$T_{vj} = 125\text{ °C}$		132	
			$T_{vj} = 150\text{ °C}$		152	
			$T_{vj} = 175\text{ °C}$		171	
Thermal resistance, junction to heat sink	R_{thJH}	per diode, Valid with IFX pre-applied Thermal Interface Material			0.111	K/W
Temperature under switching conditions	$T_{vj\text{ op}}$			-40	175	°C

Note: $T_{vj\ op} > 150^{\circ}\text{C}$ is allowed for operation at overload conditions. For detailed specifications, please refer to AN 2018-14.

4 NTC-Thermistor

Table 7 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Rated resistance	R_{25}	$T_{NTC} = 25^{\circ}\text{C}$		5		k Ω
Deviation of R_{100}	$\Delta R/R$	$T_{NTC} = 100^{\circ}\text{C}$, $R_{100} = 493\ \Omega$	-5		5	%
Power dissipation	P_{25}	$T_{NTC} = 25^{\circ}\text{C}$			20	mW
B-value	$B_{25/50}$	$R_2 = R_{25} \exp[B_{25/50}(1/T_2 - 1/(298,15\ \text{K}))]$		3375		K
B-value	$B_{25/80}$	$R_2 = R_{25} \exp[B_{25/80}(1/T_2 - 1/(298,15\ \text{K}))]$		3411		K
B-value	$B_{25/100}$	$R_2 = R_{25} \exp[B_{25/100}(1/T_2 - 1/(298,15\ \text{K}))]$		3433		K


Note: For an analytical description of the NTC characteristics please refer to AN2009-10, chapter 4

5 Characteristics diagrams

Output characteristic (typical), IGBT, Inverter

$I_C = f(V_{CE})$


$V_{GE} = 15\text{ V}$



Output characteristic field (typical), IGBT, Inverter

$I_C = f(V_{CE})$


$T_{vj} = 175\text{ °C}$



Transfer characteristic (typical), IGBT, Inverter

$I_C = f(V_{GE})$


$V_{CE} = 20\text{ V}$



Gate charge characteristic (typical), IGBT, Inverter

$V_{GE} = f(Q_G)$


$I_C = 750\text{ A}, T_{vj} = 25\text{ °C}$



5 Characteristics diagrams


Capacity characteristic (typical), IGBT, Inverter

$C = f(V_{CE})$
 $f = 100\text{ kHz}$, $V_{GE} = 0\text{ V}$, $T_{vj} = 25\text{ °C}$




Switching times (typical), IGBT, Inverter

$t = f(I_C)$
 $R_{Goff} = 2.2\text{ }\Omega$, $R_{Gon} = 0.51\text{ }\Omega$, $V_{GE} = \pm 15\text{ V}$, $V_{CC} = 900\text{ V}$, $T_{vj} = 175\text{ °C}$




Switching times (typical), IGBT, Inverter

$t = f(R_G)$
 $V_{GE} = \pm 15\text{ V}$, $I_C = 750\text{ A}$, $V_{CC} = 900\text{ V}$, $T_{vj} = 175\text{ °C}$



Voltage slope (typical), IGBT, Inverter


$dv/dt = f(R_G)$
 $V_{GE} = \pm 15\text{ V}$, $I_C = 750\text{ A}$, $V_{CC} = 900\text{ V}$, $T_{vj} = 25\text{ °C}$



5 Characteristics diagrams


Switching losses (typical), IGBT, Inverter

$E = f(I_C)$
 $R_{Goff} = 2.2 \Omega$, $R_{Gon} = 0.51 \Omega$, $V_{GE} = \pm 15 \text{ V}$, $V_{CC} = 900 \text{ V}$




Switching losses (typical), IGBT, Inverter

$E = f(R_G)$
 $V_{GE} = \pm 15 \text{ V}$, $I_C = 750 \text{ A}$, $V_{CC} = 900 \text{ V}$




Reverse bias safe operating area (RBSOA), IGBT, Inverter

$I_C = f(V_{CE})$
 $R_{Goff} = 2.2 \Omega$, $V_{GE} = \pm 15 \text{ V}$, $T_{vj} = 175 \text{ °C}$



Transient thermal impedance, IGBT, Inverter


$Z_{th} = f(t)$



5 Characteristics diagrams

Forward characteristic (typical), Diode, Inverter


$I_F = f(V_F)$



Switching losses (typical), Diode, Inverter

$E_{rec} = f(I_F)$


$R_{Gon} = 0.51\ \Omega, V_{CC} = 900\ \text{V}$



Switching losses (typical), Diode, Inverter


$E_{rec} = f(R_G)$

$I_F = 750\ \text{A}, V_{CC} = 900\ \text{V}$



Transient thermal impedance, Diode, Inverter


$Z_{th} = f(t)$



5 Characteristics diagrams

Temperature characteristic (typical), NTC-Thermistor

$R = f(T_{NTC})$



6 Circuit diagram





Figure 1



Revision 1.10
2025-08-11

8 Module label code

Module label code			
Code format	Data Matrix		Barcode Code128
Encoding	ASCII text		Code Set A
Symbol size	16x16		23 digits
Standard	IEC24720 and IEC16022		IEC8859-1
Code content	<i>Content</i>	<i>Digit</i>	<i>Example</i>
	Module serial number	1 – 5	71549
	Module material number	6 - 11	142846
	Production order number	12 - 19	55054991
	Date code (production year)	20 – 21	15
	Date code (production week)	22 – 23	30
Example			
			
71549142846550549911530		71549142846550549911530	

Figure 3



Revision history

Revision history

Document revision	Date of release	Description of changes
1.00	2024-05-28	Initial version
1.10	2025-08-11	Initial version

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2025-08-11

Published by

Infineon Technologies AG
81726 Munich, Germany

© 2025 Infineon Technologies AG
All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference
IFX-ABK214-002

Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.