

Final datasheet**High speed IGBT in Trench and Fieldstop technology recommended in combination with SiC diode IDH15S120****Features**

- $V_{CE} = 1200\text{ V}$
- $I_C = 40\text{ A}$
- TRENCHSTOP™ technology offering
- Best-in-class switching performance: less than 500 μJ total switching losses achievable
- Very low V_{CEsat}
- Low EMI
- Maximum junction temperature $T_{vjmax} = 175^\circ\text{C}$
- Qualified according to JEDEC for target applications
- Pb-free lead plating; RoHS compliant
- Complete product spectrum and PSpice Models: <http://www.infineon.com/igbt/>



Lead-free



Green



Halogen-free



RoHS


Potential applications

- Solar inverters
- Uninterruptible power supplies
- Welding converters
- Converters with high switching frequency

Description

Package pin definition:

- Pin G – Gate
- Pin C & backside – Collector
- Pin E – Emitter



Type	Package	Marking
IGW40N120H3	PG-TO247-3	G40H1203



Table of contents

	Description	1
	Features	1
	Potential applications	1
	Table of contents	2
1	IGBT	3
2	Characteristics diagrams	5
	Revision history	11
	Disclaimer	12

1 IGBT

Table 1 Maximum rated values

Parameter	Symbol	Note or test condition		Values	Unit
Collector-emitter voltage	V_{CE}	$T_{vj} \geq 25\text{ °C}$		1200	V
DC collector current, limited by T_{vjmax}	I_C		$T_c = 25\text{ °C}$	80	A
			$T_c = 100\text{ °C}$	40	
Pulsed collector current, t_p limited by T_{vjmax}	I_{Cpulse}			160	A
Turn-off safe operating area		$V_{CE} \leq 1200\text{ V}, T_{vj} \leq 175\text{ °C}$		160	A
Gate-emitter voltage	V_{GE}			± 20	V
Transient gate-emitter voltage	V_{GE}	$t_p \leq 10\text{ }\mu\text{s}, D < 0.01$		± 30	V
Short-circuit withstand time	t_{SC}	$V_{CC} \leq 600\text{ V}, V_{GE} = 15\text{ V}$, Allowed number of short circuits < 1000, Time between short circuits $\geq 1.0\text{ s}, T_{vj} = 175\text{ °C}$		10	μs

Table 2 Characteristic values

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Collector-emitter breakdown voltage	V_{BRCES}	$I_C = 0.5\text{ mA}, V_{GE} = 0\text{ V}$		1200			V
Collector-emitter saturation voltage	V_{CEsat}	$I_C = 40\text{ A}, V_{GE} = 15\text{ V}$	$T_{vj} = 25\text{ °C}$		2.05	2.4	V
			$T_{vj} = 125\text{ °C}$		2.5		
			$T_{vj} = 175\text{ °C}$		2.7		
Gate-emitter threshold voltage	V_{GETh}	$I_C = 1.5\text{ mA}, V_{CE} = V_{GE}$		5	5.8	6.5	V
Zero gate-voltage collector current	I_{CES}	$V_{CE} = 1200\text{ V}, V_{GE} = 0\text{ V}$	$T_{vj} = 25\text{ °C}$			250	μA
			$T_{vj} = 175\text{ °C}$			2500	
Gate-emitter leakage current	I_{GES}	$V_{CE} = 0\text{ V}, V_{GE} = 20\text{ V}$				600	nA
Transconductance	g_{fs}	$I_C = 40\text{ A}, V_{CE} = 20\text{ V}$			20		S
Short-circuit collector current	I_{SC}	$V_{CC} \leq 600\text{ V}, V_{GE} = 15\text{ V}, t_{SC} \leq 10\text{ }\mu\text{s}$, Allowed number of short circuits < 1000, Time between short circuits $\geq 1.0\text{ s}, T_{vj} = 175\text{ °C}$			139		A
Input capacitance	C_{ies}	$V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 1000\text{ kHz}$			2330		pF
Output capacitance	C_{oes}	$V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 1000\text{ kHz}$			150		pF
Reverse transfer capacitance	C_{res}	$V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 1000\text{ kHz}$			130		pF

(table continues...)

Table 2 (continued) **Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Gate charge	Q_G	$V_{CC} = 960 \text{ V}, I_C = 40 \text{ A}, V_{GE} = 15 \text{ V}$		185		nC
Turn-on delay time	$t_{d(on)}$	$V_{CC} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 12 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	30		ns
			$T_{vj} = 175 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	29		
Rise time (inductive load)	t_r	$V_{CC} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 12 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	57		ns
			$T_{vj} = 175 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	49		
Turn-off delay time	$t_{d(off)}$	$V_{CC} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 12 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	290		ns
			$T_{vj} = 175 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	366		
Fall time (inductive load)	t_f	$V_{CC} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 12 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	16		ns
			$T_{vj} = 175 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	48		
Turn-on energy	E_{on}	$V_{CC} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 12 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	1.93		mJ
			$T_{vj} = 175 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	2.21		
Turn-off energy	E_{off}	$V_{CC} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 12 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	1.23		mJ
			$T_{vj} = 175 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	2.66		
Total switching energy	E_{ts}	$V_{CC} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 12 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	3.16		mJ
			$T_{vj} = 175 \text{ }^\circ\text{C}, I_C = 40 \text{ A}$	4.87		
Operating junction temperature	T_{vj}		-40		175	$^\circ\text{C}$


Note: Maximum rated values: For optimum lifetime and reliability, Infineon recommends operating conditions that do not exceed 80% of the maximum ratings stated in this datasheet.
Characteristic values at $T_{vj} = 25^\circ\text{C}$, unless otherwise specified.
Dynamic test circuit: $L_\sigma = 70 \text{ nH}$, $C_\sigma = 67 \text{ pF}$ from Figure E. Energy losses include “tail” and diode (IDH15S120) reverse recovery.

2 Characteristics diagrams

Collector current as a function of switching frequency

$$I_C = f(f)$$


$D = 0.5$, $V_{CE} = 600 \text{ V}$, $T_{vj} \leq 175 \text{ }^\circ\text{C}$, $V_{GE} = 0/15 \text{ V}$, $R_G = 12 \text{ } \Omega$



Forward bias safe operating area

$$I_C = f(V_{CE})$$


$D = 0$, $T_{vj} \leq 175 \text{ }^\circ\text{C}$, $V_{GE} = 15 \text{ V}$, $T_c = 25 \text{ }^\circ\text{C}$



Power dissipation as a function of case temperature

$$P_{tot} = f(T_c)$$


$T_{vj} \leq 175 \text{ }^\circ\text{C}$



Collector current as a function of case temperature

$$I_C = f(T_c)$$


$T_{vj} \leq 175 \text{ }^\circ\text{C}$, $V_{GE} \geq 15 \text{ V}$



2 Characteristics diagrams


Typical output characteristic

$I_C = f(V_{CE})$
 $T_{vj} = 25\text{ }^{\circ}\text{C}$




Typical output characteristic

$I_C = f(V_{CE})$
 $T_{vj} = 175\text{ }^{\circ}\text{C}$




Typical transfer characteristic

$I_C = f(V_{GE})$
 $V_{CE} = 20\text{ V}$



Typical collector-emitter saturation voltage as a function of junction temperature


$V_{CEsat} = f(T_{vj})$
 $V_{GE} = 15\text{ V}$



2 Characteristics diagrams


Gate-emitter threshold voltage as a function of junction temperature

$V_{GEth} = f(T_{vj})$
 $I_C = 1.5\text{ mA}$




Typical switching times as a function of collector current

$t = f(I_C)$
 $V_{CC} = 600\text{ V}, T_{vj} = 175\text{ °C}, V_{GE} = 0/15\text{ V}, R_G = 12\text{ }\Omega$




Typical switching times as a function of gate resistor

$t = f(R_G)$
 $I_C = 40\text{ A}, V_{CC} = 600\text{ V}, T_{vj} = 175\text{ °C}, V_{GE} = 0/15\text{ V}$



Typical switching times as a function of junction temperature

$t = f(T_{vj})$
 $I_C = 40\text{ A}, V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_G = 12\text{ }\Omega$




2 Characteristics diagrams

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$


$V_{CC} = 600 \text{ V}$, $T_{vj} = 175 \text{ }^{\circ}\text{C}$, $V_{GE} = 0/15 \text{ V}$, $R_G = 12 \text{ } \Omega$



Typical switching energy losses as a function of gate resistor

$$E = f(R_G)$$


$I_C = 40 \text{ A}$, $V_{CC} = 600 \text{ V}$, $T_{vj} = 175 \text{ }^{\circ}\text{C}$, $V_{GE} = 0/15 \text{ V}$



Typical switching energy losses as a function of junction temperature

$$E = f(T_{vj})$$


$I_C = 40 \text{ A}$, $V_{CC} = 600 \text{ V}$, $V_{GE} = 0/15 \text{ V}$, $R_G = 12 \text{ } \Omega$



Typical switching energy losses as a function of collector emitter voltage

$$E = f(V_{CE})$$


$I_C = 40 \text{ A}$, $T_{vj} = 175 \text{ }^{\circ}\text{C}$, $V_{GE} = 0/15 \text{ V}$, $R_G = 12 \text{ } \Omega$



2 Characteristics diagrams


Typical gate charge

$V_{GE} = f(Q_G)$
 $I_C = 40\text{ A}$




Typical capacitance as a function of collector-emitter voltage

$C = f(V_{CE})$
 $f = 1000\text{ kHz}, V_{GE} = 0\text{ V}$




Typical short circuit collector current as a function of gate-emitter voltage

$I_{C(SC)} = f(V_{GE})$
 $T_{vj, start} = 25\text{ }^{\circ}\text{C}, V_{CC} \leq 600\text{ V}$



Short circuit withstand time as a function of gate-emitter voltage


$t_{SC} = f(V_{GE})$
 $T_{vj, start} \leq 150\text{ }^{\circ}\text{C}, V_{CC} \leq 600\text{ V}$



2 Characteristics diagrams

IGBT transient thermal impedance as a function of pulse width

$Z_{th(j-c)} = f(t_p)$
 $D = t_p/T$



Revision history

Document revision	Date of release	Description of changes
V2.1	2012-07-31	Final data sheet
V2.2	2014-11-26	Minor change Figure 7
V2.3	2015-10-08	Minor change Static Characteristic
n/a	2020-11-30	Datasheet migrated to a new system with a new layout and new revision number schema: target or preliminary datasheet = 0.xy; final datasheet = 1.xy
1.10	2025-06-12	Added transient Gate-emitter voltage Editorial changes

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2025-06-12

Published by

Infineon Technologies AG
81726 Munich, Germany

© 2025 Infineon Technologies AG
All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference
IFX-AAK648-004

Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Please note that this product is not qualified according to the AEC Q100 or AEC Q101 documents of the Automotive Electronics Council.

Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.