3rd Generation thinQ!™ SiC Schottky Diode


Features

- Revolutionary semiconductor material - Silicon Carbide
- Switching behavior benchmark
- No reverse recovery / No forward recovery
- Temperature independent switching behavior
- High surge current capability
- Pb-free lead plating; RoHS compliant
- Qualified according to JEDEC[1)] for target applications
- Breakdown voltage tested at 20mA[2)]
- Optimized for high temperature operation
- Lowest Figure of Merit Q_C/I_F

Product Summary

V_{DC}	600	V
Q_C	3.2	nC
I_F; T_C< 130 °C	3	A

PG-TO220-2



thinQ! 3G Diode designed for fast switching applications like:

- SMPS e.g.; CCM PFC
- Motor Drives; Solar Applications; UPS

Type	Package	Marking	Pin 1	Pin 2
IDH03SG60C	PG-TO220-2	D03G60C	C	A

Maximum ratings

Parameter	Symbol	Conditions	Value	Unit
Continuous forward current	I_F	T_C<130 °C	3	A
Surge non-repetitive forward current, sine halfwave	$I_{F,SM}$	T_C=25 °C, t_p=10 ms	11.5	
		T_C=150 °C, t_p=10 ms	9.7	
Non-repetitive peak forward current	$I_{F,max}$	T_C=25 °C, t_p=10 µs	100	
i^2t value	$\int i^2dt$	T_C=25 °C, t_p=10 ms	0.61	A^2s
		T_C=150 °C, t_p=10 ms	0.44	
Repetitive peak reverse voltage	V_{RRM}	T_j=25 °C	600	V
Diode dv/dt ruggedness	dv/dt	V_R= 0….480 V	50	V/ns
Power dissipation	P_{tot}	T_C=25 °C	38	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 175	°C
Soldering temperature, wavesoldering only allowed at leads	T_{sold}	1.6mm (0.063 in.) from case for 10s	260	
Mounting torque		M3 and M3.5 screws	60	Ncm

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics						
Thermal resistance, junction - case	R_{thJC}		-	-	3.9	K/W
Thermal resistance, junction - ambient	R_{thJA}	Thermal resistance, junction- ambient, leaded	-	-	62	
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
DC blocking voltage	V_{DC}	I_R=0.05 mA, T_j=25 °C	600	-	-	V
Diode forward voltage	V_F	I_F=3 A, T_j=25 °C	-	2.1	2.3	
		I_F=3 A, T_j=150 °C	-	2.8	-	
Reverse current	I_R	V_R=600 V, T_j=25 °C	-	0.23	15	µA
		V_R=600 V, T_j=150 °C	-	1	150	
AC characteristics						
Total capacitive charge	Q_c	V_R=400 V,$I_F \leq I_{F,max}$, di_F/dt=200 A/µs, T_j=150 °C	-	3.2	-	nC
Switching time[3)]	t_c		-	-	<10	ns
Total capacitance	C	V_R=1 V, f=1 MHz	-	60	-	pF
		V_R=300 V, f=1 MHz	-	8	-	
		V_R=600 V, f=1 MHz	-	8	-	

[1)] J-STD20 and JESD22

[2)] All devices tested under avalanche conditions, for a time periode of 10ms, at 20mA.


[3)] t_c is the time constant for the capacitive displacement current waveform (independent from T_j, I_{LOAD} and di/dt), different from t_{rr} which is dependent on T_j, I_{LOAD} and di/dt. No reverse recovery time constant t_{rr} due to absence of minority carrier injection.

[4)] Under worst case Z_{th} conditions.

[5)] Only capacitive charge occuring, guaranteed by design.


1 Power dissipation

$P_{tot}=f(T_C)$; parameter: $R_{thJC(max)}$




2 Diode forward current

$I_F=f(T_C)$[4]; $T_j \leq 175$ °C; parameter: $D = t_p/T$




3 Typ. forward characteristic

$I_F=f(V_F)$; $t_p=400$ µs; parameter: T_j




4 Typ. forward characteristic in surge current mode

$I_F=f(V_F)$; $t_p=400$ µs; parameter: T_j




5 Typ. capacitance charge vs. current slope

Q_C=f(di_F/dt)[5]; $I_F \leq I_{F,max}$




6 Typ. reverse current vs. reverse voltage

I_R=f(V_R); parameter: T_j




7 Typ. transient thermal impedance

Z_{thJC}=f(t_p); parameter: $D = t_P/T$




8 Typ. capacitance vs. reverse voltage

C=f(V_R); T_C=25 °C, f=1 MHz




9 Typ. C stored energy

$E_C=f(V_R)$



PG-TO220-2: Outline



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.30	4.50	0.169	0.177
A1	1.17	1.37	0.046	0.054
A2	2.30	2.50	0.091	0.098
b	0.65	0.85	0.026	0.033
b1	1.19	1.69	0.047	0.066
b2	1.19	1.39	0.047	0.055
c	0.40	0.60	0.016	0.024
D	15.35	15.95	0.604	0.628
D1	9.05	9.45	0.356	0.372
D2	12.30	13.05	0.484	0.514
E	9.80	10.20	0.386	0.402
E1	7.25	8.60	0.285	0.339
e1	5.08		0.200	
N	2		2	
H1	5.90	6.90	0.232	0.272
L	13.00	14.00	0.512	0.551
L1	3.30	3.70	0.130	0.146
øP	3.55	3.70	0.140	0.146
Q	2.60	3.00	0.102	0.118

DOCUMENT NO.
Z8B00150560

SCALE 0 2.5 0 2.5 5mm

EUROPEAN PROJECTION

ISSUE DATE
28-10-2008

REVISION
01

Dimensions in mm/inches

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2012 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support , automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support systems are intended to be implanted in the human body and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.