


HighSpeed 2-Technology



- **Designed for:**
  - TV – Horizontal Line Deflection
- **2nd generation HighSpeed-Technology for 1200V applications offers:**
  - loss reduction in resonant circuits
  - temperature stable behavior
  - parallel switching capability
  - tight parameter distribution
  - E_{off} optimized for I_C =3A
  - simple Gate-Control


PG-TO220-3-31
(FullPAK)


PG-TO220-3-34
(FullPAK)

- Qualified according to JEDEC[1] for target applications
- Pb-free lead plating; RoHS compliant
- Complete product spectrum and PSpice Models : http://www.infineon.com/igbt/

Type	V_{CE}	I_C	E_{off}	$T_{j,max}$	Marking	Package
IGA03N120H2	1200V	3A	0.15mJ	150°C	G03H1202	PG-TO-220-3-31
IGA03N120H2	1200V	3A	0.15mJ	150°C	G03H1202	PG-TO-220-3-34

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-emitter voltage	V_{CE}	1200	V
Triangular collector peak current (V_{GS} = 15V) T_C = 100°C, f = 32kHz	I_{Cpk}	8.2	A
Pulsed collector current, t_p limited by T_{jmax}	I_{Cpuls}	9	
Turn off safe operating area $V_{CE} \le$ 1200V, $T_j \le$ 150°C	-	9	
Gate-emitter voltage	V_{GE}	±20	V
Power dissipation T_C = 25°C	P_{tot}	29	W
Operating junction and storage temperature	T_j , T_{stg}	-40...+150	°C
Soldering temperature, 1.6mm (0.063 in.) from case for 10s	-	260	
Isolation Voltage	V_{isol}	2500	V_{rms}

[1] J-STD-020 and JESD-022

Thermal Resistance

Parameter	Symbol	Conditions	Max. Value	Unit
Characteristic				
IGBT thermal resistance, junction – case	R_{thJC}		4.3	K/W
Thermal resistance, junction – ambient	R_{thJA}		64	

Electrical Characteristic, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			min.	Typ.	max.	
Static Characteristic						
Collector-emitter breakdown voltage	$V_{(BR)CES}$	V_{GE}=0V, I_C=300µA	1200	-	-	V
Collector-emitter saturation voltage	$V_{CE(sat)}$	V_{GE} = 15V, I_C=3A				
		T_j=25°C	-	2.2	2.8	
		T_j=150°C	-	2.5	-	
		V_{GE} = 10V, I_C=3A, T_j=25°C	-	2.4	-	
Gate-emitter threshold voltage	$V_{GE(th)}$	I_C=90µA, V_{CE}=V_{GE}	2.1	3	3.9	
Zero gate voltage collector current	I_{CES}	V_{CE}=1200V, V_{GE}=0V				µA
		T_j=25°C	-	-	20	
		T_j=150°C	-	-	80	
Gate-emitter leakage current	I_{GES}	V_{CE}=0V, V_{GE}=20V	-	-	100	nA
Transconductance	g_{fs}	V_{CE}=20V, I_C=3A	-	2	-	S
Dynamic Characteristic						
Input capacitance	C_{iss}	V_{CE}=25V	-	205	-	pF
Output capacitance	C_{oss}	V_{GE}=0V	-	24	-	
Reverse transfer capacitance	C_{rss}	f=1MHz	-	7	-	
Gate charge	Q_{Gate}	V_{CC}=960V, I_C=3A V_{GE}=15V	-	8.6	-	nC
Internal emitter inductance measured 5mm (0.197 in.) from case	L_E		-	7	-	nH

Switching Characteristic, Inductive Load, at T_j=25 °C

Parameter	Symbol	Conditions	Value			Unit
			min.	Typ.	max.	
IGBT Characteristic						
Turn-on delay time	$t_{d(on)}$	T_j=25°C	-	9.2	-	ns
Rise time	t_r	V_{CC}=800V, I_C=3A	-	5.2	-	
Turn-off delay time	$t_{d(off)}$	V_{GE}=0V/15V	-	281	-	
Fall time	t_f	R_G=82Ω	-	29	-	
Turn-on energy	E_{on}	L_σ [2)]=180nH	-	0.14	-	mJ
Turn-off energy	E_{off}	C_σ [1)]=40pF	-	0.15	-	
Total switching energy	E_{ts}	Energy losses include "tail" and diode [2)] reverse recovery.	-	0.29	-	

Switching Characteristic, Inductive Load, at T_j=150 °C

Parameter	Symbol	Conditions	Value			Unit
			min.	Typ.	max.	
IGBT Characteristic						
Turn-on delay time	$t_{d(on)}$	T_j=150°C	-	9.4	-	ns
Rise time	t_r	V_{CC}=800V, I_C=3A	-	6.7	-	
Turn-off delay time	$t_{d(off)}$	V_{GE}=0V/15V	-	340	-	
Fall time	t_f	R_G=82Ω	-	63	-	
Turn-on energy	E_{on}	L_σ [1)]=180nH	-	0.22	-	mJ
Turn-off energy	E_{off}	C_σ [1)]=40pF	-	0.26	-	
Total switching energy	E_{ts}	Energy losses include "tail" and diode [3)] reverse recovery.	-	0.48	-	

Switching Energy ZVT, Inductive Load

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
IGBT Characteristic						
Turn-off energy	E_{off}	V_{CC}=800V, I_C=3A				mJ
		V_{GE}=0V/15V				
		R_G=82Ω, C_r [1)]=4nF				
		T_j=25°C	-	0.05	-	
		T_j=150°C	-	0.09	-	

[2)] Leakage inductance L_σ and stray capacity C_σ due to dynamic test circuit in figure E
[3)] Commutation diode from device IKP03N120H2




Figure 1. Collector current as a function of switching frequency
($T_j \le 150°C$, $D = 0.5$, $V_{CE} = 800V$, $V_{GE} = +15V/0V$, $R_G = 82\Omega$)




Figure 2. Safe operating area
($D = 0$, $T_C = 25°C$, $T_j \le 150°C$)




Figure 3. Power dissipation as a function of case temperature
($T_j \le 150°C$)




Figure 4. Collector current as a function of case temperature
($V_{GE} \le 15V$, $T_j \le 150°C$)




Figure 5. Typical output characteristics
(T_j = 25°C)




Figure 6. Typical output characteristics
(T_j = 150°C)




Figure 7. Typical transfer characteristics
(V_{CE} = 20V)




Figure 8. Typical collector-emitter saturation voltage as a function of junction temperature
(V_{GE} = 15V)




Figure 9. Typical switching times as a function of collector current
(inductive load, T_j = 150°C,
V_{CE} = 800V, V_{GE} = +15V/0V, R_G = 82Ω,
dynamic test circuit in Fig.E)




Figure 10. Typical switching times as a function of gate resistor
(inductive load, T_j = 150°C,
V_{CE} = 800V, V_{GE} = +15V/0V, I_C = 3A,
dynamic test circuit in Fig.E)




Figure 11. Typical switching times as a function of junction temperature
(inductive load, V_{CE} = 800V,
V_{GE} = +15V/0V, I_C = 3A, R_G = 82Ω,
dynamic test circuit in Fig.E)




Figure 12. Gate-emitter threshold voltage as a function of junction temperature
(I_C = 0.09mA)




Figure 13. Typical switching energy losses as a function of collector current
(inductive load, T_j = 150°C,
V_{CE} = 800V, V_{GE} = +15V/0V, R_G = 82Ω,
dynamic test circuit in Fig.E)




Figure 14. Typical switching energy losses as a function of gate resistor
(inductive load, T_j = 150°C,
V_{CE} = 800V, V_{GE} = +15V/0V, I_C = 3A,
dynamic test circuit in Fig.E)




Figure 15. Typical switching energy losses as a function of junction temperature
(inductive load, V_{CE} = 800V,
V_{GE} = +15V/0V, I_C = 3A, R_G = 82Ω,
dynamic test circuit in Fig.E)




Figure 16. Typical turn off switching energy loss for soft switching
(*dynamic test circuit in Fig. E*)




Figure 19. Typical capacitance as a function of collector-emitter voltage
(V_{GE} = 0V, f = 1MHz)




Figure 18. Typical gate charge
(I_C = 3A)





Figure 17. IGBT transient thermal impedance as a function of pulse width
(D=t_P/T)

PG-TO-220-3-31 (FullPAK)



symbol	dimensions			
	[mm]		[inch]	
	min	max	min	max
A	10.37	10.63	0.4084	0.4184
B	15.86	16.12	0.6245	0.6345
C	0.65	0.78	0.0256	0.0306
D	2.95 typ.		0.1160 typ.	
E	3.15	3.25	0.124	0.128
F	6.05	6.56	0.2384	0.2584
G	13.47	13.73	0.5304	0.5404
H	3.18	3.43	0.125	0.135
K	0.45	0.63	0.0177	0.0247
L	1.23	1.36	0.0484	0.0534
M	2.54 typ.		0.100 typ.	
N	4.57	4.83	0.1800	0.1900
P	2.57	2.83	0.1013	0.1113
T	2.51	2.62	0.0990	0.1030

Edition 2006-01

Published by
Infineon Technologies AG
81726 München, Germany

© Infineon Technologies AG 12/14/06.
All Rights Reserved.

Attention please!

The information given in this data sheet shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.