

SCHOTTKY RECTIFIER HIGH EFFICIENCY SERIES

35 Amp. 60V

Major Ratings and Characteristics



Characteristics	35SCGQ060	Units
$I_{F(AV)}$	35	A
V_{RRM} (Per Leg)	60	V
I_{FSM} @ $t_p = 8.3\text{ms}$ half-sine (Per Leg)	400	A
V_F @ 17.5Apk, $T_J = 125^\circ\text{C}$ (Per Leg)	0.61	V
T_J, T_{stg} Operating and storage	-55 to 150	$^\circ\text{C}$

Description/Features

The 35SCGQ060 center tap Schottky rectifier has been expressly designed to meet the rigorous requirements of IR HiRel environments. It is packaged in the hermetic isolated TO-254AA package. The device's forward voltage drop and reverse leakage current are optimized for the lowest power loss and the highest circuit efficiency for typical high frequency switching power supplies and resonant power converters. Full MIL-PRF-19500 quality conformance testing is available on source control drawings to TX, TXV and S quality levels.

- Hermetically Sealed
- Center Tap
- Low Forward Voltage Drop
- High Frequency Operation
- Guard Ring for Enhanced Ruggedness and Long term Reliability
- Light Weight

CASE STYLE



Case Outline and Dimensions - TO-254AA

Voltage Ratings

Part Number	35SCGQ060
V _R Max. DC Reverse Voltage (V) (Per Leg)	60
V _{RRM} Max. Working Peak Reverse Voltage (V) (Per Leg)	

Absolute Maximum Ratings

Parameter	Limits	Units	Conditions
I _{F(AV)} Max. Average Forward Current See Fig. 5	35	A	50% duty cycle @ T _C = 113°C, square waveform
I _{FSM} Max. Peak One Cycle Non - Repetitive Surge Current (Per Leg)	400	A	@ t _p = 8.3 ms half-sine

Electrical Specifications

Parameter	Limits	Units	Conditions
V _{FM} Max. Forward Voltage Drop (Per Leg) See Fig. 1 ①	0.64	V	@ I _F = 17.5A
	0.82	V	@ I _F = 35A
	0.61	V	@ I _F = 17.5A
	0.86	V	@ I _F = 35A
	0.61	V	@ I _F = 17.5A
	0.93	V	@ I _F = 35A
I _{RM} Max. Reverse Leakage Current (Per Leg) See Fig. 2 ①	0.3	mA	T _J = 25°C
	40	mA	T _J = 100°C
	180	mA	T _J = 125°C
C _T Max. Junction Capacitance (Per Leg)	1520	pF	V _R = rated V _R
L _S Typical Series Inductance (Per Leg)	7.8	nH	T _J = 25°C

Thermal-Mechanical Specifications

Parameter	Limits	Units	Conditions
T _J Max. Junction Temperature Range	-55 to 150	°C	
T _{stg} Max. Storage Temperature Range	-55 to 150	°C	
R _{thJC} Max. Thermal Resistance, Junction to Case (Per Leg)	1.25	°C/W	DC operation See Fig. 4
R _{thJC} Max. Thermal Resistance, Junction to Case (Per Package)	0.63	°C/W	DC operation
Wt Weight (Typical)	9.3	g	
Die Size (Typical)	150 x 180	mils	
Case Style	TO-254AA		

① Pulse Width < 300μs, Duty Cycle < 2%




Fig 1. Max. Forward Voltage Drop Characteristics (Per Leg)




Fig 2. Typical Values of Reverse Current Vs. Reverse Voltage (Per Leg)




Fig 3. Typical Junction Capacitance Vs. Reverse Voltage (Per Leg)




Fig 4. Max. Thermal Impedance ZthJC Characteristics (Per Leg)




Fig 5. Max. Allowable Case Temperature Vs. Average Forward Current (Per Package)

IMPORTANT NOTICE

The information given in this document shall be in no event regarded as guarantee of conditions or characteristic. The data contained herein is a characterization of the component based on internal standards and is intended to demonstrate and provide guidance for typical part performance. It will require further evaluation, qualification and analysis to determine suitability in the application environment to confirm compliance to your system requirements.

With respect to any example hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind including without limitation warranties on non-infringement of intellectual property rights and any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's product and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of any customer's technical departments to evaluate the suitability of the product for the intended applications and the completeness of the product information given in this document with respect to applications.

For further information on the product, technology, delivery terms and conditions and prices, please contact your local sales representative or go to (www.infineon.com/hirel).

WARNING

Due to technical requirements products may contain dangerous substances. For information on the types in question, please contact your nearest Infineon Technologies office.