



---

The following document contains information on Cypress products. The document has the series name, product name, and ordering part numbering with the prefix “MB”. However, Cypress will offer these products to new and existing customers with the series name, product name, and ordering part number with the prefix “CY”.

#### **How to Check the Ordering Part Number**

1. Go to [www.cypress.com/pcn](http://www.cypress.com/pcn).
2. Enter the keyword (for example, ordering part number) in the **SEARCH PCNS** field and click **Apply**.
3. Click the corresponding title from the search results.
4. Download the Affected Parts List file, which has details of all changes

#### **For More Information**

Please contact your local sales office for additional information about Cypress products and solutions.

#### **About Cypress**

Cypress is the leader in advanced embedded system solutions for the world's most innovative automotive, industrial, smart home appliances, consumer electronics and medical products. Cypress' microcontrollers, analog ICs, wireless and USB-based connectivity solutions and reliable, high-performance memories help engineers design differentiated products and get them to market first. Cypress is committed to providing customers with the best support and development resources on the planet enabling them to disrupt markets by creating new product categories in record time. To learn more, go to [www.cypress.com](http://www.cypress.com).

## FM3 IEC60730 Class B Self-Test Library

| Associated Part Family: | Series Name     | Product Number   |
|-------------------------|-----------------|--|
|                         | <b>MB9B500B</b> | <b>MB9BF504NB,MB9BF505NB,MB9BF506NB<br/>MB9BF504RB,MB9BF505RB,MB9BF506RB</b>                       |
|                         | <b>MB9B400A</b> | <b>MB9BF404NA,MB9BF405NA,MB9BF406NA<br/>MB9BF404RA,MB9BF405RA,MB9BF406RA</b>                       |
|                         | <b>MB9B300B</b> | <b>MB9BF304NB,MB9BF305NB,MB9BF306NB<br/>MB9BF304RB,MB9BF305RB,MB9BF306RB</b>                       |
|                         | <b>MB9B100A</b> | <b>MB9BF102NA,MB9BF104NA,MB9BF105NA,MB9BF106NA<br/>MB9BF102RA,MB9BF104RA,MB9BF105RA,MB9BF106RA</b> |

This application notes describes how to use and implement the library functions provided. It will first show the requirement of IEC60730 Class B, and then explain how it can be implemented. At last an example is given to show how to integrate test functions into a real system.

## Contents

|     |   |    |     |                              |    |
|-----|---|----|-----|------------------------------|----|
| 1   | Introduction .....  | 1  | 4.6 | Variable Memory Test .....   | 25 |
| 1.1 | About Document .....  | 1  | 4.7 | IO Test .....                | 26 |
| 1.2 | About IEC60730 .....  | 1  | 4.8 | AD Test .....                | 28 |
| 1.3 | About MB9B100A / MB9B300B / MB9B400A /<br>MB9B500B Series MCU ..... | 2  | 5   | Example project .....        | 29 |
| 1.4 | About FM3 IEC60730 STL Demo Project .....                           | 2  | 5.1 | User Configuration .....     | 29 |
| 2   | IEC60730 Class B Requirement .....                                  | 4  | 5.2 | Project Structure .....      | 29 |
| 3   | IEC60730 Class B STL Overview .....                                 | 5  | 5.3 | Sample Code .....            | 31 |
| 4   | IEC60730 Class B STL API .....                                      | 6  | 6   | STL API Performance .....    | 34 |
| 4.1 | CPU Register Test .....   | 6  | 7   | Reference Documents .....    | 35 |
| 4.2 | CPU PC Test .....   | 8  | 8   | Appendix .....               | 35 |
| 4.3 | Interrupt Test .....  | 9  | 8.1 | CRC code making method ..... | 35 |
| 4.4 | Clock Test .....  | 11 | 9   | Document History .....       | 39 |
| 4.5 | Invariable Memory Test .....  | 18 |     |                              |    |

## 1 Introduction

### 1.1 About Document

This application notes describes how to use and implement the library functions provided. It will first show the requirement of IEC60730 Class B, and then explain how it can be implemented. At last an example is given to show how to integrate test functions into a real system.

### 1.2 About IEC60730

The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). International Standard IEC60730-1 has been prepared by IEC technical committee for automatic controls in household use. From 2007 onwards, home appliances have to comply with Standard IEC60730 to make system more safety.

The Annex H of IEC60730 applies to electronic controls and embedded systems implemented by both hardware and software. Therefore the system using a microcontroller is typically the case in modern appliances. Especially, Annex H of IEC60730 explains detailed test and diagnostic methods for microcontrollers.

In Annex H, the software-related Standard items are classified by Class A, B or C.

- Class A: control functions which are not intended to be relied upon for the safety of the equipment, such as humidity controls, lighting controls and timers.
- Class B: software that includes code intended to prevent hazards if a fault, other than a software fault, occurs in the appliance, such as thermal cut-outs and door locks for laundry equipment.
- Class C: software that includes code intended to prevent hazards without the use of other protective devices, such as thermal cut-outs for closed water heater systems.

### 1.3 About MB9B100A/MB9B300B/MB9B400A/MB9B500B Series MCU

MB9B100A/MB9B300B/MB9B400A/MB9B500B series MCU is 32-bit general purpose MCU of FM3 family that features the industry's leading-edge ARM Cortex™-M3 CPU and integrates Fujitsu's highly reliable and high-speed secure embedded flash technology. This MCU can operate at up to 80MHz CPU frequency and work at a widevoltage range (2.7-5.5V), which can be both compatible with 3.3V and 5V system.

It includes a host of robust peripheral features, including motor control timers (MFT), base timer (can be configured to PWM, PPG, Reload, PWC timer), ADCs, on-chip memory (up to 512K Flash, up to 64K SRAM) and a wide range of communication interfaces (USB, I2C, SIO, LIN, CAN).

The size of on-chip memory can be configured according to different part number and the package is available in LQFP and QFN, shown in [Table 1](#).

**Table 1. FM3 Product List**

| Product       | Flash | SRAM | Package                             |
|---------------|-------|------|-------------------------------------|
| MB9BF104NA/RA | 256kB | 32KB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF105NA/RA | 384kB | 48kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF106NA/RA | 512kB | 64kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF304NB/RB | 256kB | 32kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF305NB/RB | 384kB | 48kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF306NB/RB | 512kB | 64kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF404NA/RA | 256kB | 32kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF405NA/RA | 384kB | 48kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF406NA/RA | 512kB | 64kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF504NB/RB | 256kB | 32kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF505NB/RB | 384kB | 48kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |
| MB9BF506NB/RB | 512kB | 64kB | NA: LQFP100/BGA-112<br>NA: LQFP-120 |

### 1.4 About FM3 IEC60730 STL Demo Project

This is a sample project to demonstrate how to use FM3 IEC60730 Self-Test Library. It is developed in IAR EWARM Workbench V6.50 and Keil µVision V4.20 IDE, and evaluated on IAR MB9BF506-SK EV-Board and Keil MCB9BF500 EV-Board (Vers.2) respectively

**Notes:**

1. If the later version of IAR EWARM Workbench V6.21 and Keil  $\mu$ Vision V4.20 are used to open this example project, MCU type information in project setting may lose, please check it.
2. If user select the "Use CMSIS" option (in Library Configuration table of General Options) with IAR EWARM Workbench V6.20 later, please erase the head files with prefix "core\_" in common folder (path: ..\..\common).
3. If the former version of IAR EWARM Workbench V6.21 is used to open this example project, MCU type, pre-included files (in preprocess table of C/C++ compiler), icf file (in link table of debug option), flash loader file (down table of debugger option) may lose, please check these settings.
4. If the former version of Keil  $\mu$ Vision V4.20 is used to open this example project, MCU type, pre-included files (in C/C++ table of project option), debug setting (in debug table of project setting) may lose, please check these information.
5. If user uses former version of IAR EWARM Workbench V6.20, it is a MUST to copy two files (core\_cmFunc.h and core\_cmInstr.h in cmsis\_low\_ver folder in current project directory) to common folder (path: ..\..\common)

## 2 IEC60730 Class B Requirement

The specification defined in IEC60730 requires controls with functions classified as software class B or C shall use measures to avoid and control software-related faults/errors in safety-related data and safety-related segments of the software. This means the software must use test method to detect faults internal and external of the microcontroller.

FM0+ IEC60730 self-test library (STL) focuses on software Class B requirement for S6E1A1 series MCU, which covers most IEC60730 requirements listed in the standard. For Class B controllers, below table lists elements that must be tested, method to be adapted and definitions to be implemented as summary of Annex H table H.11.12.7.

**Table 2. FM0+ IEC60730 STL Test Items**

| Component                            | Fault/Error                             | Method used in STL                         | Definitions | In STL |
|--------------------------------------|---|--|-------------|--------|
| 1. CPU                               |   |  |             |        |
| 1.1 Register                         | Stuck at                                | static memory test                         | H. 2.19.6   | YES    |
| 1.2 Program counter                  | Stuck at                                | logical monitoring of the program sequence | H.2.18.10.2 | YES    |
| 2. Interrupt                         | No interrupt or too frequency interrupt | Time-slot monitoring                       | H.2.18.10.4 | YES    |
| 3. Clock                             | Wrong frequency                         | Frequency monitor                          | H.2.18.10.1 | YES    |
| 4. Memory                            |   |  |             |        |
| 4.1. Invariable memory               | All single bit faults                   | Redundancy check                           | H.2.19.3.2  | YES    |
| 4.2. Variable memory                 | DC fault                                | static memory test                         | H.2.19.6    | YES    |
| 4.3. Address <sup>[1]</sup>          | Stuck at                                | Redundancy check                           | -           | YES    |
| 5. Internal data path <sup>[2]</sup> | Stuck at                                | -  | -           | NO     |
| 6.External communication             |   |  |             |        |
| 6.1 Data <sup>[3]</sup>              | Hamming distance 3                      | -  | -           | NO     |
| 6.3 Timing                           | Wrong point in time                     | -  | -           | NO     |
| 7. Input/output periphery            |   |  |             |        |
| 7.1 Digital I/O                      | Function error                          | Output verification                        | H.2.18.12   | YES    |
| 7.2 A/D                              | Function error                          | Input comparison                           | H.2.18.8    | YES    |

**Notes:**


1. The address test can be partly covered by test method of invariable and variable memory test. E.g. the error that two cells are mapped to a same address can be identified when doing invariable memory test with CRC test.
2. Internal data path is only tested when using external memory.
3. The external communication test is not involved in this STL. But external communication data can be tested with similar method of invariable memory test.

### 3 IEC60730 Class B STL Overview

As shown in following figure, the STL block diagram includes CPU, Interrupt, Clock, Memory, and Input/output peripheral module. It shows file structure and software APIs in the STL. The STL is coded by mixed C and assembly language.

FM0P IEC60730 STL should be compatible with ARM, IAR compiler. So STL supplies two kinds of CPU test.s and ram test.s files according to different compilers.

Figure 1. FM3 IEC60730 Class B STL Block Diagram



The STL consists of several independent function modules, which have to be executed once or cyclically as required by the application.

The test function implemented once is called Power-On Self-Test (POST), which should be implemented in system initialization, this test is always complete but destructive(need Initialize), which means it covers full test area but the data is not restored after executing test. PC, register, ROM/RAM, IO, AD test are all POST.

The test function implemented cyclically is called Build-In Self-Test (BIST), which should be implemented in main loop or timer interrupt service routine in a certain interval, this test will not change test data and act as a monitor when program is running. Interrupt and clock are BIST.

#### Notes:

1. The library should be used as explained, if any part is changed, a new validation is needed for these parts.
2. This library is usable, as-is, for all Cypress Cortex-M0+ MCU, including those not especially mentioned in this application notes.
3. The prefix of file and function name is omitted for easy description.
4. The STL provides two types of assembly files for CPU and RAM test for IAR and Keil IDE.
5. User has alternative test method in clock and Flash test.

## 4 IEC60730 Class B STL API

### 4.1 CPU Register Test

ARM Cortex-M0+ has 19 core registers, which can be read and written. These registers below need to be tested.

| Register Name                            | Bits tested |
|--|-------------|
| R0-R12                                   | [31:0]      |
| R13 (SP_main, SP_process) <sup>[1]</sup> | [31:4]      |
| R14 (LR)                                 | [31:0]      |
| APSR <sup>[2]</sup>                      | [31:27]     |
| PRIMASK <sup>[3]</sup>                   | 0           |
| FAULTMASK <sup>[4]</sup>                 | 0           |
| BASEPRI <sup>[5]</sup>                   | [7:4]       |

Table 4-1: Cotex-M0+ Register List

**Notes:**

1. ARM Cortex-M0+ kernel has two stack pointers: main stack pointer (MSP) and process stack pointer (PSP). Handler mode uses MSP and process mode uses MSP or PSP. R13 indicates current SP.
2. Only high 4 bits of APSR is valid.
3. Only bit 0 of PRIMASK is valid.
4. Only bit 0 of FAULTMASK is valid.
5. 16 interrupt priority levels can be configured by bit[7:4] of Interrupt Priority Registers in FM3 MCU, so only bit[7:4] of BASEPRI can be used to mask user interrupt.

#### 4.1.1 Test Description


As shown at table H.11.12.7, registers must be checked for “stuck-at error”, a simple checkerboard method is used to implement register test, which is an effective method to detect stuck-at error.

This test should be called at startup file when system resets in Privileged mode, as kernel registers needs to be accessed. This test does not disable interrupts during the register test. It is the responsibility of the application to disable interrupts when this function is called to ensure that the register test is not interrupted.

Assembly is used to implement register test due to access to registers directly. And as it is highly critical, it is designed that once register test error is detected, program will run into an infinite loop.

The flow chart to test 1 register is shown as following figure.

Figure 2. Test 1 Register



#### 4.1.2 API Definition

|                  |                   |
|------------------|-------------------|
| <b>Name</b>      | iec60730_reg_test |
| <b>Parameter</b> | None              |
| <b>Return</b>    | None              |

##### Description:

This function tests all registers including R0-R12 (low: R0-R7, high: R8-R12) special registers (SP, LR, APSR, PRIMASK) with checkerboard method. This function should be called at reset handler.



## 4.2 CPU PC Test

### 4.2.1 Test Description


As shown at table H.11.12.7, PC must be checked for “stuck-at error”. PC test makes use of 8 subroutines and validates if PC value gotten from each subroutines is same with pre-define value.

This test should be called at startup file when system resets in Privileged mode. This test does not disable interrupts during the register test. It is the responsibility of the application to disable interrupts when this function is called to ensure that the register test is not interrupted.

Assembly is used to implement PC test due to access to PC register directly. As it is highly critical, it is designed that once PC test error is detected, program will run into an infinite loop.

The PC test flow is shown as following figure.

Figure 3. PC Test Flow Chart



### 4.2.2 API Definition

|                  |                  |
|------------------|------------------|
| <b>Name</b>      | iec60730_pc_test |
| <b>Parameter</b> | None             |
| <b>Return</b>    | None             |

#### Description:

This function jumps to subroutines at different areas and gets the subroutine address, then verifies whether address gotten is correct. It should be called at reset handler.


## 4.3 Interrupt Test

### 4.3.1 Test Description

To meet Class B requirement, interrupt must be checked for “incorrect frequency”. This test is a task which is highly system dependent and therefore the STL can only contribute the wrap up handle, which checks that a number of specific interrupts occurred at least and at most a predefined number of times. It is assumed that **IEC60730\_IntTest** (interrupt test function) is called in specified intervals, e.g. triggered by a timer or line frequency interrupt. Each specific interrupt handler which is to be supervised, must decrement a dedicated global variable (**Freq**) by calling **IEC60730\_IntCnt**, **IEC60730\_IntTest** compares that variable to predefined upper and lower bounds, sets it to its preset value and returns an error, if the limits are exceeded.

For example, measure if timer 0-3 interrupts happen 5 times in 10 second, assume 10 second timing can be gotten by a reload timer and set the range of interrupt frequency of timer 0-3 at [3, 7].

Figure 4. Interrupt Test Block Diagram



The interrupt test is independent from user application. User just needs to add the interrupt test API into his interrupt which he wants to test.

### 4.3.2 API Definition

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_IntTestInit</b>   |
| <b>Parameter</b> | pFreq: pointer to frequency counters<br>pFreqLower: pointer to lower frequencies<br>pFreqUpper: pointer to upper frequencies<br>pFreqInitial: pointer to frequency initial value<br>ArraySize: pointer to interrupt num |
| <b>Return</b>    | None  |

#### Description:

This function initializes str\_int\_test\_par\_t structure for interrupt test, which includes pre-defined frequency ranges and frequency initial values. It should be called at system initialization, before interrupt test starts.

|                  |                           |
|------------------|---------------------------|
| <b>Name</b>      | <b>IEC60730_IntCntPro</b> |
| <b>Parameter</b> | IntNum: interrupt number  |
| <b>Return</b>    | None                      |

#### Description:

This function decreases frequency counter of the interrupt specified by the interrupt number, and should be called in the interrupt which to be supervised.

|                  |  |
|------------------|--|
| <b>Name</b>      | <b>IEC60730_IntTest</b>                                |
| <b>Parameter</b> | None   |
| <b>Return</b>    | 0: IEC60730_TEST_NORMAL<br>1: IEC60730_TEST_FUNC_ERROR |

#### Description:

This is interrupt test main function, which verifies whether the interrupts are handled in time. It should be called at a timer interrupt or main loop in a certain interval.

## 4.4 Clock Test

### 4.4.1 Test Description

To meet Class B requirement, CPU clock must be checked for “wrong frequency”. This requires a second independent clock as a standard clock for clock test. This library provides two ways to implement clock test. First, FM0+ MCU has integrated a watch counter which can be sourced by an external sub clock (32.768kHz oscillator). The sub clock can be treated as the standard clock. For the second, FM0+ MCU has integrated a **Clock Supervisor** (in following called **CSV**), which includes the functions: Clock failure detection and Anomalous frequency detection. The CSV can also be used for clock test.


User should enable the definition “IEC60730\_CLKTEST\_USE\_CSV” in IEC60730\_user.h file if he wants to use CSV to perform clock test.

#### Use watch counter to do clock test

This test takes watch counter as standard clock, and tests whether the frequency of CPU clock is within acceptable bound by verifying a time tick which is counted in a timer interrupt. The source clock of timer interrupt should be same with CPU clock. The case that CPU clock is sourced by sub clock can not be tested, as 32.768kHz oscillator is assumed accurate.


These test functions are implemented: **IEC60730\_ClkCnt**, **IEC60730\_ClkTest**, and **IEC60730\_ClkMonMainloop**, shown as following figure. The timer interrupt occurrence frequency is monitored by watch counter and the watch counter interrupt occurrence is checked in main loop.

Figure 5. Clock Test Block Diagram



The API **IEC60730\_ClkCnt** is used to count a global variable “freq”, which is called in a timer interrupt handler, the source clock of timer should be same with CPU clock. The flowchart of **IEC60730\_ClkCnt** is shown as following figure.


Figure 6. Clock Counter Flowchart



**Note:** The global variable “freq” starts to count until first watch counter interrupt occurred, because it is a limitation of watch counter in FM3 MCU that the first count cycle is 2 times of normal cycle. So the first watch counter interrupt should be ignored.


API **IEC60730\_ClkTest** is to check whether “freq” is in pre-defined range, which is called in watch counter interrupt handler.

Figure 7. Clock Test Flowchart



API **IEC60730\_ClkMonInMainloop** guarantees the occurrence of watch counter interrupt in a certain period, this period depends on the threshold value set by user according to a real application. The flowchart of **IEC60730\_ClkMonMainInloop** is shown as following figure.

Figure 8. Clock Main Loop Monitor Flowchart




#### Use CSV to do clock test

The CSV has two types of functions: **Clock failure detection (CSV: Clock failure detection by clock Super Visor)** and **Anomalous frequency detection (FCS: anomalous Frequency detection by Clock Super visor)**.


The clock failure detection monitors the main and sub clocks. If a rising edge of the monitored clock is not detected within the specified period, this function determines that the oscillator has failed, and outputs a system reset request. The main clock is monitored with the high-speed CR clock, and the sub clock is monitored with the low-speed CR clock. When a rising edge is not detected within 32 clocks of high-speed CR for the main clock, or within 32 clocks of low-speed CR for the sub clock, this function determines that the oscillator has failed. Figure 4-8 shows the block diagram of the clock failure detection.

Figure 9. Clock Failure Detection Block Diagram



The Anomalous frequency detection monitors the main clock. Within the specified period between an edge and the next edge of the divided clock of high-speed CR, this function counts up the internal counter using the main clock. If the count value reaches out of the set window range, the function determines that the main clock frequency is anomalous, and outputs an interrupt request or a system reset request to the CPU. Figure 10 shows the block diagram of the anomalous frequency detection.


Figure 10. Anomalous Frequency Detection Block Diagram



Two test functions are implemented: **IEC60730\_InitCSV** and **IEC60730\_CheckCSVStat**.

The API **IEC60730\_InitCSV** provides a selection for user to disable/enable Clock failure detection and Anomalous frequency detection functions. It should be called before system clock initialization. Figure 11 shows the flow chart of it.

Figure 11. IEC60730\_InitCSV Flow Chart




**Notes:**

1. The default high-speed CR trimming value is stored in the address 0x00100004 when leaving factory.
2. If the CR trimming value in the address 0x00100004 is destroyed, a typical value must be written into the trimming register MCR\_FTRM.
3. When setting the expected accuracy of main clock, high-speed CR frequency should also be considered. Consider the high-speed CR oscillator precision is  $4M\pm3\%$  (As found in data sheet, for MB9B100A / MB9B300A / MB9B400A / MB9B500A, the high-speed CR oscillator precision is  $4M\pm2\%$  in 25°C, so  $4M\pm3\%$  is used for a little margin). The base upper and lower count can be calculated by following formula.  
 base lower count (operating in +3.0%) =  $1/[(\text{freq}/512^*) \times (1 + 0.03)] \times \text{freq} = 512/1.03 = 497$   
 base upper count (operating in -3.0%) =  $1/[(\text{freq}/512^*) \times (1 - 0.03)] \times \text{freq} = 512/0.97 = 528$   
 If 5% accuracy is set, lower count =  $497 \times 0.95 = 472$  upper count =  $528 \times 1.05 = 554$
4. After enable CSV function, a reset will occurred when a rising edge is not detected within 32 clocks of high-speed CR for the main clock, or within 32 clocks of low-speed CR for the sub clock.
5. After enable FCS function and FCS interrupt, a FCS interrupt will occur if main clock frequency is detected not in the setting range, but FCS reset is set not to output.

The API **IEC60730\_CheckCSVStat** is used to check if Clock failure detection or Anomalous frequency detection happens. This API should be called before **IEC60730\_InitCSV**. Figure 12 shows the flow chart of it.

Figure 12. IEC60730\_CheckCSVStat Flow Chart





#### 4.4.2 API Definition

##### Use watch counter to do clock test

|                  |                        |
|------------------|------------------------|
| <b>Name</b>      | <b>IEC60730_ClkCnt</b> |
| <b>Parameter</b> | None                   |
| <b>Return</b>    | None                   |

##### Description:

This API is used to count clock frequency, which should be called in the timer interrupt.

|                  |  |
|------------------|--|
| <b>Name</b>      | <b>IEC60730_ClkTest</b>                                |
| <b>Parameter</b> | None   |
| <b>Return</b>    | 0: IEC60730_TEST_NORMAL<br>1: IEC60730_TEST_FUNC_ERROR |

##### Description:

This API tests if the frequency of CPU clock is within acceptable bound by verifying a time tick which is counted in a timer interrupt. It should be called in the watch counter interrupt, which is sourced by an independent 32.768kHz clock (sub-clock of FM4 MCU).

|                  |  |
|------------------|--|
| <b>Name</b>      | <b>IEC60730_ClkMonInMainloop</b>                       |
| <b>Parameter</b> | None   |
| <b>Return</b>    | 0: IEC60730_TEST_NORMAL<br>1: IEC60730_TEST_FUNC_ERROR |

##### Description:

This API is used to monitor watch counter interrupt occurrence, it should be called in main loop.

|                  |                              |
|------------------|------------------------------|
| <b>Name</b>      | <b>IEC60730_ClkTestReset</b> |
| <b>Parameter</b> | None                         |
| <b>Return</b>    | None                         |

##### Description:

This API resets interrupt test variables.

|                  |  |
|------------------|--|
| <b>Name</b>      | <b>IEC60730_ClkInit</b>  |
| <b>Parameter</b> | FreqLower: indicate timer interrupt minimum occur frequency<br>FreqUpper: indicate timer interrupt maximum occur frequency<br>ClkTestThreshold: indicate threshold value |
| <b>Return</b>    | None   |

##### Description:

This API should be called at system initialization before clock test starts.

The parameter FreqLower and FreqUpper should be set according to actual example. For example, if user uses 1s interval for watch counter to monitor a 50ms timer interrupt. The value FreqLower =18, FreqUpper =22 can be set as bound of timer clock frequency, the standard of which is 20.

It is important to estimate threshold value, which should be at least 1s/mainloop execution time.

**Use CSV to do clock test**

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_CheckCSVStat</b>                        |
| <b>Parameter</b> | pRegRSTStat: get the data from reset cause register |
| <b>Return</b>    | None  |

**Description:**

This API is used to check if Clock failure detection or anomalous frequency detection happens. The parameter "pRegRSTStat" store the address of data read from reset cause register. This API only handles the reset caused by CSV, otherwise it will return normal status. It should be called before IEC60730\_InitCSV.

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_InitCSV</b>   |
| <b>Parameter</b> | CSV_MCLKMonEn: 0: disable CSV main clock monitor 1:enable CSV main clock monitor<br>CSV_SCLKMonEn: 0: disable CSV sub clock monitor 1:enable CSV sub clock monitor<br>FCS_MONInfo: a fcs_mon_info_t structure<br>typedef struct fcs_mon_info<br>{<br>stl_uint8_t FCSMonEn;               /* 0: disable FCS function, 1: enable FCS function */<br>stl_uint8_t MCLKFreqAccuracy; /* input the excepted accuracy of main clock, 5->5% */<br>} fcs_mon_info_t; |
| <b>Return</b>    | 0: IEC60730_TEST_NORMAL<br>2: IEC60730_TEST_PARA_ERROR  |

**Description:**

This API can enable/disable CSV main/sub clock function, and input the expected accuracy of main clock frequency. It should be called before system clock initialization.

## 4.5 Invariable Memory Test

Invariable memory in FM3 MCU means On-Chip Flash. The Flash size can be configured according to different product shown as [Table 1](#).


FM3 MCU integrates an On-Chip CRC module. The CRC (Cyclic Redundancy Check) module is an error detection system. The CRC code is a remainder after an input data string is divided by the pre-defined generator polynomial, assuming the input data string is a high order polynomial. Ordinarily, a data string is suffixed by a CRC code when being sent, and the received data is divided by a generator polynomial as described above. If the received data is dividable, it is judged to be correct. On-Chip Flash Test confirms with CRC that data and program is correct.

This module can either use CCITT CRC16 or IEEE-802.3 CRC32, which can be configured by CRCCR: CRC32 bit. In this module, the generator polynomials are fixed to the numeric values for those two modes.

- CCITT CRC16 generator polynomial: 0x1021(Omitted most significant bit of 0x11021)
- IEEE-802.3 CRC32 generator polynomial: 0x04C11DB7

Following figure shows an application of CRC test when FM3 MCU communicates with other devices.

Figure 13. CRC test by communication



### 4.5.1 Test Description

To meet Class B requirement, Flash test must be checked for "single bit fault". This test can be implemented as CRC16/32 test. On-Chip CRC module is used to implement hardware CRC16/32 test, and software CRC16/32 are also provided with same implementation arithmetic as hardware CRC

Enable the definition "FLASH\_TEST\_USE\_CRC16" in IEC60730\_user.h file if user wants to use CRC16 arithmetic for Flash test, otherwise CRC32 arithmetic will be implemented.

This test can be implemented at startup procedure to test whole code area, or it can also be called periodically to test sub blocks. Flash Test compares the generated CRC code at the time of test with the stored CRC code when build by a workbench tool. See, [8.1CRC code making method](#) for generating CRC code with a workbench tool.


**Note:** The CRC can also be used to test external communication data, which fulfills H.2.19.4.1 to detect hamming distance 3 errors.

## ■ Hardware CRC

The procedure to generate CRC code with hardware CRC module can be described as following steps.

- (1) Initial CRC control register CRCCR and initial value register CRCINIT
- (2) Write “1” to the initial value bit (CRCCR:INIT). The value of CRCINIT is loaded into CRC register CRCCR.
- (3) Write data into input data register CRCIN continuously. Then CRC calculation starts. To obtain a CRC code, read the CRC register (CRCCR).

Figure 14. Sequence of generating CRC code



## ■ Software CRC

### Software CRC16 Arithmetic

The CRC table enquiry method is used. The software CRC16 arithmetic should implement 6 steps to generate a new CRC code.

- (1) Initialize CRC code in 0xFFFF.
- (2) Store CRC code in “temp” after having divided it by 256.
- (3) Left shift 8 bits of the CRC code.
- (4) Store the CRC code by XOR CRC code with the data gotten from CRC table (use the data which calculated by XOR “temp” with the target data for a table index).
- (5) Increment the target data for 1 byte.
- (6) Repeat processes of (2) to (5) until byte size of target data.

The software CRC16 generation code and CRC16 table is shown as following figure.

Figure 15. Software CRC16 Generation Source Code

```

stl uint16 t IEC60730 SoftwareCRC16Gen(stl uint8 t *pData, stl uint32 t Size)
{
    stl uint8 t temp;
    stl uint8 t *p temp data = pData;
    stl uint16 t crc = 0xFFFF;
    while(Size-- != 0)
    {
        temp = crc/256;
        crc <<= 8;
        crc ^= CRCTable[temp^*p temp data];
        p temp data++;
    }
    return crc;
}
  
```

Figure 16. CRC16 table

```
const stl_uint16_t crc_table[256]={
    0x0000, 0x1021, 0x2042, 0x3063, 0x4084, 0x50A5, 0x60C6, 0x70E7,
    0x8108, 0x9129, 0xA14A, 0xB16B, 0xC18C, 0xD1AD, 0xE1CE, 0xF1EF,
    0x1231, 0x0210, 0x3273, 0x2252, 0x52B5, 0x4294, 0x72F7, 0x62D6,
    0x9339, 0x8318, 0xB37B, 0xA35A, 0xD3BD, 0xC39C, 0xF3FF, 0xE3DE,
    0x2462, 0x3443, 0x0420, 0x1401, 0x64E6, 0x74C7, 0x44A4, 0x5485,
    0xA56A, 0xB54B, 0x8528, 0x9509, 0xE5EE, 0xF5CF, 0xC5AC, 0xD58D,
    0x3653, 0x2672, 0x1611, 0x0630, 0x76D7, 0x66F6, 0x5695, 0x46B4,
    0xB75B, 0xA77A, 0x9719, 0x8738, 0xF7DF, 0xE7FE, 0xD79D, 0xC7BC,
    0x48C4, 0x58E5, 0x6886, 0x78A7, 0x0840, 0x1861, 0x2802, 0x3823,
    0xC9CC, 0xD9ED, 0xE98E, 0xF9AF, 0x8948, 0x9969, 0xA90A, 0xB92B,
    0x5AF5, 0x4AD4, 0x7AB7, 0x6A96, 0x1A71, 0x0A50, 0x3A33, 0x2A12,
    0xDBFD, 0xCBDC, 0xFBBF, 0xEB9E, 0x9B79, 0x8B58, 0xBB3B, 0xAB1A,
    0x6CA6, 0x7C87, 0x4CE4, 0x5CC5, 0x2C22, 0x3C03, 0x0C60, 0x1C41,
    0xEDAE, 0xFD8F, 0xCDEC, 0xDDCD, 0xAD2A, 0xBD0B, 0x8D68, 0x9D49,
    0x7E97, 0x6EB6, 0x5ED5, 0x4EF4, 0x3E13, 0x2E32, 0x1E51, 0x0E70,
    0xFF9F, 0xEFBE, 0xDFDD, 0xCFFC, 0xBF1B, 0xAF3A, 0x9F59, 0x8F78,
    0x9188, 0x81A9, 0xB1CA, 0xA1EB, 0xD10C, 0xC12D, 0xF14E, 0xE16F,
    0x1080, 0x00A1, 0x30C2, 0x20E3, 0x5004, 0x4025, 0x7046, 0x6067,
    0x83B9, 0x9398, 0xA3FB, 0xB3DA, 0xC33D, 0xD31C, 0xE37F, 0xF35E,
    0x02B1, 0x1290, 0x22F3, 0x32D2, 0x4235, 0x5214, 0x6277, 0x7256,
    0xB5EA, 0xA5CB, 0x95A8, 0x8589, 0xF56E, 0xE54F, 0xD52C, 0xC50D,
    0x34E2, 0x24C3, 0x14A0, 0x0481, 0x7466, 0x6447, 0x5424, 0x4405,
    0xA7DB, 0xB7FA, 0x8799, 0x97B8, 0xE75F, 0xF77E, 0xC71D, 0xD73C,
    0x26D3, 0x36F2, 0x0691, 0x16B0, 0x6657, 0x7676, 0x4615, 0x5634,
    0xD94C, 0xC96D, 0xF90E, 0xE92F, 0x99C8, 0x89E9, 0xB98A, 0xA9AB,
    0x5844, 0x4865, 0x7806, 0x6827, 0x18C0, 0x08E1, 0x3882, 0x28A3,
    0xCB7D, 0xDB5C, 0xEB3F, 0xFB1E, 0x8BF9, 0x9BD8, 0xABBB, 0xBB9A,
    0x4A75, 0x5A54, 0x6A37, 0x7A16, 0x0AF1, 0x1AD0, 0x2AB3, 0x3A92,
    0xFD2E, 0xED0F, 0xDD6C, 0xCD4D, 0xBDAA, 0xAD8B, 0x9DE8, 0x8DC9,
    0x7C26, 0x6C07, 0x5C64, 0x4C45, 0x3CA2, 0x2C83, 0x1CE0, 0x0CC1,
    0xEF1F, 0xFF3E, 0xCF5D, 0xDF7C, 0xAF9B, 0xBFBA, 0x8FD9, 0x9FF8,
    0x6E17, 0x7E36, 0x4E55, 0x5E74, 0x2E93, 0x3EB2, 0x0ED1, 0x1EF0
};
```

### Software CRC32 Arithmetic

The CRC table enquiry method is used. The software CRC32 arithmetic should implement 6 steps to generate a new CRC code.

- (1) Initialize CRC code in 0xFFFFFFFF.
- (2) Store CRC code in “temp” after having 24 bits shifted it.
- (3) Store the CRC code by XOR left 8 bits shifted CRC code with the data gotten from CRC table (use the data which calculated by XOR “temp” with the target data for a table index).
- (4) Increment the target data for 1 byte.
- (5) Repeat processes of (2) to (4) until byte size of target data.
- (6) Finally, return reversed bit of CRC code.

The software CRC32 generation code and CRC32 table is shown as following figure.

Figure 17. Software CRC32 Generation Source Code

```
stl uint32 t IEC60730 SoftwareCRC32Gen(stl uint8 t *pData, stl uint32 t Size)
{
    stl_uint8_t temp;
    stl uint8 t *p temp data = pData;
    stl uint32 t crc = 0xFFFFFFFF;
    while(Size--)
    {
        temp=( crc >> 24 );
        crc = ( crc << 8 ) ^ CRCTable[temp^*p_temp_data];
        p temp data++;
    }
    return ~crc;
}
```

Figure 18. CRC32 table

```

const stl uint32 t CRCTable[256]={
    0x00000000L, 0x04c11db7L, 0x09823b6eL, 0x0d4326d9L,
    0x130476dcL, 0x17c56b6bL, 0x1a864db2L, 0x1e475005L,
    0x2608edb8L, 0x22c9f00fL, 0x2f8ad6d6L, 0x2b4bcb61L,
    0x350c9b64L, 0x31cd86d3L, 0x3c8ea00aL, 0x384fbbdbL,
    0x4c11db70L, 0x48d0c6c7L, 0x4593e01eL, 0x4152fda9L,
    0x5f15adacL, 0x5bd4b01bL, 0x569796c2L, 0x52568b75L,
    0x6a1936c8L, 0x6ed82b7fL, 0x639b0da6L, 0x675a1011L,
    0x791d4014L, 0x7ddc5da3L, 0x709f7b7aL, 0x745e66cdL,
    0x9823b6e0L, 0x9ce2ab57L, 0x91a18d8eL, 0x95609039L,
    0x8b27c03cL, 0x8fe6dd8bL, 0x82a5fb52L, 0x8664e6e5L,
    0xbe2b5b58L, 0xbaea46efL, 0xb7a96036L, 0xb3687d81L,
    0xad2f2d84L, 0xa9ee3033L, 0xa4ad16eaL, 0xa06c0b5dL,
    0xd4326d90L, 0xd0f37027L, 0xddb056feL, 0xd9714b49L,
    0xc7361b4cL, 0xc3f706fbL, 0xceb42022L, 0xca753d95L,
    0xf23a8028L, 0xf6fb9d9fL, 0xfbb8bb46L, 0xff79a6f1L,
    0xe13ef6f4L, 0xe5ffeb43L, 0xe8bccd9aL, 0xec7dd02dL,
    0x34867077L, 0x30476dc0L, 0x3d044b19L, 0x39c556aeL,
    0x278206abL, 0x23431b1cL, 0x2e003dc5L, 0x2ac12072L,
    0x128e9dcfL, 0x164f8078L, 0x1b0ca6a1L, 0x1fcdabb1L,
    0x018aeb13L, 0x054bf6a4L, 0x0808d07dL, 0x0cc9cdcaL,
    0x7897ab07L, 0x7c56b6b0L, 0x71159069L, 0x75d48ddeL,
    0x6b93dddL, 0x6f52c06cL, 0x6211e6b5L, 0x66d0fb02L,
    0x5e9f46bfL, 0x5a5e5b08L, 0x571d7dd1L, 0x53dc6066L,
    0x4d9b3063L, 0x495a2dd4L, 0x44190b0dL, 0x40d81bbaL,
    0xaca5c697L, 0xa864db20L, 0xa527fdf9L, 0xale6e04eL,
    0xbfa1b04bL, 0xbb60adfcL, 0xb6238b25L, 0xb2e29692L,
    0x8aad2b2fL, 0x8e6c3698L, 0x832f1041L, 0x87ee0df6L,
    0x99a95df3L, 0x9d684044L, 0x902b669dL, 0x94ea7b2aL,
    0xe0b41de7L, 0xe4750050L, 0xe9362689L, 0xedf73b3eL,
    0xf3b06b3bL, 0xf771768cL, 0xfa325055L, 0xfef34de2L,
    0xc6bcf05fL, 0xc27dede8L, 0xcf3ecb31L, 0xcbffd686L,
    0xd5b88683L, 0xd1799b34L, 0xdc3abdedL, 0xd8fba05aL,
    0x690ce0eeL, 0x6dcdfd59L, 0x608edb80L, 0x644fc637L,
    0x7a089632L, 0x7ec98b85L, 0x738aad5cL, 0x774bb0ebL,
    0x4f040d56L, 0x4bc510e1L, 0x46863638L, 0x42472b8fL,
    0x5c007b8aL, 0x58c1663dL, 0x558240e4L, 0x51435d53L,
    0x251d3b9eL, 0x21dc2629L, 0x2c9f0f0L, 0x285e1d47L,
    0x36194d42L, 0x32d850f5L, 0x3f9b762cL, 0x3b5a6b9bL,
    0x0315d626L, 0x07d4cb91L, 0x0a97ed48L, 0x0e560fffL,
    0x1011a0faL, 0x14d0bd4dL, 0x19939b94L, 0x1d528623L,
    0xf12f560eL, 0xf5ee4bb9L, 0xf8ad6d60L, 0xfc6c70d7L,
    0xe22b20d2L, 0xe6ea3d65L, 0xeba91bbcL, 0xef68060bL,
    0xd727bbb6L, 0xd3e6a601L, 0xdea580d8L, 0xda649d6fL,
    0xc423cd6aL, 0xc0e2d0ddL, 0xcda1f604L, 0xc960ebb3L,
    0xbd3e8d7eL, 0xb9ff90c9L, 0xb4bcb610L, 0xb07daba7L,
    0xae3afba2L, 0xaafbe615L, 0xa7b8c0ccL, 0xa379dd7bL,
    0x9b3660c6L, 0x9ff77d71L, 0x92b45ba8L, 0x9675461fL,
    0x8832161aL, 0x8cf30badL, 0x81b02d74L, 0x857130c3L,
    0x5d8a9099L, 0x594b8d2eL, 0x5408abf7L, 0x50c9b640L,
    0x4e8ee645L, 0x4a4ffbf2L, 0x470cdd2bL, 0x43cdc09cL,
    0x7b827d21L, 0x7f436096L, 0x7200464fL, 0x76c15bf8L,
    0x68860bf4L, 0x6c47164aL, 0x61043093L, 0x65c52d24L,
    0x119b4be9L, 0x155a565eL, 0x18197087L, 0x1cd86d30L,
    0x029f3d35L, 0x065e2082L, 0x0b1d065bL, 0x0fcd1becL,
    0x3793a651L, 0x3352bbe6L, 0x3e119d3fL, 0x3ad08088L,
    0x2497d08dL, 0x2056cd3aL, 0x2d15ebe3L, 0x29d4f654L,
    0xc5a92679L, 0xc1683bceL, 0xcc2b1d17L, 0xc8ea00a0L,
    0xd6ad50a5L, 0xd26c4d12L, 0xdf2f6bcbL, 0xdbee767cL,
    0xe3alc1c1L, 0xe760d676L, 0xea23f0afL, 0xee2ed18L,
    0xf0a5bd1dL, 0xf464a0aaL, 0xf9278673L, 0xfde69bc4L,
    0x89b8fd09L, 0x8d79e0beL, 0x803ac667L, 0x84fbbdb0L,
    0x9abc8bd5L, 0x9e7d9662L, 0x933eb0bbL, 0x97ffad0cL,
    0xafb010b1L, 0xab710d06L, 0xa6322bdfL, 0xa2f33668L,
    0xbcb4666dL, 0xb8757bdaL, 0xb5365d03L, 0xb1f740b4L
};

```

#### 4.5.2 API Definition

##### Use CRC16 arithmetic to implement Flash test

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_SoftwareCRC16Gen</b>            |
| <b>Parameter</b> | pData: test data address<br>Size: data size |
| <b>Return</b>    | CRC value                                   |

##### Description:

This API implements CRC16 generation by internal hardware CRC generator. The CCITT CRC16 generator polynomial: 0x 1021(Omitted most significant bit of 0x11021).

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_SoftwareCRC16Test</b>                                     |
| <b>Parameter</b> | pData: test data address<br>Size: data size<br>Crc: expected CRC code |
| <b>Return</b>    | 0: IEC60730_TEST_NORMAL<br>1: IEC60730_TEST_FUNC_ERROR                |

##### Description:

This API implements software CRC16 test, it can be called at startup procedure to test all code area or test sub blocks periodically when code is running.

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_SoftwareCRC16Gen</b>            |
| <b>Parameter</b> | pData: test data address<br>Size: data size |
| <b>Return</b>    | CRC value                                   |

##### Description:

This API implements CRC16 generation by software CRC arithmetic. The CRC table enquiry method is used. It provides a reference CRC method that On-chip CRC is implemented in a software way. It may be used in other system with which FM3 MCU communicate.

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_SoftwareCRC16Test</b>                                     |
| <b>Parameter</b> | pData: test data address<br>Size: data size<br>Crc: expected CRC code |
| <b>Return</b>    | 0: IEC60730_TEST_NORMAL<br>1: IEC60730_TEST_FUNC_ERROR                |

##### Description:

This API implements software CRC16 test, this test may be implemented in other system with which FM3 MCU communicate.



### Use CRC32 arithmetic to implement Flash test

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_HardwareCRC32Gen</b>            |
| <b>Parameter</b> | pData: test data address<br>Size: data size |
| <b>Return</b>    | CRC value                                   |

#### Description:

This API implements CRC32 generation by internal hardware CRC generator.

The CRC32 generator polynomial: 0x04C11DB7

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_HardwareCRC32Test</b>                                     |
| <b>Parameter</b> | pData: test data address<br>Size: data size<br>Crc: expected CRC code |
| <b>Return</b>    | 0: IEC60730_TEST_NORMAL<br>1: IEC60730_TEST_FUNC_ERROR                |

#### Description:

This API implements hardware CRC32 test, it can be called at startup procedure to test all code area or test sub blocks periodically when code is running.

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_SoftwareCRC32Gen</b>            |
| <b>Parameter</b> | pData: test data address<br>Size: data size |
| <b>Return</b>    | CRC value                                   |

#### Description:

This API implements CRC32 generation by software CRC arithmetic. The CRC table enquiry method is used. It provides a reference CRC method that On-chip CRC is implemented in a software way. It may be used in other system with which FM3 MCU communicate.

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_SoftwareCRC32Test</b>                                     |
| <b>Parameter</b> | pData: test data address<br>Size: data size<br>Crc: expected CRC code |
| <b>Return</b>    | 0: IEC60730_TEST_NORMAL<br>1: IEC60730_TEST_FUNC_ERROR                |

#### Description:

This API implements software CRC32 test, this test may be implemented in other system with which FM3 MCU communicate.

## 4.6 Variable Memory Test

Variable memory test in FM3 MCU means SRAM test, the SRAM size can be configured according to different product, shown as [Table 1](#).

### 4.6.1 Test Description


To meet Class B requirement, SRAM test must be checked for “DC fault”. A simple checkerboard method is used to implement this SRAM.

This test can be implemented at startup procedure to test entire SRAM area. And it can also test sub blocks periodically when code is running, however user should pay attention that the data will be destroyed after test.

As all RAM area is involved in this test, it is better not to use variable in this test, so assembly is used to implement register test. And as it is highly critical, it is designed that once RAM test error is detected, program will run into an infinite loop.

The procedure to test 1 word data is shown as following figure.

Figure 19. Test 1 Word with Checkerboard Method



### 4.6.2 API Definition

|                  |  |
|------------------|--|
| <b>Name</b>      | <b>iec60730_ram_test</b>   |
| <b>Parameter</b> | StartAddr(R0): start RAM address<br>EndAddr(R1): end RAM address |
| <b>Return</b>    | None   |

#### Description:

This API tests SRAM area with Checkerboard arithmetic which writes alternate “0” and “1” to memory, and verifies if the write data is right by reading back the data written. It can detect stuck-at faults and direct coupling faults.

This test should be called in startup procedure, and it can also be called in cycle, but the data is not saved after test.

## 4.7 IO Test

FM3 MCU has up to 8 IO ports: Port0-Port8, each port has up to 16 channels. These ports can be configured according to different package.

### 4.7.1 Test Description

To meet Class B requirement, GPIO must be check for "Function error". So function test is implemented for both input and output function. The IO direction can be configured by IO register shown in [Figure 15](#). Please refer to the peripheral manual for detail of GPIO.


- Input IO configuration: ADE=0,PFR=0,DDR=0
- Output IO configuration: ADE=0,PFR=0,DDR=1

**Table 2. IO Function Configuration**

| I/O Port Function                     |  | ADE/<br>SPSR | PFR | DDR | PCR        |
|---------------------------------------|--|--------------|-----|-----|------------|
| Available main function               | Available sub function   |              |     |     |            |
| Special pin Analog Input Oscillation  | N/A  | 1            | -   | -   | Disconnect |
| GPIO function input pin               | Peripheral function input pin                                      | 0            | 0   | 0   | Valid      |
| GPIO function output pin              | GPIO function input pin (FB)<br>Peripheral function input pin (FB) |              |     | 1   | Disconnect |
| Peripheral function output pin        | GPIO function input pin (FB)<br>Peripheral function input pin (FB) |              | 1   | -   | Disconnect |
| Peripheral function bidirectional pin | GPIO function input pin (FB)<br>Peripheral function input pin (FB) |              |     |     | Valid      |
| Peripheral function input pin         | GPIO function input pin  |              |     |     | Valid      |

The IO input test checks if selected IO input value which stores in PDIR is same with expected value, . And IO output can check if output value by which stores in PDOR is correct. These tests should be tested in startup procedure as function test.

**Figure 20. Input /Output Test Flowchart**



#### 4.7.2 API Definition

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_GPIOOutputTest</b>  |
| <b>Parameter</b> | Port: port number<br>Bit: bit number<br>Value: output level                           |
| <b>Return</b>    | 0: IEC60730_TEST_NORMAL<br>1: IEC60730_TEST_FUNC_ERROR<br>2: IEC60730_TEST_PARA_ERROR |

##### Description:

This API implements GPIO output test by setting a level for output pin and check if read back value is the expected value.

|                  |   |
|------------------|---|
| <b>Name</b>      | <b>IEC60730_GPIOInputTest</b>   |
| <b>Parameter</b> | Port: port number<br>Bit: bit number<br>Value: expected pin level                     |
| <b>Return</b>    | 0: IEC60730_TEST_NORMAL<br>1: IEC60730_TEST_FUNC_ERROR<br>2: IEC60730_TEST_PARA_ERROR |

##### Description:

This API implements GPIO input test by reading the value from input pin and check if read value is the expected value.

## 4.8 AD Test


FM3 MCU integrates a 12bit AD module. It has 3 unit with totally 16 channels.

### 4.8.1 Test Description

To meet Class B requirement, AD must be check for “Function error”. This test samples AD signal from selected AD channels and check if the AD convert values are in the expected ranges.

Scan mode is used, multi-channel can be tested at the same time. The AD test flowchart of checking single-channel is shown as following figure.

Figure 21. AD Test Flowchart



### 4.8.2 API Definition

| Name      | IEC60730_ADTest  |
|-----------|--|
| Parameter | ADTest_Info: a ad_test_info_t structure<br><pre> typedef struct ad_test_info {     uint8_t ADUnit;      /* unit num, 8/10 bit A/D -&gt; 0/1/2 */     uint8_t *Ch;         /* pointer to AD channel num */     uint8_t ChSize;      /* channel size */     uint16_t *ExpLowerValue; /* pointer to expected lower value */     uint16_t *ExpUpperValue; /* pointer to expected upper value */ } ad_test_info_t;           </pre> |
| Return    | 0: IEC60730_TEST_NORMAL<br>1: IEC60730_TEST_FUNC_ERROR<br>2: IEC60730_TEST_PARA_ERROR  |

#### Description:

This API implements AD test by checking if AD convert result is in expected range. It should be implemented in startup procedure.

## 5 Example project

Two demo projects are provided according to IAR and keil IDE. This chapter introduces IAR demo project based on IAR MB9BF506R-SK EV-Board (MCU: MB9BF506R) and shows how to integrate the IEC60730 STL into a real system.

### 5.1 User Configuration

User should first configure some definitions in IEC60730\_user.h file.

#### 5.1.1 The definition “MCU\_TYPE\_MB9BF500”

If MB9BF500 is used, enable the definition “MCU\_TYPE\_MB9BF500”, else disable this definition. MB9BF506R is used in the IAR MB9BF506R-SK EV-Board, so disable the definition “MCU\_TYPE\_MB9BF500”.

#### 5.1.2 The definition “IEC60730\_FLASHTEST\_USE\_CRC16”

If User wants to use CRC16 arithmetic for Flash test, enable this definition, if user wants to use CRC32 arithmetic for Flash test, disable this definition.

In this demo program, CRC16 arithmetic is used.

#### 5.1.3 The definition “IEC60730\_CLKTEST\_USE\_CSV”

If User wants to use CSV to implement clock test, enable this definition, or clock test will be done with watch counter as standard timer, which is sourced by sub clock.

In the demo program, the latter method is demonstrated.

### 5.2 Project Structure

Class B STL routines are divided into two main processes: startup and periodic self-tests. The periodic test must be initialized by a set-up block before it is applied.

#### 5.2.1 Startup Self-Test

PC, register, SRAM test are all startup self-tests, and they should be called in reset handler.

And Flash, AD, IO can be tested after system clock initialization after program jumps into main function.

For AD test, channel 13 ((Potentiometer input) channel 7,8,9 (inertial Sensor input) are used for test.

For IO input test, joystick input pin P30 (LEFT), P31 (RIGHT), P40 (UP), P41 (Down) are used for test..

### 5.2.2 Periodic Test Initialization

Interrupt and clock test should be initialized before tests start.

#### ■ Interrupt Test Initialization

It is designed that a dual time interrupt is used to monitor reload timer 0-3. The initialization setting parameter is shown as following table.

Table 3. Input /Output Test Flowchart

| Interrupt Name | Interrupt Interval | interrupt of dual timer | Standard Frequency | Pre-defined Range |
|----------------|--------------------|-------------------------|--------------------|-------------------|
| Reload timer 0 | 2.5ms              | 25ms                    | 10                 | [8,12]            |
| Reload timer 1 | 1ms                | 25ms                    | 25                 | [22, 28]          |
| Reload timer 2 | 500us              | 25ms                    | 50                 | [45,55]           |
| Reload timer 3 | 250us              | 25ms                    | 100                | [95,105]          |

#### ■ Clock Test Initialization

The CPU clock is HCLK, and the source clock of dual timer in this system is set to PCLK0 (HCLK/2). So the source clock of dual timer can be tested indirectly in stead of CPU clock by watch counter.

It is designed that the interrupt Interval of watch counter is 1s and interrupt Interval of dual timer is 25ms, so the Standard Frequency of dual timer is 40 and the accepted range is set between 45 and 55. Assume it takes 10 cycles to implement main loop. So the minimum execution time of main loop is 1/8000000 s, so set the threshold value to 10000000.

### 5.2.3 Periodic Test


The interrupt and clock test should be tested in period when code is running.

Integrate **IEC60730\_IntTest** into dual timer interrupt and **IEC60730\_IntCnt** into each reload timer interrupts.

Integrate **IEC60730\_ClkTest** into watch counter interrupt, **IEC60730\_ClkCnt** into dual timer interrupt, and **IEC60730\_ClkMonInMainloop** into main loop.

The Figure 22 shows the basic principle of how to integrate the Class B software package into this application software.

Figure 22. Project Structure



## 5.3 Sample Code

### 5.3.1 Startup File

#### ■ Reset handler

Figure 23. Reset Handler Sample Code

```
Reset_Handler
    bl iec60730 reg test ; after reset, test register first
    bl iec60730 pc test  ; test pc
    ldr r0, =0x20000000 ; set RAM start address
    ldr r1, =0x20007fff ; set RAM end address
    bl iec60730 ram test ; test all D-RAM area
```

### 5.3.2 Main File

#### ■ Main function

Figure 24. Main Function Sample Code

```
int32_t main(void)
{
    int32_t cntr = 0;
    uint32_t hw_crc, sw_crc;
    uint8_t bit;
    uint8_t a[10] = {0x00, 0x11, 0x22, 0x33, 0x44, 0x55, 0x66, 0x77, 0x88, 0x99};
    uint8_t ch[4] = {7, 8, 9, 13}; /* ch7: X-axes input */
                                   /* ch8: Y-axes input */
                                   /* ch9: Z-axes input */
                                   /* chl3: VR2 input */
    /* place board in horizon */
    /*
    * x=0x800
    * y=0x800
    * z=0xb41
    */
    /* move the VR2 at middle */
    /* VR2 value = 0xfff/2 = 0x7ff */
    uint16_t low[16] = {0x700, 0x700, 0xb00, 0x500};
    uint16_t up[16] = {0x900, 0x900, 0xc00, 0xb00};
    ad_test_info_t ADTest_Info = {AD_UINT0, ch, sizeof(ch)/sizeof(uint8_t), low, up};
    SystemInit();
    /* use hardware CRC16 to calculate expected crc first,
    then verify if the CRC code calculated by software is same with expected crc */
    hw_crc = IEC60730_HardwareCRC16Gen(a, sizeof(a));
    if(IEC60730_TEST_NORMAL != IEC60730_SoftwareCRC16Test(a, sizeof(a), hw_crc))
    while(1);
    /* use software CRC16 to calculate expected crc first,
    then verify if the CRC code calculated by hardware is same with expected crc */
    sw_crc = IEC60730_SoftwareCRC16Gen(a, sizeof(a));
    if(IEC60730_TEST_NORMAL != IEC60730_HardwareCRC16Test(a, sizeof(a), sw_crc))
    while(1);
    /* GPIO output test
    * test P32-P39 (control LED1-LED8)
    */
    #ifdef MB9BF506R_SK
    for(bit=BIT_NUM_2; bit<BIT_NUM_9; bit++)
    {
        if(IEC60730_TEST_NORMAL != IEC60730_GPIOOutputTest(PORT_NUM_3, bit, TEST_PIN_LOW)
        || IEC60730_TEST_NORMAL != IEC60730_GPIOOutputTest(PORT_NUM_3, bit,
        TEST_PIN_HIGH))
        {
            while(1);
        }
    }
    #endif
    /* GPIO input test
    * test P30 (LEFT)
    * test P31 (RIGHT)
    * test P40 (UP)
    * test P41 (DOWN)
    */
}
```



```
#ifndef MB9BF506R_SK
    if(IEC60730 TEST NORMAL != IEC60730 GPIOInputTest(PORT_NUM 3, BIT_NUM 0,
1)){while(1);};
    if(IEC60730 TEST NORMAL != IEC60730 GPIOInputTest(PORT_NUM 3, BIT_NUM 1,
1)){while(1);};
    if(IEC60730 TEST NORMAL != IEC60730 GPIOInputTest(PORT_NUM 4, BIT_NUM 0,
1)){while(1);};
    if(IEC60730 TEST NORMAL != IEC60730 GPIOInputTest(PORT_NUM 4, BIT_NUM 1,
1)){while(1);};
#endif
/* AD test
 * check if ch7,ch8,ch9,ch13 input is in expected range.
 */
```

```
#ifndef MB9BF506R_SK
    if(IEC60730 TEST NORMAL != IEC60730 ADTest(ADTest Info)){while(1);};
#endif
/*Init LEDs*/
LED_Init();
/*Init Buttons*/
Button_Init();
/*Init LCD Pins*/
HD44780_IO_Init();
/* Interrupt test initialization */

IEC60730_IntTestInit(IntTest_Freq,IntTest_FreqLower,IntTest_FreqUpper,IntTest_FreqInit,s
sizeof(IntTest_Freq)/sizeof(uint32_t));
/* clock test initialization
 * test CPU clock by checking if the 25ms interval time is set for dual timer,
 * the occurrence frequency of dual times is about 40 in a 1s interval(produced by watch
counter)
 * 1 cycle time = (1/80MHz). Assume it takes 10 cycles to implement main loop.
 * So minimum
 */
IEC60730_ClkInit(35,45,10000000);
/* init watch counter */
WTC_Init();
/* init dual timer */
DT_Init();
/* init 4 base timers */
BT_Init();
/*Power up LCD*/
if(HD44780_OK != HD44780_PowerUpInit())
{
    return 1;
}
#endif
/* LCD display */
HD44780_StrShow(1,1,(const HD44780_STRING_DEF *)"IEC60730 Class B");
HD44780_StrShow(3,2,(const HD44780_STRING_DEF *)"Self-Test Lib");
#endif
/*Main Loop*/
while(1)
{ /*Wait for timer tick*/
    if(Tmr1Tick)
    { /*Clear timer tick flag*/
        Tmr1Tick = 0;
        /*update counter*/
        cntr--;
        /*leds update*/
        LED_PDOR ^= ~LED_MASK;
        LED_PDOR |= ((cntr) & LED_MASK);
    }
    if(IEC60730 TEST NORMAL != IEC60730_ClkMonInMainloop()) /* monitor watch counter
    {
        while(1);
    }
}
}
```

## ■ Dual Timer ISR

Figure 25. Dual Timer ISR

```
void CLK_IRQHandler(void)
{
    if(bFM3_INTREQ_IRQ24MON_WCINT)
    {
        FM3_WC->WCCR &= 0xFE; /* Clear interrupt flag */
        /* implement clock test */
        if(IEC60730_TEST_NORMAL != IEC60730_ClkTest())
        {
            while(1);
        }
    }
}
```

## ■ Watch Counter ISR

Figure 26. Watch Counter ISR

```
void CLK_IRQHandler(void)
{
    if(bFM3_INTREQ_IRQ24MON_WCINT)
    {
        FM3_WC->WCCR &= 0xFE; /* Clear interrupt flag */
        /* implement clock test */
        if(IEC60730_TEST_NORMAL != IEC60730_ClkTest())
        {
            while(1);
        }
    }
}
```

## ■ Reload Timer ISR

Figure 27. Reload Timer ISR

```
void BTIM_IRQHandler(void)
{
    if(FM3_BT0_RT->STC&0x01)
    {
        FM3_BT0_RT->STC = FM3_BT0_RT->STC & 0xFE;
        IEC60730_IntCntPro(0); /* count frequency value for interrupt 0 */
    }
    else if(FM3_BT1_RT->STC&0x01)
    {
        FM3_BT1_RT->STC = FM3_BT1_RT->STC & 0xFE;
        IEC60730_IntCntPro(1); /* count frequency value for interrupt 1 */
    }
    else if(FM3_BT2_RT->STC&0x01)
    {
        FM3_BT2_RT->STC = FM3_BT2_RT->STC & 0xFE;
        IEC60730_IntCntPro(2); /* count frequency value for interrupt 2 */
    }
    else if(FM3_BT3_RT->STC&0x01)
    {
        FM3_BT3_RT->STC = FM3_BT3_RT->STC & 0xFE;
        IEC60730_IntCntPro(3); /* count frequency value for interrupt 3 */
    }
}
```

## 6 STL API Performance

Table 4. STL API Performance

| API Name                   | Execution time<br>(Cycles) | Stack usage<br>(Bytes) | ROM Usage<br>(Bytes)       | RAM usage (Bytes)<br>(Global variable) |
|----------------------------|----------------------------|------------------------|----------------------------|--|
| iec60730_pc_test           | 158                        | 0                      | 136                        | 0                                      |
| iec60730_reg_test          | 498                        | 0                      | 642                        | 0                                      |
| IEC60730_IntTestInit       | 191 (4 interrupts)         | 8                      | 58                         | 0                                      |
| IEC60730_IntCntPro         | 47                         | 0                      | 36                         | 0                                      |
| IEC60730_IntTest           | 339 (4 interrupts)         | 0                      | 74                         | 20                                     |
| IEC60730_ClkCnt            | 54                         | 0                      | 32                         | 0                                      |
| IEC60730_ClkTest           | 92                         | 0                      | 80                         | 29                                     |
| IEC60730_ClkMonInMainloop  | 79                         | 8                      | 68                         | 0                                      |
| IEC60730_ClkTestReset      | 60                         | 0                      | 30                         | 0                                      |
| IEC60730_InitCSV           | 280                        | 8                      | 224                        | 0                                      |
| IEC60730_CheckCSVStat      | 30                         | 0                      | 56                         | 0                                      |
| IEC60730_HardwareCRC16Gen  | 320 (10 bytes data)        | 4                      | 98                         | 0                                      |
| IEC60730_HardwareCRC16Test | 348 (10 bytes data)        | 8                      | 20                         | 0                                      |
| IEC60730_SoftwareCRC16Gen  | 326 (10 bytes data)        | 4                      | 52+<br>512<br>(CRC table)  | 0                                      |
| IEC60730_SoftwareCRC16Test | 354 (10 bytes data)        | 8                      | 22                         | 0                                      |
| IEC60730_HardwareCRC32Gen  | 320<br>(10 bytes data)     | 8                      | 92                         | 0                                      |
| IEC60730_HardwareCRC32Test | 348 (10 bytes data)        | 8                      | 20                         | 0                                      |
| IEC60730_SoftwareCRC32Gen  | 244 (10 bytes data)        | 4                      | 42+<br>1024<br>(CRC table) | 0                                      |
| IEC60730_SoftwareCRC32Test | 266 (10 bytes data)        | 8                      | 84                         | 0                                      |
| iec60730_ram_test          | 262 (10 bytes data)        | 0                      | 84                         | 0                                      |
| IEC60730_GPIOOutputTest    | 264                        | 24                     | 254                        | 0                                      |
| IEC60730_GPIOInputTest     | 265                        | 28                     | 266                        | 0                                      |
| IEC60730_ADTest            | (4 Channels)               | 80                     | 1064                       | 0                                      |

### Notes:

1. The code execution cycle is tested in normal run status.
2. The ROM size of this STL is 3528 bytes. (Use CRC16 for Flash test, and watch counter for clock test)

## 7 Reference Documents

- [1]. IEC 60730-1 Reference Manual Edition3.2, 2007
- [2]. ARMv7-M Architecture Application Level Reference Manual, 2008
- [3]. Cortex-M3 r2p0 Technical Reference Manual, 2008
- [4]. MB98bF500a- DS706-00021-1v0-E ([MB9B500 Data Sheet](#))
- [5]. MB9Bxxx-MN706-00002-1v0-E (MB9Axxx/MB9Bxxx Series Periphery Manual)


## 8 Appendix

### 8.1 CRC code making method

The method to make CRC code to use in [4.1 CPU Register Test](#), follows is example of IAR Embedded Workbench. Please refer to IAR's manual for details

#### 8.1.1 Start of the Command-Line

Click "Project"→"Options"→"Linker"→"Extra options" tabs, then check the "Use command line options".



### 8.1.2 Input the command

#### “--place\_holder” command

“--place\_holder” is used to make CRC code and a section in ROM. If input the following command, to set the size of section in 4byte and the alignment in 1.

```
--place_holder __checksum,4,.checksum,1
```

#### “--fill” command

The unused area of the target area needs to fill with optional value making the CRC code. Therefore, use “--fill” command. If input the following command, 0x00000000-0x00003FFF is filled with 0xFF.

```
--fill 0xFF;0x0000-0x3FFF
```

If input the following command, 0x00000000-0x00003FFF, 0x5000-0x5FFF and 0x6500-0x6FFF are filled with 0xFF.


```
--fill 0xFF;0x0-0x3FFF;0x5000-0x5FFF;0x6500-0x6FFF
```

#### “--checksum” command

Set algorithm of CRC. If input the following command, you can set items as follow. The CRC code is stored in the symbol name “\_\_checksum”, the CRC code size is 4byte, the algorithm is CRC32, calculation is LSB first, CRC code is initialized by 0xFFFFFFFF, 0x00000000-0x00003FFF, 0x5000-0x5FFF and 0x6500-0x6FFF are filled with 0xFF.

```
--checksum __checksum:4,crc32:mi,0xffffffff;0x0-0x3FFF;0x5000-0x5FFF;0x6500-0x6FFF
```


If input the command mentioned above (1, 2, and 3), close the window by clicking the “OK”.



### 8.1.3 Setting of build messages to display in the message window

If set the following contents, you can display build messages at the time of make to the message window.

Click “Tools”→“Options”→“Messages” tabs, then select the “All” from the combo box of “Show build messages”. Finally, close the window by clicking the “OK”.



### 8.1.4 Setting of the Linker configuration file


Add settings to the Linker configuration file to store CRC code in Flash. In the case of debug mode, you must use “S6E1A11x0A\_ram.icf” file. In the case of release mode, you must use “mb9bf506\_ram.icf” file.

In the case of release mode, you must use “mb9bf506.icf” file. If input the following command, CRC code is stored in 0x8000.

```
define symbol __ICFEDIT_checksum_start__ = 0x00008000;  
define block CHECKSUM {ro section .checksum};  
define symbol __ICFEDIT_checksum_start__ = 0x00008000;
```

### 8.1.5 Making CRC code

Confirm that the CRC code was made after make.



The screenshot shows the IAR Embedded Workbench IDE interface. The left pane displays the project structure for 'IEC60730\_demo'. The main editor window shows the source code for 'board.h', which includes a CRC calculation function. The bottom pane shows the linker output messages, with a red circle highlighting the message 'Adding fill section over range 16ec0ff'.

```

/*
 * @ interrupt 3
 * @ standard frequency of interrupt 3: 100
 * @ brief: if the 250us interval time is set for reload timer 3(set by base time 3), check if it happens
 *         about 100 times in a 25us interval(produced by dault timer).
 */
extern uint32_t __checksum;

uint32_t IntTest_Freq[4];
uint32_t IntTest_FreqLower[4] = {8,22,45,95};
uint32_t IntTest_FreqUpper[4] = {12,28,55,105};
uint32_t IntTest_FreqInit[4] = {200,200,200,200};

/*****
 * Function Name: main
 * Parameters: none
 * Return: none
 * Description: main
 *****/
uint32_t main(void)
  
```

```

Link time: 0.08(CPU), 0.09(elapsed)
ielltool -il 0x00-0x3FFF -checksum __checksum_4 crc32mi 0x00000000 0x100-0x3FFF -verbose D:\m3_jec60730_1v4\example\IAR\Release\Exe\
IEC60730_demo.out\mp D:\m3_jec60730_1v4\example\IAR\Release\Exe\IEC60730_demo.out
IAR ELF Tool V9.10.10.43 [BUILT on IAR]
Copyright 2007-2011 IAR Systems AB.
Loading D:\m3_jec60730_1v4\example\IAR\Release\Exe\IEC60730_demo.out\mp
Adding fill section over range 16ec0ff
Saving ELF file to D:\m3_jec60730_1v4\example\IAR\Release\Exe\IEC60730_demo.out

Total number of errors: 0
Total number of warnings: 0
  
```

## Document History

Document Title: AN204348 - FM3 IEC60730 Class B Self-Test Library

Document Number: 002-04348

| Revision | ECN     | Orig. of Change | Submission Date | Description of Change   |
|----------|---------|-----------------|-----------------|---|
| **       | —       | MIQI            | 11/01/2012      | Initial Release   |
| *A       | 5640643 | MIQI            | 02/23/2017      | Migrated Fujitsu Application Note “AN706-00037-2v0-E” to Cypress format |
| *B       | 5833436 | AESATP12        | 07/26/2017      | Updated logo and copyright.   |



## Worldwide Sales and Design Support

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives, and distributors. To find the office closest to you, visit us at [Cypress Locations](#).

## Products

|                               |  |
|-------------------------------|--|
| ARM® Cortex® Microcontrollers | <a href="http://cypress.com/arm">cypress.com/arm</a>               |
| Automotive                    | <a href="http://cypress.com/automotive">cypress.com/automotive</a> |
| Clocks & Buffers              | <a href="http://cypress.com/clocks">cypress.com/clocks</a>         |
| Interface                     | <a href="http://cypress.com/interface">cypress.com/interface</a>   |
| Internet of Things            | <a href="http://cypress.com/iot">cypress.com/iot</a>               |
| Memory                        | <a href="http://cypress.com/memory">cypress.com/memory</a>         |
| Microcontrollers              | <a href="http://cypress.com/mcu">cypress.com/mcu</a>               |
| PSoC                          | <a href="http://cypress.com/psoc">cypress.com/psoc</a>             |
| Power Management ICs          | <a href="http://cypress.com/pmic">cypress.com/pmic</a>             |
| Touch Sensing                 | <a href="http://cypress.com/touch">cypress.com/touch</a>           |
| USB Controllers               | <a href="http://cypress.com/usb">cypress.com/usb</a>               |
| Wireless Connectivity         | <a href="http://cypress.com/wireless">cypress.com/wireless</a>     |

## PSoC® Solutions

[PSoC 1](#) | [PSoC 3](#) | [PSoC 4](#) | [PSoC 5LP](#) | [PSoC 6](#)

## Cypress Developer Community

[Forums](#) | [WICED IOT Forums](#) | [Projects](#) | [Videos](#) | [Blogs](#) | [Training](#) | [Components](#)

## Technical Support

[cypress.com/support](http://cypress.com/support)

All other trademarks or registered trademarks referenced herein are the property of their respective owners.



Cypress Semiconductor  
198 Champion Court  
San Jose, CA 95134-1709

© Cypress Semiconductor Corporation, 2012-2017. This document is the property of Cypress Semiconductor Corporation and its subsidiaries, including Spansion LLC ("Cypress"). This document, including any software or firmware included or referenced in this document ("Software"), is owned by Cypress under the intellectual property laws and treaties of the United States and other countries worldwide. Cypress reserves all rights under such laws and treaties and does not, except as specifically stated in this paragraph, grant any license under its patents, copyrights, trademarks, or other intellectual property rights. If the Software is not accompanied by a license agreement and you do not otherwise have a written agreement with Cypress governing the use of the Software, then Cypress hereby grants you a personal, non-exclusive, nontransferable license (without the right to sublicense) (1) under its copyright rights in the Software (a) for Software provided in source code form, to modify and reproduce the Software solely for use with Cypress hardware products, only internally within your organization, and (b) to distribute the Software in binary code form externally to end users (either directly or indirectly through resellers and distributors), solely for use on Cypress hardware product units, and (2) under those claims of Cypress's patents that are infringed by the Software (as provided by Cypress, unmodified) to make, use, distribute, and import the Software solely for use with Cypress hardware products. Any other use, reproduction, modification, translation, or compilation of the Software is prohibited.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS DOCUMENT OR ANY SOFTWARE OR ACCOMPANYING HARDWARE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. To the extent permitted by applicable law, Cypress reserves the right to make changes to this document without further notice. Cypress does not assume any liability arising out of the application or use of any product or circuit described in this document. Any information provided in this document, including any sample design information or programming code, is provided only for reference purposes. It is the responsibility of the user of this document to properly design, program, and test the functionality and safety of any application made of this information and any resulting product. Cypress products are not designed, intended, or authorized for use as critical components in systems designed or intended for the operation of weapons, weapons systems, nuclear installations, life-support devices or systems, other medical devices or systems (including resuscitation equipment and surgical implants), pollution control or hazardous substances management, or other uses where the failure of the device or system could cause personal injury, death, or property damage ("Unintended Uses"). A critical component is any component of a device or system whose failure to perform can be reasonably expected to cause the failure of the device or system, or to affect its safety or effectiveness. Cypress is not liable, in whole or in part, and you shall and hereby do release Cypress from any claim, damage, or other liability arising from or related to all Unintended Uses of Cypress products. You shall indemnify and hold Cypress harmless from and against all claims, costs, damages, and other liabilities, including claims for personal injury or death, arising from or related to any Unintended Uses of Cypress products.

Cypress, the Cypress logo, Spansion, the Spansion logo, and combinations thereof, WICED, PSoC, CapSense, EZ-USB, F-RAM, and Traveo are trademarks or registered trademarks of Cypress in the United States and other countries. For a more complete list of Cypress trademarks, visit [cypress.com](http://cypress.com). Other names and brands may be claimed as property of their respective owners.