



THIS SPEC IS OBSOLETE

Spec No: 002-04391

Spec Title: AN204391 - FM0+ Low Voltage, 3-Phase
BLDC/PMSM Motor Control

Replaced by: 002-02483

AN204391

FM0+ Low Voltage, 3-Phase BLDC/PMSM Motor Control

This document describes low voltage 3-phase BLDC/PMSM control on S6E1A1 MCU, including whole system scope, hardware design, software design and test result.

Contents

1	Introduction.....	1	5	Software Design.....	10
1.1	Purpose	1	5.1	Firmware File Structure	10
1.2	Definitions, Acronyms and Abbreviations	1	5.2	Control Implementation.....	12
1.3	Document Overview	1	6	Results	16
2	Control Theory.....	3	6.1	Current Waveform with Sensor-less Control	16
2.1	Structure of a 3-Phase PMSM	3	6.2	Current Waveform with 3 Hall Sensor Control.....	18
2.2	FOC Principle	3	6.3	Lock Rotor	20
2.3	FOC Control Structure	4	7	Document History.....	21
2.4	Hall Sensor Introduction.....	6			
2.5	Sensor-less Introduction	8			
3	System Scope	8			
4	Hardware Design.....	9			

1 Introduction

1.1 Purpose

This document describes low voltage 3-phase BLDC/PMSM control on S6E1A1 MCU, including whole system scope, hardware design, software design and test result.

1.2 Definitions, Acronyms and Abbreviations

HW	-	Hardware, at this document it means Inverter platform hardware board
FW	-	Firmware
I/O	-	Input and output
MFT	-	Multi-Function Timer
LVBP	-	Low Voltage 3-Phase BLDC/PMSM

1.3 Document Overview

The rest of document is organized as the following:

Section2 explains Control theory.

Section3 explains System Scope.

Section4 explains Hardware design.

Section5 explains Software design.

Section6 explains Results.

OBsolete

2 Control Theory


2.1 Structure of a 3-Phase PMSM

A 3-phase PMSM is mainly composed of two parts: the stator and the rotor.

At stator side, the 3-phase windings are coiled on the stator core. The windings of 3 phases are separately placed by the rule of 120 degrees angle to generate a round rotating magnetic field (F_s) when a 3-phase AC current goes through the 3 phase windings. The separated 3-phase winding placed by the rule of 120 degrees angle is named as 3-phase symmetric winding.

At rotor side, one or more pairs of permanent magnetic poles are mounted to offer a constant rotor magnetic field (F_r).

Figure 1. Structure of a 3-Phase PMSM




Because F_s is a rotating magnetic field, the F_r will be dragged and follow the F_s . If the F_r cannot catch up with F_s , the rotor will rotate continuously. If the 3-phase current in 3-phase windings disappears, the F_s will disappear at the same time, and the rotor will also stop.

2.2 FOC Principle

Brush DC motor is a conventional DC motor with a long history. A big advantage of the brush DC motor is that its torque control and magnetizing control are decoupled, which makes brush DC motor is easy to control. The brush DC motor de-coupled control is shown in below figure.


Figure 2. Brush DC Motor De-coupled Control



The magnetizing is controlled by magnetizing current (I_f), and the torque control is controlled by torque current (I_a). The direction of the magnetizing magnetic field is parallel with d-axis (vertical direction), and the direction of the torque magnetic field is parallel with q-axis (horizontal direction). So these two magnetic fields do not influence each other. That is to say, it is decoupled between the 2 magnetic fields and motor's magnetizing and torque can be adjusted individually. For example, the torque control formula is $T_e = C_m I_a$, which means torque is only controlled by torque current I_a .

The condition of PMSM motor control is much more complex than a brush DC motor. The magnetic field of a 3-phase symmetry winding is a coupled magnetic field. We can discover the complex coupled relationship from the torque control formula.

Figure 3. The Coupled Magnetic Flux of a PMSM



$$T_e = \frac{1}{2} n_p [I_{ABC}]^T \frac{\partial [L_{ABC}]}{\partial \theta} [I_{ABC}] \dots (3.1.1-1)$$

$$[L_{ABC}] = \begin{bmatrix} L_A & M_{AB} & M_{AC} \\ M_{BA} & L_B & M_{BC} \\ M_{CA} & M_{CB} & L_C \end{bmatrix} (M \text{ is mutual inductance}), [I_{ABC}] = \begin{bmatrix} I_A \\ I_B \\ I_C \end{bmatrix}$$

From the expression of T_e , it is easy to understand that the torque is determined by all 3-phase inductances (including self-inductance and mutual-inductance) and currents. Obviously, the torque control seems much more complex than a brush DC motor.

Coordinate transformation is just the way to simplify the PMSM torque control. By coordinate transformation, a PMSM control model is converted from A-B-C coordinate to d-q coordinate. The torque control formula is also converted into d-q coordinate, the formula is:

$$T_e = 3/2 n_p \psi_d I_q \dots (3.1.1-2)$$

The simple formula in d-q coordinate makes the PMSM torque control as easy as a brush DC motor.

2.3 FOC Control Structure

From the explanation above, the key of FOC is to make the torque control of PMSM as easy as a DC brush motor through a motor rotor magnetic field orientation technology. In the technology, the coordinate transformation method turns the motor module from the u-v-w coordinate to the rotational d-q coordinate, and the d-q coordinate rotational speed is the same as the stator magnetic field rotational speed. Then the control of a PMSM is simplified and the control performance is almost the same as a DC brush motor.

Some PID regulators are added to adjust the motor output according to the given input. By setting different PID parameters, system gets different dynamic and static performance.

SVPWM technology is applied to accept the driving voltage in α - β coordinate and output a set of switching instruction to control the 6 switches in full bridge inverter.

Position and speed estimator is used to observe the real time motor speed by the motor driving voltage and current. The estimated motor speed compares with the reference speed, and the compare result acts as the input of the speed PI regulator. The estimated rotor position angle is used by the coordinate transformation unit.

Motor's position can be got from physical feedback sensor signal: encoder or hall sensor. On the other hand, it only can be estimated by a firmware sensor less observation module. In this design note, it includes both ways to get the position information.

Figure 4. FOC Control Diagram with Hall Sensor





Figure 5. FOC Control Diagram without Sensor




2.4 Hall Sensor Introduction

Hall sensor can sense PMSM/BLDC's rotor's position. 2 Hall sensors can check rotor's 4 point position and 3 Hall sensors can check 6 point position in one electrical cycle. Hall sensor is installed in motor's stator. It is an independent physical component.


Hall sensor signal has only 2 statuses: high level and low level. Its change process is shown in Figure 6.

Figure 6. Hall Sensor Electrical Status Change Process




Three hall sensors have 6 statuses by logical combine. It is shown in Figure 7.

Figure 7. Three Hall Sensor's Electrical Logical Combination



Hall sensor signals are connected to MCU's I/O port. Once the status changed, interrupt will occur and the firmware module will calculate the rotor's position and speed. The process is as shown in Figure 8.

Figure 8. Rotor Angle Calculated by Hall Edge Trigger Interrupt




2.5 Sensor-less Introduction

Motor's position also can be got from the Back-EMF when there is no sensor installed in motor. To make the low voltage platform more compatible, one basic rotor position observation method is introduced in this solution.

Back-EMF on α and β axis voltage wave is shown in Figure 9.

Figure 9. Back-EMF Voltage Wave Vary with Rotor Phase Angle



Rotor position can be calculated in every PWM interrupt time:

$$e_{\alpha} = \text{LPF}(V_{\alpha} - R_s i_{\alpha} - L \frac{di_{\alpha}}{dt})$$

$$e_{\beta} = \text{LPF}(V_{\beta} - R_s i_{\beta} - L \frac{di_{\beta}}{dt})$$

$$\theta_e = \arctan(-e_{\alpha}/e_{\beta})$$

The LPF is a one order low pass filter. As filter is used in the calculation process, angle θ_e must have a little phase delay compared with the real rotor position. Offset angle need to be added on the calculated angle.

$$\theta_e(\text{correct}) = \theta_e + \theta_{\text{offset}}$$


Inner R_s can be checked by "Stator Resistor Check" module and L can be checked by inductor component.

After the Back-EMF angle was calculated, if the hall interrupts happen, angle table can be replaced by value $\theta_e(\text{correct})$ at high speed.

3 System Scope

This chapter describes the driving system of 3-phase permanent magnet synchronous motor. The system structure and driving performance is shown below.

Figure 10. System Whole Structure



- S6E1A1 is the target controller with configured 40MHZ main clock
- Motor can work with hall sensor or sensor-less ways.
- The followings are the whole system specification
 - Auto hall sensor phase angle detect.
 - Wide speed range: 360rpm ~ 4000rpm.
 - Input voltage range from 24V to 48V. Max current: 3A.
 - Carrier wave frequency can be changed on line.
 - All protect function implementation.
 - Rapid speed acceleration up to 2000rpm/s
 - Field-weaken do not implement in this system.
 - Accurate speed controlling with less than 1% target error.
- Firmware development environment
 - Windows XP or later
 - IAR 7.3

4 Hardware Design

For documents about hardware, please refer to hardware design application note.

Here gives some specification about hardware.

- DC-DC power supply
- Three-shunt current sample
- Support J-LINK connection
- Combine hall sensor interface (HA , HB, HC, 5V, GND)
- IPM for motor drive

Hardware system connection is shown as Figure 11.

Figure 11. System Hardware Structure




5 Software Design

This chapter describes motor control implementation. Firmware version, firmware structure and control process are explained respectively.

5.1 Firmware File Structure

The following figure shows firmware file structure.

Figure 12. Firmware File Structure



Firmware contains three sub-folders: folder code, folder config and folder editor.

All source codes are stored in folder code including head-files and c-source files.

Configuration files and MCU description files are stored in folder config.


Double click on file "fm0_lowvoltagebldc.eww" to open project.

Code Folder Introduction

Source codes are divided into five different types by function and stored in five different folders.

Five layers are named "global", "driver", "module", "app" and "user" respectively.

Figure 13. Firmware Structure in Project



Global layer is empty.

Driver layer stores MCU header file and macro definition files.

Module layer stores independent functions.

App layer is related to actual project. Function in this folder is changeable depending on different system.

User layer is open to customer for configuration and debugging.

5.2 Control Implementation

This chapter explains peripherals and interrupts used in firmware firstly, and then control process flow.

5.2.1 Peripherals in Firmware

All peripherals used in firmware are configured in "init_mcu.c" stored in folder "s05_user".

Details on peripheral initialization can refer to MCU datasheets.

Table 1. Peripherals Used in Firmware

Peripherals	Function in firmware
clock	Configure system main clock and bus clock
NVIC	Enable or disable interrupts, configure priorities
base timer	Measure the width of hall signal to calculate motor current speed
Adc	Be used to sample phase current, ADC unit 0 is being used.
Multi-function timer(MFT)	Generate PWM signals to control 3 half-bridge to drive motor running. MFT unit 0 is being used.
Watch dog	Reset MCU when program goes wrong

- Clock setting
 - SCM_CTL: System clock mode control.
 - BSC_PSR: Base clock mode control.
 - APBC0_PSR: APB0 prescaler register.
 - APBC1_PSR: APB1 prescaler register.
 - APBC2_PSR: APB2 prescaler register.
- NVIC setting
 - NVIC_SetPriority(IRQn, x):priority setting
 - NVIC_EnableIRQ(IRQn): enable priority
 - IRQn: irq number
 - X: indicate priority number
- Base timer setting
 - PWC function is selected in this firmware.
 - TMCR:Timer control register
 - STC:Status control register
 - DTBF: Data Buffer control
- Adc setting
 - Scan interrupt is enabled in this firmware, priority mode interrupt is not used.
 - ADCR: AD control registers.
 - ADSR: AD status registers.
 - SCCR: Scan conversion control.
- MFT setting
 - FRT, OCU, WFG and ADCMP is used in this firmware.
 - Configuration details can refer to MCU datasheet.
 - FRT selects up and down count mode. Complementary output of WFG with dead-time is selected.

- Watch dog setting
 - WdogControl: Software watchdog timer control registers.
 - WDG_CTL: Hardware watchdog timer control registers.

5.2.2 Interrupts in Firmware

The following table shows interrupts being used in system. Function "InitMcu_Nvic()" in "init_mcu.c" is for interrupt control.

More details about interrupt control can refer to document "Cortex-M0 Technical Reference Manual"

Table 2. Interrupt Function Used in Firmware

Interrupt type	Function in firmware
Multi-function timer zero match interrupt	FOC algorithm is executing in this interrupt.
ADC scan interrupt	It is for DC voltage and three-phase current sampling. Triggered by MFT zero matching.
Multi-function timer DTIF interrupt	It is for hardware over-current protection.
Software watch dog interrupt	When software watch overflow, motor stops running.
Base timer hall capture interrupt	It is for capture hall sensor signal edge change.

- For priority setting, the less the digit is, the higher the priority is.

NVIC_SetPriority(ADC0_IRQn,1)

NVIC_SetPriority(FRT0_ZERO_IRQn,2)


ADC0_IRQn priority is higher than FRT_ZERO_IRQn through above setting.

MFT and ADC interrupt execution illustration is shown below, MFT and ADC interrupt includes all functions about motor controlling.

MFT and ADC interrupts is triggered every PWM cycle.

Base timer interrupt is triggered by hall sensor edge change.

Figure 14. Interrupt Trigger Process



5.2.3 Control Process Flow

Because of higher priority the ADC interrupt is than MFT zero-match, basic control theory is shown below.

The main flow about control process contains three primary parts: ADC interrupt, MFT interrupt and main function.

Figure 15. ADC and MFT Interrupt in Motor Control





Figure 16. System Run Machine State



6 Results

All results are based on a BLDC motor. Control system will run it with sensor and sensor-less mode.

Motor parameters are listed on table below

Table 3. Motor Parameter in the Test Platform

Motor parameters	max	units
Phase current(peak)	2	A
Speed range	360~4000	rpm
Ld	0.65	mh
Lq	0.85	mh
Rs	0.5	Ω
Ke	2.8	Vrms/krpm
Pole pairs	2	N/A

6.1 Current Waveform with Sensor-less Control


360rpm and 4000rpm current waveform under sensor control mode is shown below.

Figure 17. Motor Phase Current Wave at 360rpm without Hall Sensor Control



Motor's phase current peak value is less than 190mA. Speed is very stable at low speed. System reached the low speed running requirement.

Figure 18. Motor phase current in 4000rpm without sensor control



From the test wave, it can be seen that the motor run at the max speed is very stable and current enveloping is much smooth. Actually, it also can reflect the noise is also much low indirectly.

6.2 Current Waveform with 3 Hall Sensor Control

360rpm and 4000rpm current waveform with hall sensor control is shown below.

Figure 19. Motor phase current at 360rpm with 3 hall sensor control





Figure 20. Motor phase current at 4000rpm with 3 hall sensor control




From the test wave, it can be seen that the motor's phase current at 4000rpm is not better than the sensor-less solution. Because the position calculation result is different: one is from the physical hall sensor and the other is estimated based on the sampled current and Back-EMF. So the harmonic and noise of hall sensor are much worse than sensor-less solution at high speed.

6.3 Lock Rotor

Figure 21. Motor phase current wave when add lock load with hall sensor at 1000rpm



Figure 22. Motor Phase CurrentWave when Add Lock Load without Hall Sensor at 1000rpm



7 Document History

Document Title: AN204391 - FM0+ Low Voltage, 3-Phase BLDC/PMSM Motor Control

Document Number: 002-04391

Revision	ECN	Orig. of Change	Submission Date	Description of Change
**	-	DOHE	04/02/2015	Initial Release
*A	5056680	DOHE	12/18/2015	This spec is for obsolete.

Worldwide Sales and Design Support

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives, and distributors. To find the office closest to you, visit us at [Cypress Locations](#).

Products

Automotive	cypress.com/go/automotive
Clocks & Buffers	cypress.com/go/clocks
Interface	cypress.com/go/interface
Lighting & Power Control	cypress.com/go/powerpsoc
Memory	cypress.com/go/memory
PSoC	cypress.com/go/psoc
Touch Sensing	cypress.com/go/touch
USB Controllers	cypress.com/go/usb
Wireless/Rf	cypress.com/go/wireless
Spansion Products	spansion.com/products

PSoC® Solutions

psoc.cypress.com/solutions

[PSoC 1](#) | [PSoC 3](#) | [PSoC 4](#) | [PSoC 5LP](#)

Cypress Developer Community

[Community](#) | [Forums](#) | [Blogs](#) | [Video](#) | [Training](#)

Technical Support

cypress.com/go/support

All other trademarks or registered trademarks referenced herein are the property of their respective owners.



Cypress Semiconductor
198 Champion Court
San Jose, CA 95134-1709
Phone : 408-943-2600
Fax : 408-943-4730
Website : www.cypress.com

© Cypress Semiconductor Corporation, 2015. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges. This Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.