

Product brief

CIPOS™ Mini IPM

600 V/4–30 A

Infineon's energy-efficient CIPOS™ Mini intelligent power modules (IPM) integrate various power and control components to increase reliability and optimize PCB size and system cost. This simplifies the power design and significantly reduces time to market. The CIPOS™ Mini IPM is designed to control AC motors in variable speed drives for applications such as air conditioning, washing machines, refrigerators, vacuum cleaners, compressors and industrial drives up to 3 kW.

The package concept is specially adapted to power applications that need good thermal conduction and electrical isolation, but also EMI-safe control, innovative FAULT indication and overload protection. Infineon's reverse-conducting IGBTs, TRENCHSTOP™ IGBTs, or CoolMOS™ Power MOSFETs are used with a new optimized Infineon SOI gate driver for excellent electrical performance.

Applications

Broad range of applications from power factor correction (PFC) to inverter



Key features

- > Fully isolated dual in-line molded module with fullpack and DCB
- > Current rating from 4 A to 30 A, power rating up to 3 kW
- > Application-specific performance
- > Very low thermal resistance with DCB
- > Reverse-conducting IGBTs with low $V_{CE(sat)}$ and optimal anti-parallel diode for better EMI performance
- > TRENCHSTOP™ IGBTs with low $V_{CE(sat)}$
- > CoolMOS™ Power MOSFET for high efficiency
- > Rugged 3-phase SOI gate driver technology with stability against transient and negative voltage
- > Matched propagation delay for all channels
- > Fast switching capability:
 $f_{sw} \leq 20$ kHz
- > Fully compliant to 3.3 V and 5 V microcontrollers
- > Temperature sensor (optional)
- > Accessible FAULT pin
- > Undervoltage lockout at all channels
- > Cross-conduction prevention
- > Low-side emitter pins accessible for all phase current monitoring (open emitter)
- > Lead-free terminal plating, RoHS compliant




CIPOS™ Mini IPM

600 V/4–30 A



Block diagram



Product	Package	Voltage [V]	Nominal current @ 25 °C [A]	Power up to [kW]	T _{jmax} [°C]	Built in thermistor	Remark
3-phase inverter, open emitter, target applications: air conditioning, general motor drives							
IGCM04F60xA	Mini FullPACK	600	4	0.6	150	optional ¹⁾	–
IGCM06F60xA	Mini FullPACK	600	6	0.8	150	optional	–
IGCM10F60xA	Mini FullPACK	600	10	1.2	150	optional	–
IGCM15F60xA	Mini FullPACK	600	15	1.2	150	optional	–
IGCM20F60xA	Mini FullPACK	600	20	1.6	150	optional	–
IKCM10L60xA	Mini FullPACK	600	10	1.2	150	optional	–
IKCM15L60xA	Mini FullPACK	600	15	1.6	150	optional	–
IKCM20L60xA	Mini FullPACK	600	20	1.8	150	optional	–
IKCM30F60xA	Mini FullPACK	600	30	2.0	150	optional	–
IKCM20L60xD	Mini DCB	600	20	2.4	150	optional	–
IKCM30F60xD	Mini DCB	600	30	2.6	150	optional	–
3-phase inverter, open emitter, target applications: washing machines							
IKCM10H60xA	Mini FullPACK	600	10	1.0	150	optional	–
IKCM15H60xA	Mini FullPACK	600	15	1.2	150	optional	–
2-phase asymmetric inverter for switched reluctance motor drives, target application: vacuum cleaners							
IKCM15R60GD	Mini DCB	600	15	2.2	150	✓	–
IKCM20R60GD	Mini DCB	600	20	2.4	150	✓	–
2-phase or 3-phase inverter, open source, with CoolMOS™ MOSFET, target applications: high efficient refrigerators, low power motor drives							
IM512-L6A	Mini FullPACK	600	10	0.4	150	✓	2-phase
IM513-L6A	Mini FullPACK	600	10	0.6	150	✓	3-phase
2-phase or 3-phase interleaved topology for PFC (Power Factor Correction), target applications: air conditioning, pumps, fans							
IFCM20T65GD	Mini DCB	650	20	3.6	150	✓	2-phase
IFCM30T65GD	Mini DCB	650	30	5.4	150	✓	2-phase
IFCM20U65GD	Mini DCB	650	20	4.4	150	✓	3-phase
IFCM30U65GD	Mini DCB	650	30	6.4	150	✓	3-phase
PFC (Power Factor Correction) integrated 3-phase inverter, with 20 kHz or 40 kHz PFC switching, target applications: air conditioning, pumps, fans							
IFCM10P60GD	Mini DCB	600	10	1.2	150	✓	40 kHz
IFCM15P60GD	Mini DCB	600	15	1.8	150	✓	40 kHz
IFCM10S60GD	Mini DCB	600	10	1.2	150	✓	20 kHz
IFCM15S60GD	Mini DCB	600	15	1.8	150	✓	20 kHz

1) x = G (built in thermistor), x = H (no thermistor)

Published by
Infineon Technologies AG
81726 Munich, Germany

© 2018 Infineon Technologies AG.
All Rights Reserved.

Please note!

THIS DOCUMENT IS FOR INFORMATION PURPOSES ONLY AND ANY INFORMATION GIVEN HEREIN SHALL IN NO EVENT BE REGARDED AS A WARRANTY, GUARANTEE OR DESCRIPTION OF ANY FUNCTIONALITY, CONDITIONS AND/OR QUALITY OF OUR PRODUCTS OR ANY SUITABILITY FOR A PARTICULAR PURPOSE. WITH REGARD TO THE TECHNICAL SPECIFICATIONS OF OUR PRODUCTS, WE KINDLY ASK YOU TO REFER TO THE RELEVANT PRODUCT DATA SHEETS PROVIDED BY US. OUR CUSTOMERS AND THEIR TECHNICAL DEPARTMENTS ARE REQUIRED TO EVALUATE THE SUITABILITY OF OUR PRODUCTS FOR THE INTENDED APPLICATION.

WE RESERVE THE RIGHT TO CHANGE THIS DOCUMENT AND/OR THE INFORMATION GIVEN HEREIN AT ANY TIME.

Additional information

For further information on technologies, our products, the application of our products, delivery terms and conditions and/or prices, please contact your nearest Infineon Technologies office (www.infineon.com).

Warnings

Due to technical requirements, our products may contain dangerous substances. For information on the types in question, please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by us in a written document signed by authorized representatives of Infineon Technologies, our products may not be used in any life-endangering applications, including but not limited to medical, nuclear, military, life-critical or any other applications where a failure of the product or any consequences of the use thereof can result in personal injury.