

Release Notes

CY3218-CAPEXP1 CapSense® Express™ Kit

Release Date: June 16, 2015

Thank you for your interest in the CY3218-CAPEXP1 CapSense® Express™ Kit. This document lists installation requirements, software and hardware updates, limitations, and known issues with the kit.

System Requirements and Recommendations

Hardware/Operating System Requirements	Minimum	Recommended
Processor speed	1 GHz	2 GHz
RAM	1 GB	2 GB
Free hard drive space	800 MB	1 GB
Screen resolution	1024 × 768	1280 × 1024
CD/DVD drive	✓	✓
USB	Full Speed	2.0 Hi-Speed
Windows XP (SP3 or higher), Vista or Windows Vista	✓	✓
Software Prerequisites	Minimum	Recommended
Microsoft Internet Explorer	7	Latest
Adobe Reader (for PDF documents)	6	9+
Windows Installer	3.1	Latest
.NET Framework	2.0 SP1	Latest
PSoC Designer	5.0 SP6	5.0 SP6
PSoC® Programmer	3.13.3	Latest*

Installation

To install, insert the kit CD into your PC's CD-ROM drive. If the installer does not start automatically, run *cyautorun.exe* in the root directory of the CD/DVD. Follow the installation instructions.

Updates

Check <http://www.cypress.com/go/CY3218-CAPEXP1> for the latest downloads of software and documentation.

Kit Revision and New Features

Code examples for the CY3218-CAPEXP1 kit are supported in PSoC Designer 5.0 SP6. The onboard mechanical button can be used as input in both resistive pull-up and open drain GPIO drive modes, based on the fix provided in this revision of the kit. See the errata provided in the kit CD for more details.

Limitations and Known Issues

If the drive mode of GPIO, which is connected to the mechanical button, is set to resistive pull-up, the mechanical button input does not function as intended. The button is expected to provide logic 0 during inactive state (not pressed) and logic 1 during active state (pressed). In the original design (121R_45800 Rev**), the button provides logic 1 in both states.

All projects using the mechanical button input in combination with resistive pull-up drive mode are affected. The kit circuit is modified with manual rework to fix this defect. With this fix, the mechanical button can be used as input in both resistive pull-up and open drain drive mode of GPIO.

Due to this defect, the mechanical button input cannot be used to 'wake up the CapSense Controller from sleep'. With this fix, the mechanical button can be used as 'wake up from sleep' input signal.

Documentation

Kit documents are located in the CD, in the following location: <CD_Root>\Documentation

Documents include:

- CY3218-CAPEXP1 Kit_User_Guide.pdf
- CY3218-CAPEXP1 Quick_Start_Guide.pdf
- CY3218-CAPEXP1 Release_Notes.pdf
- CY3218-CAPEXP1 Errata.pdf

Silicon Errata

The most up-to-date versions of the silicon errata are available in the device datasheets on the web site at <http://www.cypress.com>.

For assistance go to <http://www.cypress.com> or contact our Applications team at +1(425) 787-4814

Technical Support

For assistance, go to <http://www.cypress.com/go/support> or contact our customer support at +1(800) 541-4736 Ext. 2 (in the USA), or +1 (408) 943-2600 Ext. 2 (International).

Additional Information

- For more information about PSoC Designer functionality and releases, review the user guide and release notes on the PSoC Designer web page: <http://www.cypress.com/go/psocdesigner>
- For more information about PSoC Programmer, supported hardware, and COM layer, visit the PSoC Programmer web page: <http://www.cypress.com/go/psocprogrammer>
- For a list of trainings on PSoC Designer, visit <http://www.cypress.com/?rID=40543>
- For getting started with CY8C201xx Configuration tool, PSoC Designer 5.0 SP6, refer to Application [AN42137 - Capsense™ Express Software Tool](#)



Cypress Semiconductor
198 Champion Ct.
San Jose, CA 95134-1709 USA
Tel: 408.943.2600
Fax: 408.943.4730
Application Support Hotline: 425.787.4814
www.cypress.com

© Cypress Semiconductor Corporation, 2011-2015. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

PSoC Designer™, Programmable System-on-Chip™, and PSoC Express™ are trademarks and PSoC® is a registered trademark of Cypress Semiconductor Corp. All other trademarks or registered trademarks referenced herein are property of the respective corporations.

This Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.
