

Please note that Cypress is an Infineon Technologies Company.

The document following this cover page is marked as “Cypress” document as this is the company that originally developed the product. Please note that Infineon will continue to offer the product to new and existing customers as part of the Infineon product portfolio.

Continuity of document content

The fact that Infineon offers the following product as part of the Infineon product portfolio does not lead to any changes to this document. Future revisions will occur when appropriate, and any changes will be set out on the document history page.

Continuity of ordering part numbers

Infineon continues to support existing part numbers. Please continue to use the ordering part numbers listed in the datasheet for ordering.



CYTVII-B-H-8M-176-CPU

Evaluation board user guide

Document Number: 002-25907 Rev. *D

Cypress Semiconductor
An Infineon Technologies Company
198 Champion Court
San Jose, CA 95134-1709
www.cypress.com, www.infineon.com

© Cypress Semiconductor Corporation, 2019–2021. This document is the property of Cypress Semiconductor Corporation, an Infineon Technologies company, and its affiliates (“Cypress”). This document, including any software or firmware included or referenced in this document (“Software”), is owned by Cypress under the intellectual property laws and treaties of the United States and other countries worldwide. Cypress reserves all rights under such laws and treaties and does not, except as specifically stated in this paragraph, grant any license under its patents, copyrights, trademarks, or other intellectual property rights. If the Software is not accompanied by a license agreement and you do not otherwise have a written agreement with Cypress governing the use of the Software, then Cypress hereby grants you a personal, non-exclusive, nontransferable license (without the right to sublicense) (1) under its copyright rights in the Software (a) for Software provided in source code form, to modify and reproduce the Software solely for use with Cypress hardware products, only internally within your organization, and (b) to distribute the Software in binary code form externally to end users (either directly or indirectly through resellers and distributors), solely for use on Cypress hardware product units, and (2) under those claims of Cypress’s patents that are infringed by the Software (as provided by Cypress, unmodified) to make, use, distribute, and import the Software solely for use with Cypress hardware products. Any other use, reproduction, modification, translation, or compilation of the Software is prohibited.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS DOCUMENT OR ANY SOFTWARE OR ACCOMPANYING HARDWARE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. No computing device can be absolutely secure. Therefore, despite security measures implemented in Cypress hardware or software products, Cypress shall have no liability arising out of any security breach, such as unauthorized access to or use of a Cypress product. CYPRESS DOES NOT REPRESENT, WARRANT, OR GUARANTEE THAT CYPRESS PRODUCTS, OR SYSTEMS CREATED USING CYPRESS PRODUCTS, WILL BE FREE FROM CORRUPTION, ATTACK, VIRUSES, INTERFERENCE, HACKING, DATA LOSS OR THEFT, OR OTHER SECURITY INTRUSION (collectively, “Security Breach”). Cypress disclaims any liability relating to any Security Breach, and you shall and hereby do release Cypress from any claim, damage, or other liability arising from any Security Breach. In addition, the products described in these materials may contain design defects or errors known as errata which may cause the product to deviate from published specifications. To the extent permitted by applicable law, Cypress reserves the right to make changes to this document without further notice. Cypress does not assume any liability arising out of the application or use of any product or circuit described in this document. Any information provided in this document, including any sample design information or programming code, is provided only for reference purposes. It is the responsibility of the user of this document to properly design, program, and test the functionality and safety of any application made of this information and any resulting product. “High-Risk Device” means any device or system whose failure could cause personal injury, death, or property damage. Examples of High-Risk Devices are weapons, nuclear installations, surgical implants, and other medical devices. “Critical Component” means any component of a High-Risk Device whose failure to perform can be reasonably expected to cause, directly or indirectly, the failure of the High-Risk Device, or to affect its safety or effectiveness. Cypress is not liable, in whole or in part, and you shall and hereby do release Cypress from any claim, damage, or other liability arising from any use of a Cypress product as a Critical Component in a High-Risk Device. You shall indemnify and hold Cypress, including its affiliates, and its directors, officers, employees, agents, distributors, and assigns harmless from and against all claims, costs, damages, and expenses, arising out of any claim, including claims for product liability, personal injury or death, or property damage arising from any use of a Cypress product as a Critical Component in a High-Risk Device. Cypress products are not intended or authorized for use as a Critical Component in any High-Risk Device except to the limited extent that (i) Cypress’s published data sheet for the product explicitly states Cypress has qualified the product for use in a specific High-Risk Device, or (ii) Cypress has given you advance written authorization to use the product as a Critical Component in the specific High-Risk Device and you have signed a separate indemnification agreement.

Cypress, the Cypress logo, and combinations thereof, PSoC, CapSense, EZ-USB, F-RAM, Traveo, WICED, and ModusToolbox are trademarks or registered trademarks of Cypress or a subsidiary of Cypress in the United States or in other countries. For a more complete list of Cypress trademarks, visit cypress.com. Other names and brands may be claimed as property of their respective owners.

Disclaimer of Schematics and Layouts: This material constitutes a reference design. CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all changes.

Contents



1. Introduction	4
1.1 Precautions and warnings	4
2. Overview	5
2.1 Functional overview	7
3. Operation	15
4. Connections and settings	17
4.1 Evaluation board connections.....	17
4.2 Power supply settings	23
4.3 External power supply control signal settings	24
4.4 Ethernet settings	24
4.5 Settings	25
5. Power management IC (PMIC)	26
5.1 Power management IC (PMIC) module	26
A. CPU board schematics	28
B. CPU board component assembly	60
C. Baseboard schematics	63
D. Baseboard component assembly	80
Revision history	83

1. Introduction



This user guide provides instructions to handle the CYTVII-B-H-8M-176-CPU and CYTVII-B-H-176-SO evaluation boards, collectively referred to as 'CPU board' in this document. This is an evaluation platform for the CYT4BF8C TRAVEO™ T2G device. The board can be used as a standalone for basic validation or in combination with the CYTVII-B-E-BB TRAVEO™ T2G baseboard (available separately from Infineon). This document assumes that you will work with the combination (CPU board + baseboard), and provides guidance on how to use the features of the evaluation platform.

1.1 Precautions and warnings

The board is a delicate PCB; make sure that the evaluation board is handled by qualified personnel who are aware of the capabilities of the board. Handle the board carefully and make sure it is not bent or subjected to stress. Ensure your own safety arising from electrical hazards and other sources.


The CPU board is shipped with a 12 V DC power adapter. This adapter can be plugged into the AC mains supply anywhere in the world and is designed to receive 100-240 V AC V @ 50/60 Hz. While powering the board, you must connect only the power adapter supplied with the evaluation board and not any other part.

2. Overview



Figure 2-1 shows the CYTVII-B-H-176-SO board. Insert a TRAVEO™ T2G device into the IC socket (highlighted in red) while the evaluation board is powered OFF.

Figure 2-1. CYTVII-B-H-176-SO board




A variant of the CPU board (CYTVII-B-H-8M-176-CPU) is also available, where the TRAVEO™ T2G device is soldered directly onto the PCB. Functionally, the CYTVII-B-H-8M-176-CPU and CYTVII-B-H-176-SO boards are identical, except that the device can be easily replaced in the latter.

For CYTVII-B-H-176-SO kit open the four screws with a screwdriver, insert the device. Make sure that the device pin number 1 mark is facing the white arrow on the PCB, which is near C21. After inserting the device close the socket cover, tighten the screws. Make sure that the three holes on the socket cover are aligned as shown in [Figure 2-1](#) for the proper working of the device.


The CPU board is meant to be used along with a TRAVEO™ T2G baseboard (CYTVII-B-E-BB). The baseboard brings out all important interface connections such as CAN, LIN, SPI EEPROM, CXPI, and Flexray, and can be used in conjunction with several CPU boards of the TRAVEO™ T2G family. [Figure 2-2](#) shows the baseboard.

Figure 2-2. TRAVEO™ T2G baseboard (CYTVII-B-E-BB)



Two Samtec connectors on the CPU board and corresponding mating connectors on the baseboard are used to connect signals across the two boards. When put together, the boards appear as shown in [Figure 2-3](#).

Figure 2-3. Combination of CPU board and TRAVEO™ T2G baseboard



2.1 Functional overview

The CPU board has the following components:

1. One TRAVEO™ T2G device, either soldered or mounted on a socket (U3)
2. PMIC to generate the 5-V, 3.3-V, and 1.1-V output, which powers the CPU board and the baseboard (if connected)
3. Programming interface (Arm® Standard JTAG, Cortex® Debug, Cortex® Debug + ETM and Arm® ETM Mictor) to connect several programming tools such as IAR I-jet, Green Hills MULTI, also Infineon MiniProg
4. USB-UART interface for terminal logging (J25)
5. Two user switches (SW2 and SW4) and two user LEDs (LED4 and LED5) for standalone operation without the baseboard
6. One hibernate wakeup switch. (SW3)


7. Reset controller with manual reset switch (SW5) and voltage supervision
8. Measurement of device current on VCCD using jumper J5, VDDD using jumper J6, VDDIO_1 using jumper J7, VDDIO_2 using jumper J9, and VDDA using jumper J11 respectively
9. Samtec connector interface (J34 and J35) for connecting to the baseboard CYTVII-B-E-BB
10. SMIF connector (J33) so that the SMIF module can be mounted

The TRAVEO™ T2G baseboard has the following components:

1. Six CAN-FD transceivers based on TJA1057GT (Dual connectors P6, P7, P8)
2. Four CAN-FD transceivers based on TJA1145T, with SPI-based transceiver configuration (Dual connectors P9, P10)
3. Six LIN transceivers based on TJA1021T (Dual connectors P3, P4, P5)
4. Two Flexray transceivers based on TJA1081TS (Dual connector P2)
5. One CXPI transceiver based on S6BT112A01 (Connector P1)
6. One SPI EEPROM 25LC320A (U9)
7. Five user switches (SW1 through SW5), 10 user LEDs (USER_LED0 through USER_LED9), and one potentiometer (POT1) for analog input
8. Pin headers to access all I/Os of the TRAVEO™ T2G device (when a CPU board is connected to the baseboard)
9. Samtec connector interface (J38 and J84) for connecting to a CPU board


2.1.1 Block diagram

Figure 2-4. Block diagram




2.1.2 USB connector

Figure 2-5. USB connector




2.1.3 Ethernet connector

Figure 2-6. Ethernet connector




2.1.4 SMIF connector

Figure 2-7. SMIF connector




2.1.5 eMMC connector

Figure 2-8. eMMC connector



2.1.6 Audio connector

Figure 2-9. Audio Connector




3. Operation



This section describes the operation of the CPU board and the baseboard. It is assumed that you have connected the CPU board to the baseboard using the Samtec interface and inserted a TRAVEO™ T2G device into the IC socket (applicable to CYT7II-B-H-176-SQ boards only). Follow these steps to operate the CPU board and the baseboard:

1. For the socketed CPU board, ensure that the device is inserted into the socket. Remove the four screws on the socket using the screwdriver provided in the box and open the socket cover. If the device is not present, place one carefully using a vacuum picker or a pair of tweezers.
2. Ensure that pin 1 of the device is near the pin 1 marking on the PCB, as shown in [Figure 3-1](#). Also, ensure that the device is placed in an angle such that the pins on all four sides of the LQFP package match well with the socket pins. Align the device slightly, if required.

Figure 3-1. Orientation of the device when inserted in the socket.



3. Replace the socket cover and fix the four screws so that the socket cover tightly sits on the socket base.
4. A 12 V wall adapter board is supplied along with the CPU board. Connect the 12 V wall adapter to the barrel connector marked "12V DC" on the CPU board. Connect its plug to a mains socket using one of the four plug adapters provided in the white box (depending on the geographical location and the socket type available).
5. Ensure that jumpers J45 (default "2-3"), J5, J6, J8, J7, J10, J9, J11 (current measurement jumpers) are inserted on the CPU board.
6. Turn ON the mains supply to the wall adapter. Turn ON the switch SW1 on the CPU board. The LED labeled PWR should light up.
7. Connect an appropriate programming tool to one of the programming interfaces (J19, J20, J21, J22). Programming tool options are:
 - ❑ Arm® ETM MICTOR on J19
 - ❑ Cortex® DEBUG on J20
 - ❑ Arm® Standard JTAG on J21
 - ❑ Cortex® DEBUG and ETM on J22

8. Install the appropriate programming integrated design environment (IDE) on a PC. The programming IDE (GHS MULTI, IAR Embedded Workbench, Cypress Programmer, and so on) should be able to detect a device (read the device ID) and to load a firmware HEX file (.srec) into the device flash successfully.
As part of the release package, various firmware examples compiled in .srec programming IDEs are available. Some examples use specific transceivers on the baseboard.
9. To start with, use the LED blink example provided with the release package to test the functioning of the board.
10. Connect a USB-mini cable to J25 and the other end to a PC. Open Tera Term or your preferred terminal logging application and set the appropriate port and baud rate (typically 115,200 baud, 8, N, 1). Ensure that jumpers J24 and J26 are inserted on the CPU board. Some firmware examples provide data logs from the device or ask for user inputs over the terminal.

4. Connections and settings



4.1 Evaluation board connections

4.1.1 Baseboard connections

Make sure that the following jumpers are inserted on the baseboard, so that each transceiver on the baseboard can be used with the respective firmware example that activate each functionality of the device:

- CAN0.0 from the device uses the CAN0 transceiver on the baseboard (connect jumpers J70, J71, J72).
- CAN0.1 from the device uses the CAN1 transceiver on the baseboard (connect jumpers J66, J67, J68).
- CAN0.2 from the device uses the CAN2 transceiver on the baseboard (connect jumpers J81, J82, J83).
- CAN1.0 from the device uses the CAN3 transceiver on the baseboard (connect jumpers J76, J77, J78).
- CAN1.1 from the device uses the CAN4 transceiver on the baseboard (connect jumpers J91, J92, J93).
- CAN1.2 from the device uses the CAN5 transceiver on the baseboard (connect jumpers J86, J87, J88).
- LIN0 from the device uses the LIN0 transceiver on the baseboard (connect jumpers J58, J59, J60, J63).
- LIN1 from the device uses the LIN1 transceiver on the baseboard (connect jumpers J51, J52, J53, J56).
- LIN2 from the device uses the LIN2 transceiver on the baseboard (connect jumpers J37, J39, J40, J43).
- LIN3 from the device uses the LIN3 transceiver on the baseboard (connect jumpers J30, J31, J32, J35).
- LIN4 from the device uses the LIN4 transceiver on the baseboard (connect jumpers J22, J23, J24, J27).
- LIN5 from the device uses the LIN5 transceiver on the baseboard (connect jumpers J10, J16, J17, J20).
- EEPROM on the baseboard is enabled by connecting jumpers J47, J48, J49.
- The user switch functionality is enabled by connecting jumper J102.
- The potentiometer functionality is enabled by connecting jumper J89.

In addition, power is supplied to the baseboard by connecting jumper J80 to the 3 V or 5 V select jumper pin in the '5 V' position. Make sure that jumper J80 is always connected. Once a specific functionality is chosen by connecting the jumpers listed above, ensure that the appropriate firmware is loaded onto the device. Incorrect firmware can result in port pins being configured incorrectly leading to bus contention and damage to hardware. For example, if you connect jumpers related to CAN0.0, you must ensure that firmware configures the related ports as CAN pins. Contact technical support for firmware examples.

Apart from these interface transceivers that can be used for specific functions, all pins of the device are also accessible on the baseboard using pin headers JP1 through JP12.

The device port pins are connected to pin headers on the baseboard as listed in [Table 4-1](#).

Table 4-1. Device port pin connections on the baseboard

MCU port pin	Connection 1 Signal name of schematics	Connection 1 CPU board Test point	Connection 1 Base board Test point
VSSD	GND	TP2	Not applicable
P0.0	GPIO_P0_0	Not applicable	JP12.11
P0.1	GPIO_P0_1	Not applicable	JP12.15
P0.2	GPIO_P0_2	Not applicable	JP6.17
P0.3	GPIO_P0_3	Not applicable	JP12.18
P1.0	BB_SPI0_MISO	Not applicable	JP3.18
P1.1	BB_SPI0_MOSI	Not applicable	JP3.16
P1.2	BB_SPI0_CLK	Not applicable	JP9.17
P1.3	BB_SPI0_SS0	Not applicable	JP9.18
P2.0	GPIO_P2_0	R257.1, R258.1	Not applicable
P2.1	GPIO_P2_1	Not applicable	JP12.12
P2.2	ETH_RXER	TP137	Not applicable
P2.3	GPIO_P2_3	Not applicable	JP12.17
P2.4	BB_SPI0_HOLD	TP122	JP12.4
P2.5	BB_SPI0_WP	TP123	JP2.3
P3.0	ETH_MDIO	TP142	Not applicable
P3.1	ETH_MDC	TP143	Not applicable
P3.2	USER_LED1	J16.2	Not applicable
P3.3	USER_LED2	J17.2	Not applicable
P3.4	USER_SW1	J13.1	Not applicable
P3.5	USER_SW2	J15.1	Not applicable
VDDD	Not applicable	TP9	Not applicable
VSSD	GND	TP2	Not applicable
P4.0	BB_LIN1_RXD	TP130	JP6.15
P4.1	BB_LIN1_TXD	TP131	JP6.14
P4.2	BB_LIN1_SLP	TP132	JP6.3
P4.3	BB_CAN1_TXD	TP133	JP6.9
P4.4	BB_CAN1_RXD	TP134	JP6.8
P5.0	GPIO_P5_0	Not applicable	Not applicable
P5.1	GPIO_P5_1	Not applicable	JP12.13
P5.2	GPIO_P5_2	Not applicable	JP6.13
P5.3	GPIO_P5_3	Not applicable	JP5.18
P5.4	GPIO_P5_4	TP140	JP6.10
P5.5	BB_LIN1_WAKE	TP139	JP6.4
P6.0	UART_RX	TP185	JP7.3
P6.1	UART_TX	TP186	JP7.6
P6.2	EMMC_WP	TP277	Not applicable
P6.3	GPIO_P6_3	R197.1, R247.1	Not applicable
P6.4	GPIO_P6_4	R196.1, R221.1	Not applicable
P6.5	GPIO_P6_5	R198.1, R223.1	Not applicable
P6.6	GPIO_P6_6	Not applicable	JP10.10
P6.7	GPIO_P6_7	Not applicable	JP10.9
VDDD	Not applicable	TP9	Not applicable

Table 4-1. Device port pin connections on the baseboard (*continued*)

MCU port pin	Connection 1 Signal name of schematics	Connection 1 CPU board Test point	Connection 1 Base board Test point
VDDIO_1	Not applicable	TP10	Not applicable
VSSD	GND	TP2	Not applicable
VCCD	Not applicable	TP8	Not applicable
VCCD	Not applicable	TP8	Not applicable
P7.0	SPIHB_SEL1	R157.2, R170.1, R189	Not applicable
P7.1	GPIO_P7_1	R199.1, R250.1	Not applicable
P7.2	GPIO_P7_2	R200.1, R252.1	Not applicable
P7.3	GPIO_P7_3	R201.1, R254.1	Not applicable
P7.4	GPIO_P7_4	R202.1, R256.1	Not applicable
P7.5	SPIHB_DATA4	TP279	Not applicable
P7.6	BB_USER_LED0	TP155	JP7.18
P7.7	BB_USER_LED1	Not applicable	JP7.10
P8.0	SPIHB_DATA5	TP281	Not applicable
P8.1	SPIHB_DATA6	TP283	Not applicable
P8.2	SPIHB_DATA7	TP282	Not applicable
P8.3	BB_USER_LED2	Not applicable	JP7.13
P8.4	BB_USER_LED3	Not applicable	JP7.9
P9.0	BB_USER_LED4	Not applicable	JP7.14
P9.1	BB_USER_LED5	Not applicable	JP7.8
P9.2	BB_USER_LED6	Not applicable	JP7.15
P9.3	BB_USER_LED7	Not applicable	JP7.7
P10.0	BB_USER_LED8	TP166	JP6.7
P10.1	BB_USER_LED9	TP167	JP6.6
P10.2	BB_FRA_RXD	Not applicable	Not applicable
P10.3	BB_FRA_TXD	Not applicable	Not applicable
P10.4	BB_FRA_TXEN	Not applicable	Not applicable
P10.5	BB_FRB_RXD	Not applicable	Not applicable
P10.6	BB_FRB_TXD	Not applicable	Not applicable
P10.7	BB_FRB_TXEN	Not applicable	Not applicable
P11.0	GPIO_P11_0	Not applicable	JP5.16
P11.1	GPIO_P11_1	Not applicable	JP5.15
P11.2	BB_FRA_STBN	TP266	Not applicable
VREFL	VREFL_BB	R19.2	JP5.9
VSSA	Not applicable	R19.1	Not applicable
VDDA	Not applicable	R18.1	Not applicable
VREFH	VREFH_BB	R18.2	JP5.10
P12.0	BB_CAN2_TXD	Not applicable	JP10.8
P12.1	BB_CAN2_RXD	Not applicable	JP10.7
P12.2	GPIO_P12_2	Not applicable	JP10.11
P12.3	GPIO_P12_3	Not applicable	JP10.13
P12.4	BB_CAN4_TXD	Not applicable	JP11.8
P12.5	BB_CAN4_RXD	Not applicable	JP11.7
P12.6	BB_ADC_POT	Not applicable	JP7.11
P12.7	GPIO_P12_7	TP184	JP11.4
VDDIO_2	Not applicable	TP11	Not applicable

Table 4-1. Device port pin connections on the baseboard (*continued*)

MCU port pin	Connection 1 Signal name of schematics	Connection 1 CPU board Test point	Connection 1 Base board Test point
VSSD	GND	TP2	Not applicable
P13.0	GPIO_P13_0	R225.1	Not applicable
P13.1	GPIO_P13_1	R227.1	Not applicable
P13.2	AUDIOSS_TX_WS	TP195	Not applicable
P13.3	AUDIOSS_TX_SDO	TP196	Not applicable
P13.4	AUDIOSS_CLK_I2S_IF_R	R259.1	Not applicable
P13.5	AUDIOSS_RX_SCK	TP214	Not applicable
P13.6	AUDIOSS_RX_WS	TP216	Not applicable
P13.7	AUDIOSS_RX_SDI	TP217	Not applicable
P14.0	BB_FRA_EN	TP267	Not applicable
P14.1	BB_FRA_ERRN	TP275	Not applicable
P14.2	BB_FRA_WAKE	TP269	Not applicable
P14.3	BB_CAN7_WAKE	Not applicable	JP11.3, J101.2
P14.4	BB_FRB_STBN	Not applicable	Not applicable
P14.5	BB_FRB_EN	Not applicable	Not applicable
P14.6	BB_FRB_ERRN	Not applicable	Not applicable
P14.7	BB_FRB_WAKE	Not applicable	Not applicable
P15.0	BB_CAN6_TXD	TP200	Not applicable
P15.1	BB_CAN6_RXD	TP202	Not applicable
P15.2	BB_LIN0_WAKE	Not applicable	JP1.5
P15.3	BB_LIN2_WAKE	Not applicable	JP2.7
VDDD	Not applicable	TP9	Not applicable
VCCD	Not applicable	TP8	Not applicable
VCCD	Not applicable	TP8	Not applicable
VCCD	Not applicable	TP8	Not applicable
VSSD	GND	TP2	Not applicable
P16.3	BB_LIN3_WAKE	Not applicable	JP2.11
P17.0	BB_LIN4_RXD	Not applicable	JP2.13
P17.1	BB_LIN4_TXD	Not applicable	JP2.14
P17.2	BB_LIN4_SLP	Not applicable	JP2.16
P17.3	BB_LIN4_WAKE	Not applicable	JP2.15
P17.4	BB_LIN5_WAKE	Not applicable	JP1.11
P17.5	BB_LIN5_RXD	Not applicable	JP1.9
P17.6	BB_LIN5_TXD	Not applicable	JP1.10
P17.7	BB_LIN5_SLP	Not applicable	JP1.12
P18.0	ETH_REFCLK	TP110	Not applicable
P18.1	ETH_TXEN	TP111	Not applicable
P18.2	ETH_TXER	TP112	Not applicable
P18.3	ETH_TXC	TP113	Not applicable
P18.4	GPIO_P18_4	R229.1, R230.1	Not applicable
P18.5	GPIO_P18_5	R231.1, R232.1	Not applicable
P18.6	GPIO_P18_6	R233.1, R234.1	Not applicable
P18.7	GPIO_P18_7	R235.1, R236.1	Not applicable
VDDD	Not applicable	TP9	Not applicable
VSSD	GND	TP2	Not applicable

Table 4-1. Device port pin connections on the baseboard (*continued*)

MCU port pin	Connection 1 Signal name of schematics	Connection 1 CPU board Test point	Connection 1 Base board Test point
P19.0	GPIO_P19_0	J36.3	Not applicable
P19.1	GPIO_P19_1	J37.3	Not applicable
P19.2	GPIO_P19_2	J38.3	Not applicable
P19.3	GPIO_P19_3	J39.3	Not applicable
P19.4	SWCLK_TCLK_SEC	J40.3	Not applicable
P20.0	BB_LIN2_RXD	Not applicable	JP2.5
P20.1	BB_LIN2_TXD	Not applicable	JP2.6
P20.2	BB_LIN2_SLP	Not applicable	JP2.8
P20.3	BB_CAN5_TXD	Not applicable	JP11.6
P20.4	BB_CAN5_RXD	Not applicable	JP11.5
P20.5	BB_CAN5_S	Not applicable	JP10.16
P20.6	BB_CAN7_TXD	TP232	Not applicable
P20.7	BB_CAN7_RXD	TP234	Not applicable
P21.0	CPU_WCO_IN	R21.2	Not applicable
P21.1	CPU_WCO_OUT	R22.2	Not applicable
P21.2	CPU_ECO_IN	R23.2	Not applicable
P21.3	CPU_ECO_OUT	R24.2	Not applicable
P21.4	HIBERNATE_WAKEUP	J14.1	Not applicable
XRES	CPU_XRES	J18.1	Not applicable
VDDD	Not applicable	TP9	Not applicable
VSSD	GND	TP2	Not applicable
VSSD	GND	TP2	Not applicable
VCCD	Not applicable	TP8	Not applicable
P21.5	GPIO_P21_5	R245.1, R246.1	Not applicable
P21.6	BB_LIN0_TXD	Not applicable	JP1.4
P21.7	BB_LIN0_SLP	Not applicable	JP1.6
DRV_VOUT	DRV_VOUT	R9.1,R12.1,TP244	Not applicable
P22.1	EXT_PS_CTL0	J43.2,TP6	Not applicable
P22.2	EXT_PS_CTL1	J42.2,J44.2	Not applicable
P22.3	EXT_PS_CTL2	Not applicable	JP8.3
P22.4	TRACE_CLOCK	R46.2,TP247	Not applicable
P22.5	BB_LIN3_RXD	Not applicable	JP2.9
P22.6	BB_LIN3_TXD	TP251	JP2.10
P22.7	BB_LIN3_SLP	Not applicable	JP2.12
P23.0	BB_CAN3_TXD	TP250	JP3.12
P23.1	BB_CAN3_RXD	TP254	JP3.14
P23.2	GPIO_P23_2	Not applicable	JP10.14
P23.3	ETH_RXC	TP141	Not applicable
P23.4	SWO_TDO_PRM	J37.1	Not applicable
P23.5	SWCLK_TCLK_PRM	J40.1	Not applicable
P23.6	SWDIO_TMS_PRM	J39.1	Not applicable
P23.7	SWDOE_TDI_PRM	J38.1	Not applicable
VDDD	Not applicable	TP9	Not applicable

The first column in [Table 4-1](#) lists the pin number on the MCU, followed by the port pin name.

For each pin, the connected peripheral or net on the baseboard is depicted by the Netname of Schematics column.

The Baseboard test point column indicates the place where the signal can be probed on the baseboard. For example, JP6.15 refers to the 15th pin on the JP6 header.

A value of #NA in the Test point column indicates that the signal is unavailable on the JPx pin header on the baseboard. The signal might still be available on separate pin headers near the respective peripheral.

For details on the alternate functionality of each MCU pin, see the device datasheet.

Note: If there are pins with more than one connection to the baseboard, make sure that no two peripherals are driven at the same time. The unused peripheral jumpers must be disconnected before using the other connection.

4.1.2 Reset switch

The correspondence between the reset switch and port number is given in [Table 4-2](#).

Table 4-2. Reset Switch

Switch	Part No.	Port name
Reset Switch	SW5	XRES

4.1.3 Hibernate wakeup switch

The correspondence between the hibernate wakeup switch and port number is given in [Table 4-3](#).

Table 4-3. Hibernate Wakeup Switch

Switch	Part No.	Port name
Hibernate Wakeup Switch	SW3	P21.4

4.1.4 User switches

The correspondence between the user switches and port number is given in [Table 4-4](#).

Table 4-4. User switches

Switch	Part No.	Port name
User SW1	SW2	P3.4
User SW2	SW4	P3.5

4.1.5 User LEDs

The correspondence between the User LEDs and port number is given in [Table 4-5](#).

Table 4-5. User LEDs

Switch	Part No.	Port Name
User LED1	LED4	P3.2
User LED2	LED5	P3.3

4.1.6 JTAG select jumpers

The correspondence between the JTAG select jumpers and selected functions is given in [Table 4-6](#).

Table 4-6. JTAG select jumpers

Jumpers name	Part No.	Connection	Function
TRSTN	J36	1-2 (default)	SWJ_TRSTN
		2-3	GPIO_P19_0
SWO_TDO	J37	1-2 (default)	SWJ_SWO_TDO
		2-3	GPIO_P19_1
SWDOE_TDI	J38	1-2 (default)	SWJ_SWDOE_TDI
		2-3	GPIO_P19_2
SWDIO_TMS	J39	1-2 (default)	SWJ_SWDIO_TMS
		2-3	GPIO_P19_3
SWCLK_TCLK	J40	1-2 (default)	SWCLK_TCLK
		2-3	GPIO_P19_4


4.2 Power supply settings

Power supply settings are shown in [Table 4-7](#) and [Figure 4-1](#).

Table 4-7. Power supply jumper settings

Jumper	Pin	MCU power	Remarks
J46	1-2	VCC11 = VCC11_TR	From PASS TRANSISTOR
	2-3 (default)	VCC11 = VCC11_PMIC	From S6BP501A
J45	1-2 (default)	VDDD = +3.3 V	Short Jumper - J6
	2-3	VDDD = +5.0 V	
J8	1-2 (default)	VDDIO_1 = +3.3 V	Short Jumper - J7
	2-3	VDDIO_1 = +5.0 V	
J10	1-2 (default)	VDDIO_2 = +3.3 V	Short Jumper - J9
	2-3	VDDIO_2 = +5.0 V	
	1-2 (default)	VDDA = +3.3 V	Short Jumper - J11
	2-3	VDDA = +5.0 V	

Figure 4-1. Power supply jumpers settings



4.3 External power supply control signal settings

Jumper settings of the external power supply control signals from MCU are shown in [Table 4-8](#).

Table 4-8. External power supply control signals jumper settings

Jumpers name	PASS transistor	S6BP501A	Remarks
EXT_PS_CTL0	J43	J41	J43 open (default)
			J41 close (default)
EXT_PS_CTL1	J44	J42	J44 open (default)
			J42 close (default)

4.4 Ethernet settings

Ethernet settings are shown in [Table 4-9](#).

Table 4-9. Ethernet settings

Function status	Jumper	Settings	Remarks
Ethernet is enabled	J28	Closed	
Ethernet is disabled		Open	

4.5 Settings

Settings are shown in [Table 4-10](#).

Table 4-10. Settings

Function status	Jumper	Settings	Remarks
is enabled	J30	Closed	
is disabled		Open	

5. Power management IC (PMIC)




5.1 Power management IC (PMIC) module

5.1.1 PMIC module - CYALKIT-A18

CYALKIT-A18 is the PMIC module for the power block of an automotive application with CYT4B series MCU. The PMIC Module implements the Infineon PMIC S6BP501A and is optimized for power supply of CYT4B Series MCU. 1.1 V output to supply to VCCD of CYT4B Series MCU needs external Schottky barrier diode (SBD), output capacitor and constant load current no less than 20 mA.

Figure 5-1. Evaluation board block diagram




*SMPS: Switching Mode Power Supply

5.1.2 Input/Output pin descriptions

Table 5-1. Input/output pin descriptions

Connector symbol	I/O	Function description
1, 2	VOUT3V	O 3.3 V power rail output terminal (0 A - 0.75 A)
3, 4	PGND	O Ground terminal
5	SYNC	I Mode setting or external clock input terminal Refer to the S6BP501A datasheet
6	PG1V	O Power good terminal of 1.1 V power rail
7	PG3V	O Power good terminal of 3.3 V power rail
8	PG5V	O Power good terminal of 5 V power rail
9	FB1V_IN	I Feed-back terminal for 1.1 V power rail
10, 11	PGND	– Ground terminal
12, 13	VOUT1V	O 1.1 V output terminal (0 A - 0.75 A)
14, 15	VOUT5V	O 5 V output terminal (0 A - 0.75 A)
16, 17	PGND	– Ground terminal
18	HOT	O Thermal warning output terminal
19	EN5V	I 5 V power rail output enable terminal
20	EN3V	I 3.3 V power rail output enable terminal
21	EN1V	I 1.1 V power rail output enable terminal
22	N.C.	N.C. No connection
23, 24	PGND	– Ground terminal
25, 26	VIN	I DC power supply terminal (4.5 V-42 V, 12 V typ.)

Figure 5-2. Pin layout



A. CPU board schematics



Figure A-1. Schematic (1/31)




Figure A-2. Schematic (2/31)




Figure A-3. Schematic (3/31)




Figure A-4. Schematic (4/31)




Figure A-5. Schematic (5/31)






Figure A-7. Schematic (7/31)






Figure A-9. Schematic (9/31)




Figure A-10. Schematic (10/31)




Figure A-11. Schematic (11/31)




Figure A-12. Schematic (12/31)




Figure A-13. Schematic (13/31)




Figure A-14. Schematic (14/31)




Figure A-15. Schematic (15/31)




Figure A-16. Schematic (16/31)




Figure A-17. Schematic (17/31)




Figure A-18. Schematic (18/31)




Figure A-19. Schematic (19/31)




Figure A-20. Schematic (20/31)




Figure A-21. Schematic (21/31)




Figure A-22. Schematic (22/31)




Figure A-23. Schematic (23/31)




Figure A-24. Schematic (24/31)




Figure A-25. Schematic (25/31)




Figure A-26. Schematic (26/31)




Figure A-27. Schematic (27/31)




Figure A-28. Schematic (28/31)




Figure A-29. Schematic (29/31)




Figure A-30. Schematic (30/31)






Figure A-31. Schematic (31/31)



B. CPU board component assembly




Figure B-1. Component assembly (top)



CYTVII_C_2D_AB_REV_01
PRIMARY ASSEMBLY

ART FILM - PASSY

Figure B-2. Component assembly (bottom)



C. Baseboard schematics



Figure C-1. Schematic (1/16)




Figure C-2. Schematic (2/16)








Figure C-5. Schematic (5/16)




Figure C-6. Schematic (6/16)






Figure C-8. Schematic (8/16)






Figure C-10. Schematic (10/16)




Figure C-11. Schematic (11/16)




Figure C-12. Schematic (12/16)






Figure C-13. Schematic (13/16)



CYPRESS
 EMBEDDED IN TOMORROW™

CYPRESS SEMICONDUCTOR
 198 CHAMPION COURT
 SAN JOSE, CA 95134
 (408) 943-2600

CYPRESS SEMICONDUCTOR © 2018

SCH Title : TRAVEO II BASE BOARD

Page Title :CXPI, EEPROM & POT

Size B	Document Number 5869234	Drawn By BALA K	Approved By SPPD	Rev A
Date:	Thursday, May 24, 2018	Sheet	15	of 18

Figure C-14. Schematic (14/16)




Figure C-15. Schematic (15/16)






Figure C-16. Schematic (16/16)



D. Baseboard component assembly



Figure D-1. Component assembly (top)





Revision history



Document Title: CYTVII-B-H-8M-176-CPU evaluation board user guide			
Document Number: 002-25907			
Revision	ECN#	Issue Date	Description of Change
**	6493098	02/25/2019	New User Guide
*A	6923377	07/15/2020	Updated Overview chapter on page 5 : Updated description (Added content under Figure 2-1).
*B	7163047	06/18/2021	Updated CPU board schematics chapter on page 28 : Updated all existing schematics and added some schematics.
*C	7204851	07/30/2021	Corrected typo of the part number in all page footers (Replaced "CYTVII-B-H-1M-176-CPU" with "CYTVII-B-H-8M-176-CPU"). Updated Operation chapter on page 15 : Updated description (Replaced "J24 and J25" with "J24 and J26" in step 10).
*D	7414726	11/01/2021	Updated Overview chapter on page 5 : Updated Figure 2-1 . Updated Figure 2-2 . Updated Figure 2-3 . Updated " Functional overview " on page 7: Updated " USB connector " on page 10: Updated Figure 2-5 . Updated " Ethernet connector " on page 11: Updated Figure 2-6 . Updated " SMIF connector " on page 12: Updated Figure 2-7 . Updated " eMMC connector " on page 13: Updated Figure 2-8 . Updated " Audio connector " on page 14: Updated Figure 2-9 . Updated CPU board schematics chapter on page 28 : Updated all existing schematics.