

## 62 mm C-Series module with CoolSiC™ Trench MOSFET

### Features

- Electrical features
  - $V_{DSS} = 2000\text{ V}$
  - $I_{DN} = 300\text{ A} / I_{DRM} = 600\text{ A}$
  - Low switching losses
  - High current density
- Mechanical features
  - 4 kV AC 1 min insulation


### Potential applications

- UPS systems
- DC/DC converter
- High-frequency switching application
- Solar applications

### Product validation

- Qualified for industrial applications according to the relevant tests of IEC 60747, 60749 and 60068

### Description



## Table of contents

	<b>Description</b> .....	1
	<b>Features</b> .....	1
	<b>Potential applications</b> .....	1
	<b>Product validation</b> .....	1
	<b>Table of contents</b> .....	2
<b>1</b>	<b>Package</b> .....	3
<b>2</b>	<b>MOSFET, T1 / T2</b> .....	3
<b>3</b>	<b>Body diode (MOSFET, T1 / T2)</b> .....	5
<b>4</b>	<b>Characteristics diagrams</b> .....	7
<b>5</b>	<b>Circuit diagram</b> .....	11
<b>6</b>	<b>Package outlines</b> .....	12
<b>7</b>	<b>Module label code</b> .....	13
	<b>Revision history</b> .....	14
	<b>Disclaimer</b> .....	15

## 1 Package

**Table 1** Insulation coordination

Parameter	Symbol	Note or test condition	Values	Unit
Isolation test voltage	$V_{ISOL}$	RMS, $f = 50 \text{ Hz}$ , $t = 1 \text{ min}$	4.0	kV
Material of module baseplate			Cu	
Internal isolation		basic insulation (class 1, IEC 61140)	$Al_2O_3$	
Creepage distance	$d_{Creep}$	terminal to heatsink	29.0	mm
Creepage distance	$d_{Creep}$	terminal to terminal	23.0	mm
Clearance	$d_{Clear}$	terminal to heatsink	23.0	mm
Clearance	$d_{Clear}$	terminal to terminal	11.0	mm
Comparative tracking index	$CTI$		> 400	
Relative thermal index (electrical)	$RTI$	housing	140	°C

**Table 2** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Stray inductance module	$L_{sCE}$			20		nH
Module lead resistance, terminals - chip	$R_{CC'+EE'}$	$T_C = 25 \text{ °C}$ , per switch		0.475		mΩ
Storage temperature	$T_{stg}$		-40		125	°C
Mounting torque for module mounting	$M$	- Mounting according to valid application note	M6, Screw	3	6	Nm
Terminal connection torque	$M$	- Mounting according to valid application note	M6, Screw	2.5	5	Nm
Weight	$G$			340		g

## 2 MOSFET, T1 / T2

**Table 3** Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Drain-source voltage	$V_{DSS}$	$T_{vj} = 25 \text{ °C}$	2000	V
Implemented drain current	$I_{DN}$		300	A
Continuous DC drain current	$I_{DDC}$	$T_{vj} = 175 \text{ °C}$ , $V_{GS} = 18 \text{ V}$ $T_C = 25 \text{ °C}$	280	A
Repetitive peak drain current	$I_{DRM}$	verified by design, $t_p$ limited by $T_{vjmax}$	600	A

(table continues...)

**Table 3 (continued) Maximum rated values**

Parameter	Symbol	Note or test condition	Values	Unit
Gate-source voltage, max. transient voltage	$V_{GS}$	$D < 0.01$	-10/23	V
Gate-source voltage, max. static voltage	$V_{GS}$		-7/20	V

**Table 4 Recommended values**

Parameter	Symbol	Note or test condition	Values	Unit
On-state gate voltage	$V_{GS(on)}$		18	V
Off-state gate voltage	$V_{GS(off)}$		-3	V

**Table 5 Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit		
			Min.	Typ.	Max.			
Drain-source on-resistance	$R_{DS(on)}$	$I_D = 300\text{ A}$		$V_{GS} = 18\text{ V}, T_{vj} = 25\text{ °C}$	3.5	5.3	mΩ	
				$V_{GS} = 18\text{ V}, T_{vj} = 125\text{ °C}$		7.3		
				$V_{GS} = 18\text{ V}, T_{vj} = 175\text{ °C}$		10.4		
Gate threshold voltage	$V_{GS(th)}$	$I_D = 168\text{ mA}, V_{DS} = V_{GS}, T_{vj} = 25\text{ °C},$ (tested after 1ms pulse at $V_{GS} = +20\text{ V}$ )	3.45	4.3	5.15	V		
Total gate charge	$Q_G$	$V_{DD} = 1200\text{ V}, V_{GS} = -3/18\text{ V}$		1.17		μC		
Internal gate resistor	$R_{Gint}$	$T_{vj} = 25\text{ °C}$		1.2		Ω		
Input capacitance	$C_{ISS}$	$f = 100\text{ kHz}, V_{DS} = 1200\text{ V}, V_{GS} = 0\text{ V}, T_{vj} = 25\text{ °C}$		36.1		nF		
Output capacitance	$C_{OSS}$	$f = 100\text{ kHz}, V_{DS} = 1200\text{ V}, V_{GS} = 0\text{ V}, T_{vj} = 25\text{ °C}$		0.845		nF		
Reverse transfer capacitance	$C_{rSS}$	$f = 100\text{ kHz}, V_{DS} = 1200\text{ V}, V_{GS} = 0\text{ V}, T_{vj} = 25\text{ °C}$		0.061		nF		
$C_{OSS}$ stored energy	$E_{OSS}$	$V_{DS} = 1200\text{ V}, V_{GS} = -3/18\text{ V}, T_{vj} = 25\text{ °C}$		1520		μJ		
Drain-source leakage current	$I_{DSS}$	$V_{DS} = 2000\text{ V}, V_{GS} = -3\text{ V}, T_{vj} = 25\text{ °C}$		0.06	527	μA		
Gate-source leakage current	$I_{GSS}$	$V_{DS} = 0\text{ V}, T_{vj} = 25\text{ °C}$			400	nA		
Turn-on delay time (inductive load)	$t_{d on}$	$I_D = 300\text{ A}, R_{Gon} = 7.1\text{ Ω}, V_{DD} = 1200\text{ V}, V_{GS} = -3/18\text{ V}$	$T_{vj} = 25\text{ °C}$	204		ns		
			$T_{vj} = 125\text{ °C}$		187			
			$T_{vj} = 175\text{ °C}$		181			

**(table continues...)**

**Table 5 (continued) Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Rise time (inductive load)	$t_r$	$I_D = 300\text{ A}$ , $R_{Gon} = 7.1\ \Omega$ , $V_{DD} = 1200\text{ V}$ , $V_{GS} = -3/18\text{ V}$	$T_{vj} = 25\text{ }^\circ\text{C}$	219		ns
			$T_{vj} = 125\text{ }^\circ\text{C}$	195		
			$T_{vj} = 175\text{ }^\circ\text{C}$	194		
Turn-off delay time (inductive load)	$t_{d\ off}$	$I_D = 300\text{ A}$ , $R_{Goff} = 4.3\ \Omega$ , $V_{DD} = 1200\text{ V}$ , $V_{GS} = -3/18\text{ V}$	$T_{vj} = 25\text{ }^\circ\text{C}$	256		ns
			$T_{vj} = 125\text{ }^\circ\text{C}$	282		
			$T_{vj} = 175\text{ }^\circ\text{C}$	296		
Fall time (inductive load)	$t_f$	$I_D = 300\text{ A}$ , $R_{Goff} = 4.3\ \Omega$ , $V_{DD} = 1200\text{ V}$ , $V_{GS} = -3/18\text{ V}$	$T_{vj} = 25\text{ }^\circ\text{C}$	80.3		ns
			$T_{vj} = 125\text{ }^\circ\text{C}$	82.1		
			$T_{vj} = 175\text{ }^\circ\text{C}$	84.2		
Turn-on energy loss per pulse	$E_{on}$	$I_D = 300\text{ A}$ , $V_{DD} = 1200\text{ V}$ , $L_\sigma = 25\text{ nH}$ , $V_{GS} = -3/18\text{ V}$ , $R_{Gon} = 7.1\ \Omega$ , $di/dt = 3.4\text{ kA}/\mu\text{s}$ ( $T_{vj} = 175\text{ }^\circ\text{C}$ )	$T_{vj} = 25\text{ }^\circ\text{C}$	45.5		mJ
			$T_{vj} = 125\text{ }^\circ\text{C}$	46.5		
			$T_{vj} = 175\text{ }^\circ\text{C}$	50.5		
Turn-off energy loss per pulse	$E_{off}$	$I_D = 300\text{ A}$ , $V_{DD} = 1200\text{ V}$ , $L_\sigma = 25\text{ nH}$ , $V_{GS} = -3/18\text{ V}$ , $R_{Goff} = 4.3\ \Omega$ , $dv/dt = 11.4\text{ kV}/\mu\text{s}$ ( $T_{vj} = 175\text{ }^\circ\text{C}$ )	$T_{vj} = 25\text{ }^\circ\text{C}$	23.7		mJ
			$T_{vj} = 125\text{ }^\circ\text{C}$	24.5		
			$T_{vj} = 175\text{ }^\circ\text{C}$	25.2		
Thermal resistance, junction to case	$R_{thJC}$	per MOSFET			0.119	K/W
Thermal resistance, case to heat sink	$R_{thCH}$	per MOSFET, $\lambda_{grease} = 1\text{ W}/(\text{m}\cdot\text{K})$ , $\lambda_{grease} = 1\text{ W}/(\text{m}\cdot\text{K})$		0.0380		K/W
Temperature under switching conditions	$T_{vj\ op}$		-40		175	$^\circ\text{C}$

*Note: The selection of positive and negative gate-source voltages impacts losses and the long-term behavior of the MOSFET and body diode. The design guidelines described in Application Notes AN 2018-09 and AN 2021-13 must be considered to ensure sound operation of the device over the planned lifetime.*

*$T_{vj,op} > 150\text{ }^\circ\text{C}$  is allowed for operation at overload conditions for MOSFET and body diode. For detailed specifications, please refer to AN 2021-13.*

### 3 Body diode (MOSFET, T1 / T2)

**Table 6 Maximum rated values**

Parameter	Symbol	Note or test condition	Values	Unit
DC body diode forward current	$I_{SD}$	$T_{vj} = 175\text{ }^\circ\text{C}$ , $V_{GS} = -3\text{ V}$ $T_C = 25\text{ }^\circ\text{C}$	235	A


**Table 7**                    **Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit	
			Min.	Typ.	Max.		
Forward voltage	$V_{SD}$	$I_{SD} = 300 \text{ A}, V_{GS} = -3 \text{ V}$	$T_{vj} = 25 \text{ }^\circ\text{C}$		4.6	6.15	V
			$T_{vj} = 125 \text{ }^\circ\text{C}$		4.15		
			$T_{vj} = 175 \text{ }^\circ\text{C}$		4		

## 4 Characteristics diagrams


**Output characteristic (typical), MOSFET, T1 / T2**

$I_D = f(V_{DS})$   
 $V_{GS} = 18\text{ V}$




**Output characteristic field (typical), MOSFET, T1 / T2**

$I_D = f(V_{DS})$   
 $T_{vj} = 175\text{ °C}$




**Transfer characteristic (typical), MOSFET, T1 / T2**

$I_D = f(V_{GS})$   
 $V_{DS} = 20\text{ V}$



**Drain source on-resistance (typical), MOSFET, T1 / T2**


$R_{DS(on)} = f(T_{vj})$   
 $V_{GS} = 18\text{ V}$



4 Characteristics diagrams


**Gate charge characteristic (typical), MOSFET, T1 / T2**

$V_{GS} = f(Q_G)$   
 $I_D = 300 \text{ A}, T_{vj} = 25 \text{ }^\circ\text{C}$




**Gate-source threshold voltage (typical), MOSFET, T1 / T2**

$V_{GS(th)} = f(T_{vj})$   
 $V_{GS} = V_{DS}$




**Capacity characteristic (typical), MOSFET, T1 / T2**

$C = f(V_{DS})$   
 $f = 100 \text{ kHz}, T_{vj} = 25 \text{ }^\circ\text{C}, V_{GS} = 0 \text{ V}$



**Forward characteristic body diode (typical), MOSFET, T1 / T2**

$I_{SD} = f(V_{SD})$   
 $T_{vj} = 25 \text{ }^\circ\text{C}$






4 Characteristics diagrams

**Switching losses (typical), MOSFET, T1 / T2**

$E = f(R_G)$


$V_{DD} = 1200\text{ V}$ ,  $I_D = 300\text{ A}$ ,  $V_{GS} = -3/18\text{ V}$



**Switching losses (typical), MOSFET, T1 / T2**

$E = f(I_D)$


$R_{Goff} = 4.3\ \Omega$ ,  $R_{Gon} = 7.1\ \Omega$ ,  $V_{DD} = 1200\text{ V}$ ,  $V_{GS} = -3/18\text{ V}$



**Switching times (typical), MOSFET, T1 / T2**

$t = f(R_G)$


$V_{DD} = 1200\text{ V}$ ,  $I_D = 300\text{ A}$ ,  $T_{vj} = 175\text{ °C}$ ,  $V_{GS} = -3/18\text{ V}$



**Switching times (typical), MOSFET, T1 / T2**

$t = f(I_D)$

$R_{Goff} = 4.3\ \Omega$ ,  $R_{Gon} = 7.1\ \Omega$ ,  $V_{DD} = 1200\text{ V}$ ,  $T_{vj} = 175\text{ °C}$ ,  $V_{GS} = -3/18\text{ V}$




4 Characteristics diagrams

**Reverse bias safe operating area (RBSOA), MOSFET, T1 / T2**


$I_D = f(V_{DS})$

$R_{Goff} = 4.3 \Omega$ ,  $T_{vj} = 175 \text{ }^\circ\text{C}$ ,  $V_{GS} = -3/18 \text{ V}$



**Transient thermal impedance, MOSFET, T1 / T2**

$Z_{th} = f(t)$



## 5 Circuit diagram







Figure 1

**6 Package outlines**



**Figure 2**

## 7 Module label code

Module label code			
Code format	Data Matrix	Barcode Code128	
Encoding	ASCII text	Code Set A	
Symbol size	16x16	23 digits	
Standard	IEC24720 and IEC16022	IEC8859-1	
Code content	<i>Content</i> Module serial number Module material number Production order number Date code (production year) Date code (production week)	<i>Digit</i> 1 - 5 6 - 11 12 - 19 20 - 21 22 - 23	<i>Example</i> 71549 142846 55054991 15 30
Example	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">   71549142846550549911530 </div> <div style="text-align: center;">   71549142846550549911530 </div> </div>		

**Figure 3**

## Revision history

Document revision	Date of release	Description of changes
0.10	2021-06-28	Initial version
0.20	2022-11-09	Target datasheet
1.00	2022-12-22	Final datasheet

## Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

**Edition 2022-12-22**

**Published by**

**Infineon Technologies AG**

**81726 Munich, Germany**

**© 2022 Infineon Technologies AG**

**All Rights Reserved.**

**Do you have a question about any aspect of this document?**

**Email: [erratum@infineon.com](mailto:erratum@infineon.com)**

**Document reference**

**IFX-ABB179-003**

## Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffungsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

## Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.