SiC

Silicon Carbide Diode

5th Generation thinQ!™

650V SiC Schottky Diode

IDH16G65C5

Final Datasheet

Rev. 2.2, 2012-12-10

Power Management & Multimarket

1 Description



ThinQ!™ Generation 5 represents Infineon leading edge technology for the SiC Schottky Barrier diodes. The Infineon proprietary diffusion soldering process, already introduced with G3 is now combined with a new, more compact design and thin-wafer technology. The result is a new family of products showing improved efficiency over all load conditions, resulting from both the improved thermal characteristics and a lower figure of merit (Qc x Vf).
The new thinQ!™ Generation 5 has been designed to complement our 650V CoolMOS™ families: this ensures meeting the most stringent application requirements in this voltage range.



Features

- Revolutionary semiconductor material - Silicon Carbide
- Benchmark switching behavior
- No reverse recovery/ No forward recovery
- Temperature independent switching behavior
- High surge current capability
- Pb-free lead plating; RoHS compliant
- Qualified according to JEDEC[1)] for target applications
- Breakdown voltage tested at 35 mA[2)]
- Optimized for high temperature operation

Benefits

- System efficiency improvement over Si diodes
- System cost / size savings due to reduced cooling requirements
- Enabling higher frequency / increased power density solutions
- Higher system reliability due to lower operating temperatures
- Reduced EMI

Applications

- Switch mode power supply
- Power factor correction
- Solar inverter
- Uninterruptible power supply

Table 1 Key Performance Parameters

Parameter	Value	Unit
V_{DC}	650	V
Q_C; V_R=400V	23	nC
E_C; V_R=400V	5.3	µJ
I_F @ T_C < 135°C	16	A

Table 2 Pin Definition

Pin 1	Pin 2	Pin 3
C	A	n.a.

Type / ordering Code	Package	Marking	Related links
IDH16G65C5	PG-TO220-2	D1665C5	www.infineon.com/sic

1) J-STD20 and JESD22

2) All devices tested under avalanche conditions for a time periode of 10ms

Table of Contents

1 Description....2
2 Maximum ratings....4
3 Thermal characteristics....4
4 Electrical characteristics....5
5 Electrical characteristics diagrams....6
6 Simplified Forward Characteristics Model....8
7 Package outlines....9
8 Revision History....10

2 Maximum ratings

Table 3 Maximum ratings

Parameter	Symbol	Values			Unit	Note/Test Condition
		Min.	Typ.	Max.		
Continuous forward current	I_F	–	–	16	A	T_C < 135°C, D=1
Surge non-repetitive forward current, sine halfwave	$I_{F,SM}$	–	–	124		T_C = 25°C, t_p=10 ms
		–	–	105		T_C = 150°C, t_p=10 ms
Non-repetitive peak forward current	$I_{F,max}$	–	–	637		T_C = 25°C, t_p=10 µs
i²t value	$\int i^2dt$	–	–	76	A²s	T_C = 25°C, t_p=10 ms
		–	–	55		T_C = 150°C, t_p=10 ms
Repetitive peak reverse voltage	V_{RRM}	–	–	650	V	T_j = 25°C
Diode dv/dt ruggedness	dv/dt	–	–	100	V/ns	V_R=0..480 V
Power dissipation	P_{tot}	–	–	129	W	T_C = 25°C
Operating and storage temperature	T_j;T_{stg}	-55	–	175	°C	
Mounting torque		–	–	70	Ncm	M3 screws

3 Thermal characteristics

Table 4 Thermal characteristics TO-220-2

Parameter	Symbol	Values			Unit	Note/Test Condition
		Min.	Typ.	Max.		
Thermal resistance, junction-case	R_{thJC}	–	0.7	1.2	K/W	
Thermal resistance, junction-ambient	R_{thJA}	–	–	62		leaded
Soldering temperature, wavesoldering only allowed at leads	T_{sold}	–	–	260	°C	1.6mm (0.063 in.) from case for 10 s

4 Electrical characteristics

Table 5 Static characteristics

Parameter	Symbol	Values			Unit	Note/Test Condition
		Min.	Typ.	Max.		
DC blocking voltage	V_{DC}	650	–	–	V	I_R= 0.2 mA, T_j=25°C
Diode forward voltage	V_F	–	1.5	1.7		I_F= 16 A, T_j=25°C
		–	1.8	2.1		I_F= 16 A, T_j=150°C
Reverse current	I_R	–	0.85	200	µA	V_R=650 V, T_j=25°C
		–	0.2	71		V_R=600 V, T_j=25°C
		–	3.2	1400		V_R=650 V, T_j=150°C

Table 6 AC characteristics

Parameter	Symbol	Values			Unit	Note/Test Condition
		Min.	Typ.	Max.		
Total capacitive charge	Q_c	–	23		nC	V_R=400 V, *di/dt*=200A/µs, $I_F \leq I_{F,MAX}$, T_j=150°C
Total Capacitance	C	–	470	–	pF	V_R=1 V, *f*=1 MHz
		–	61	–		V_R=300 V, *f*=1 MHz
		–	60	–		V_R=600 V, *f*=1 MHz

5 Electrical characteristics diagrams

Table 7

Power dissipation	Diode forward Current
	
P_{tot}=f(T_C); $R_{thJC,max}$	I_F=f(T_C); T_j≤175°C; $R_{thJC,max}$; parameter D=duty cycle

Table 8

Typical forward characteristics	Typical forward characteristics in surge current
	
I_F=f(V_F); t_p=200 µs; parameter: T_j	I_F=f(V_F); t_p=200 µs; parameter: T_j

Table 9

Typ. capacitance charge vs. current slope[1)]	Typ. reverse current vs. reverse voltage
	
Q_C=f(di$_F$/dt); T_j=150°C; V_R=400 V; $I_F \leq I_{F,max}$	I_R=f(V_R); parameter: T_j

1) Only capacitive charge, guaranteed by design.

Table 10

Max. transient thermal impedance	Typ. capacitance vs. reverse voltage
	
$Z_{th,jc}$=f(t_P); parameter: D=t_P/T	C=f(V_R); T_j=25°C; f=1 MHz

Table 11

Typ. capacitance stored energy

E_C=f(V_R)

6 Simplified Forward Characteristics Model

Table 12

Equivalent forward current curve	Mathematical Equation
	$V_F = V_{TH} + R_{DIFF} \cdot I_F$ $V_{TH}(T_j) = -0.001 \cdot T_j + 1.04$ [V] $R_{DIFF}(T_j) = 8 \cdot 10^{-7} \cdot T_j^2 + 8 \cdot 10^{-5} \cdot T_j + 0.029$ [Ω]
V_F=f(I_F)	T_j in °C; -55°C < T_j < 175°C; I_F < 32 A

7 Package outlines



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.30	4.50	0.169	0.177
A1	1.17	1.37	0.046	0.054
A2	2.30	2.50	0.091	0.098
b	0.65	0.85	0.026	0.033
b1	1.19	1.69	0.047	0.066
b2	1.19	1.39	0.047	0.055
c	0.40	0.60	0.016	0.024
D	15.35	15.95	0.604	0.628
D1	9.05	9.45	0.356	0.372
D2	12.30	13.05	0.484	0.514
E	9.80	10.20	0.386	0.402
E1	7.25	8.60	0.285	0.339
e1	5.08		0.200	
N	2		2	
H1	5.90	6.90	0.232	0.272
L	13.00	14.00	0.512	0.551
L1	3.30	3.70	0.130	0.146
øP	3.55	3.70	0.140	0.146
Q	2.60	3.00	0.102	0.118

DOCUMENT NO.
Z8B00150560

SCALE 0 2.5 5mm

EUROPEAN PROJECTION

ISSUE DATE
28-10-2008

REVISION
01

Figure 1 **Outlines TO-220, dimensions in mm/inches**

8 Revision History

5th Generation thinQ!™ SiC Schottky Diode

Revision History: 2012-12-10, Rev. 2.2

Previous Revision:

Revision	Subjects (major changes since last version)
2.0	Release of the final datasheet.
2.1	Reverse current values, maximum diode forward voltage.
2.2	Reverse current values, tested avalanche current, simplified calculation model

We Listen to Your Comments
Any information within this document that you feel is wrong, unclear or missing at all?
Your feedback will help us to continuously improve the quality of this document.
Please send your proposal (including a reference to this document) to: **erratum@infineon.com**

Edition 2012-12-10
Published by
Infineon Technologies AG
81726 Munich, Germany
© 2012 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (**www.infineon.com**).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

www.infineon.com

Published by Infineon Technologies AG