

**Applications**


- High Frequency DC-DC Isolated Converters with Synchronous Rectification for Telecom and Industrial Use
- High Frequency Buck Converters for Computer Processor Power
- Lead-Free

**Benefits**

- Ultra-Low Gate Impedance
- Very Low  $R_{DS(on)}$  at 4.5V  $V_{GS}$
- Fully Characterized Avalanche Voltage and Current

HEXFET® Power MOSFET

|           |                  |       |
|-----------|------------------|-------|
| $V_{DSS}$ | $R_{DS(on)}$ max | $I_D$ |
| 30V       | 12mΩ             | 62A   |



**Absolute Maximum Ratings**

| Symbol                     | Parameter                                | Max.         | Units |
|----------------------------|--|--------------|-------|
| $V_{DS}$                   | Drain-Source Voltage                     | 30           | V     |
| $V_{GS}$                   | Gate-to-Source Voltage                   | ±12          | V     |
| $I_D$ @ $T_C = 25^\circ C$ | Continuous Drain Current, $V_{GS}$ @ 10V | 62           | A     |
| $I_D$ @ $T_C = 70^\circ C$ | Continuous Drain Current, $V_{GS}$ @ 10V | 52           |       |
| $I_{DM}$                   | Pulsed Drain Current <sup>①</sup>        | 248          |       |
| $P_D$ @ $T_C = 25^\circ C$ | Maximum Power Dissipation <sup>③</sup>   | 87           | W     |
| $P_D$ @ $T_C = 70^\circ C$ | Maximum Power Dissipation <sup>③</sup>   | 61           | W     |
|                            | Linear Derating Factor                   | 0.58         | W/°C  |
| $T_J, T_{STG}$             | Junction and Storage Temperature Range   | -55 to + 175 | °C    |

**Thermal Resistance**

|                 | Parameter  | Typ. | Max. | Units |
|-----------------|--|------|------|-------|
| $R_{\theta JC}$ | Junction-to-Case                                 | —    | 1.73 | °C/W  |
| $R_{\theta CS}$ | Case-to-Sink, Flat, Greased Surface <sup>④</sup> | 0.50 | —    |       |
| $R_{\theta JA}$ | Junction-to-Ambient <sup>④</sup>                 | —    | 62   |       |
| $R_{\theta JA}$ | Junction-to-Ambient (PCB mount)*                 | —    | 40   |       |

\* When mounted on 1" square PCB (FR-4 or G-10 Material) .  
For recommended footprint and soldering techniques refer to application note #AN-994

Notes ① through ④ are on page 10

www.irf.com

# IRF3708/S/LPbF

International  
**IR** Rectifier

## Static @ T<sub>J</sub> = 25°C (unless otherwise specified)

|  | Parameter                            | Min. | Typ.  | Max. | Units | Conditions  |
|--|--------------------------------------|------|-------|------|-------|---|
| V <sub>(BR)DSS</sub>                   | Drain-to-Source Breakdown Voltage    | 30   | —     | —    | V     | V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA                        |
| ΔV <sub>(BR)DSS</sub> /ΔT <sub>J</sub> | Breakdown Voltage Temp. Coefficient  | —    | 0.028 | —    | V/°C  | Reference to 25°C, I <sub>D</sub> = 1mA                             |
| R <sub>DS(on)</sub>                    | Static Drain-to-Source On-Resistance | —    | 8     | 12.0 | mΩ    | V <sub>GS</sub> = 10V, I <sub>D</sub> = 15A ③                       |
|  |                                      | —    | 9.5   | 13.5 |       | V <sub>GS</sub> = 4.5V, I <sub>D</sub> = 12A ③                      |
|  |                                      | —    | 14.5  | 29   |       | V <sub>GS</sub> = 2.8V, I <sub>D</sub> = 7.5A ③                     |
| V <sub>GS(th)</sub>                    | Gate Threshold Voltage               | 0.6  | —     | 2.0  | V     | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA          |
| I <sub>DSS</sub>                       | Drain-to-Source Leakage Current      | —    | —     | 20   | μA    | V <sub>DS</sub> = 24V, V <sub>GS</sub> = 0V                         |
|  |                                      | —    | —     | 100  |       | V <sub>DS</sub> = 24V, V <sub>GS</sub> = 0V, T <sub>J</sub> = 125°C |
| I <sub>GSS</sub>                       | Gate-to-Source Forward Leakage       | —    | —     | 200  | nA    | V <sub>GS</sub> = 12V   |
|  | Gate-to-Source Reverse Leakage       | —    | —     | -200 |       | V <sub>GS</sub> = -12V  |


## Dynamic @ T<sub>J</sub> = 25°C (unless otherwise specified)


| Symbol              | Parameter                       | Min. | Typ. | Max. | Units | Conditions  |
|---------------------|---------------------------------|------|------|------|-------|---|
| g <sub>fs</sub>     | Forward Transconductance        | 49   | —    | —    | S     | V <sub>DS</sub> = 15V, I <sub>D</sub> = 50A                         |
| Q <sub>g</sub>      | Total Gate Charge               | —    | 24   | —    | nC    | I <sub>D</sub> = 24.8A  |
| Q <sub>gs</sub>     | Gate-to-Source Charge           | —    | 6.7  | —    |       | V <sub>DS</sub> = 15V   |
| Q <sub>gd</sub>     | Gate-to-Drain ("Miller") Charge | —    | 5.8  | —    |       | V <sub>GS</sub> = 4.5V ③  |
| Q <sub>oss</sub>    | Output Gate Charge              | —    | 14   | 21   |       | V <sub>GS</sub> = 0V, I <sub>D</sub> = 24.8A, V <sub>DS</sub> = 15V |
| t <sub>d(on)</sub>  | Turn-On Delay Time              | —    | 7.2  | —    | ns    | V <sub>DD</sub> = 15V   |
| t <sub>r</sub>      | Rise Time                       | —    | 50   | —    |       | I <sub>D</sub> = 24.8A  |
| t <sub>d(off)</sub> | Turn-Off Delay Time             | —    | 17.6 | —    |       | R <sub>G</sub> = 0.6Ω   |
| t <sub>f</sub>      | Fall Time                       | —    | 3.7  | —    |       | V <sub>GS</sub> = 4.5V ③  |
| C <sub>iss</sub>    | Input Capacitance               | —    | 2417 | —    | pF    | V <sub>GS</sub> = 0V  |
| C <sub>oss</sub>    | Output Capacitance              | —    | 707  | —    |       | V <sub>DS</sub> = 15V   |
| C <sub>rss</sub>    | Reverse Transfer Capacitance    | —    | 52   | —    |       | f = 1.0MHz  |

## Avalanche Characteristics


| Symbol          | Parameter                      | Typ. | Max. | Units |
|-----------------|--------------------------------|------|------|-------|
| E <sub>AS</sub> | Single Pulse Avalanche Energy② | —    | 213  | mJ    |
| I <sub>AR</sub> | Avalanche Current①             | —    | 62   | A     |

## Diode Characteristics


| Symbol          | Parameter                              | Min. | Typ. | Max. | Units | Conditions   |
|-----------------|--|------|------|------|-------|--|
| I <sub>S</sub>  | Continuous Source Current (Body Diode) | —    | —    | 62   | A     | MOSFET symbol showing the integral reverse p-n junction diode.  |
| I <sub>SM</sub> | Pulsed Source Current (Body Diode) ①   | —    | —    | 248  |       |  |
| V <sub>SD</sub> | Diode Forward Voltage                  | —    | 0.88 | 1.3  | V     | T <sub>J</sub> = 25°C, I <sub>S</sub> = 31A, V <sub>GS</sub> = 0V ③  |
|                 |  | —    | 0.80 | —    |       | T <sub>J</sub> = 125°C, I <sub>S</sub> = 31A, V <sub>GS</sub> = 0V ③   |
| t <sub>rr</sub> | Reverse Recovery Time                  | —    | 41   | 62   | ns    | T <sub>J</sub> = 25°C, I <sub>F</sub> = 31A, V <sub>R</sub> = 20V  |
| Q <sub>rr</sub> | Reverse Recovery Charge                | —    | 64   | 96   | nC    | di/dt = 100A/μs ③  |
| t <sub>rr</sub> | Reverse Recovery Time                  | —    | 43   | 65   | ns    | T <sub>J</sub> = 125°C, I <sub>F</sub> = 31A, V <sub>R</sub> = 20V   |
| Q <sub>rr</sub> | Reverse Recovery Charge                | —    | 70   | 105  | nC    | di/dt = 100A/μs ③  |




**Fig 1.** Typical Output Characteristics




**Fig 2.** Typical Output Characteristics




**Fig 3.** Typical Transfer Characteristics




**Fig 4.** Normalized On-Resistance Vs. Temperature




**Fig 5.** Typical Capacitance Vs. Drain-to-Source Voltage




**Fig 6.** Typical Gate Charge Vs. Gate-to-Source Voltage




**Fig 7.** Typical Source-Drain Diode Forward Voltage




**Fig 8.** Maximum Safe Operating Area




**Fig 9.** Maximum Drain Current Vs. Case Temperature




**Fig 10a.** Switching Time Test Circuit




**Fig 10b.** Switching Time Waveforms




**Fig 11.** Maximum Effective Transient Thermal Impedance, Junction-to-Case




**Fig 12.** On-Resistance Vs. Drain Current




**Fig 13.** On-Resistance Vs. Gate Voltage



**Fig 14a&b.** Gate Charge Test Circuit and Waveform





**Fig 15a&b.** Unclamped Inductive Test circuit and Waveforms



**Fig 15c.** Maximum Avalanche Energy Vs. Drain Current

## TO-220AB Package Outline

Dimensions are shown in millimeters (inches)



LEAD ASSIGNMENTS

| HEXFET    | IGBTs, CoPACK |
|-----------|---------------|
| 1- GATE   | 1- GATE       |
| 2- DRAIN  | 2- COLLECTOR  |
| 3- SOURCE | 3- EMITTER    |
| 4- DRAIN  | 4- COLLECTOR  |

NOTES:


- 1 DIMENSIONING & TOLERANCING PER ANSI Y14.5M, 1982.
- 2 CONTROLLING DIMENSION : INCH

- 3 OUTLINE CONFORMS TO JEDEC OUTLINE TO-220AB.
- 4 HEATSINK & LEAD MEASUREMENTS DO NOT INCLUDE BURRS.

## TO-220AB Part Marking Information

EXAMPLE: THIS IS AN IRF1010  
 LOT CODE 1789  
 ASSEMBLED ON WW 19, 1997  
 IN THE ASSEMBLY LINE "C"

**Note:** "P" in assembly line position indicates "Lead-Free"




# IRF3708/S/LPbF

International  
**IR** Rectifier

## D<sup>2</sup>Pak Package Outline


Dimensions are shown in millimeters (inches)




## D<sup>2</sup>Pak Part Marking Information (Lead-Free)

EXAMPLE: THIS IS AN IRF530S WITH  
LOT CODE 8024  
ASSEMBLED ON WW 02, 2000  
IN THE ASSEMBLY LINE "L"

Note: "P" in assembly line  
position indicates "Lead-Free"




**OR**





## TO-262 Package Outline



| SYMBOL | DIMENSIONS  |       |          |      | NOTES |
|--------|-------------|-------|----------|------|-------|
|        | MILLIMETERS |       | INCHES   |      |       |
|        | MIN.        | MAX.  | MIN.     | MAX. |       |
| A      | 4.06        | 4.83  | .160     | .190 |       |
| A1     | 2.03        | 2.92  | .080     | .115 |       |
| b      | 0.51        | 0.99  | .020     | .039 |       |
| b1     | 0.51        | 0.89  | .020     | .035 | 4     |
| b2     | 1.14        | 1.40  | .045     | .055 |       |
| c      | 0.38        | 0.63  | .015     | .025 | 4     |
| c1     | 1.14        | 1.40  | .045     | .055 |       |
| c2     | 0.43        | .063  | .017     | .029 |       |
| D      | 8.51        | 9.65  | .335     | .380 | 3     |
| D1     | 5.33        |       | .210     |      |       |
| E      | 9.65        | 10.67 | .380     | .420 | 3     |
| E1     | 6.22        |       | .245     |      |       |
| e      | 2.54 BSC    |       | .100 BSC |      |       |
| L      | 13.46       | 14.09 | .530     | .555 |       |
| L1     | 3.56        | 3.71  | .140     | .146 |       |
| L2     |             | 1.65  |          | .065 |       |


**LEAD ASSIGNMENTS**

|            |              |
|------------|--------------|
|            | IGBT         |
| HEXFLET    | 1- GATE      |
| 1.- GATE   | 2- COLLECTOR |
| 2.- DRAIN  | 3- EMITTER   |
| 3.- SOURCE |              |
| 4.- DRAIN  |              |


- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
  2. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES]
  3. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.127 [0.005"] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY.
  4. DIMENSION b1 AND c1 APPLY TO BASE METAL ONLY.
  5. CONTROLLING DIMENSION: INCH.

## TO-262 Part Marking Information

EXAMPLE: THIS IS AN IRL3103L  
 LOT CODE 1789  
 ASSEMBLED ON WW 19, 1997  
 IN THE ASSEMBLY LINE "C"  
 Note: "P" in assembly line  
 position indicates "Lead-Free"



**OR**




# IRF3708/S/LPbF

International  
**IR** Rectifier

## D<sup>2</sup>Pak Tape & Reel Information

Dimensions are shown in millimeters (inches)



- NOTES:
1. CONFORMS TO EIA-418.
  2. CONTROLLING DIMENSION: MILLIMETER.
  3. DIMENSION MEASURED @ HUB.
  4. INCLUDES FLANGE DISTORTION @ OUTER EDGE.

### Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature.
- ② Starting  $T_J = 25^\circ\text{C}$ ,  $L = 0.7\text{ mH}$   
 $R_G = 25\Omega$ ,  $I_{AS} = 24.8\text{ A}$ .
- ③ Pulse width  $\leq 300\mu\text{s}$ ; duty cycle  $\leq 2\%$ .
- ④ This is only applied to TO-220AB package

Data and specifications subject to change without notice.

International  
**IR** Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information.06/04

Note: For the most current drawings please refer to the IR website at:  
<http://www.irf.com/package/>

## **IMPORTANT NOTICE**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office ([www.infineon.com](http://www.infineon.com)).

## **WARNINGS**

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.