



Material Content Data Sheet



| Sales Product Name | | | | IM69D130V01 | | Issued | | 4. July 2019 | |
|---------------------------|--------------------|-----------------------------|--------------------|-------------|------------------|----------------|--------------------|--------------|--|
| MA# | | | | MA005285760 | | | | | |
| Package | | | | PG-LLGA-5-1 | | Weight* | | 34.06 mg | |
| Construction Element | Material Group | Substances | CAS# if applicable | Weight [mg] | Average Mass [%] | Sum [%] | Average Mass [ppm] | Sum [ppm] | |
| chip_1 | inorganic material | silicon | 7440-21-3 | 0.299 | 0.88 | 0.88 | 8774 | 8774 | |
| chip_2 | inorganic material | silicon | 7440-21-3 | 3.365 | 9.88 | 9.88 | 98785 | 98785 | |
| wire | noble metal | gold | 7440-57-5 | 0.033 | 0.10 | 0.10 | 983 | 983 | |
| encapsulation | inorganic material | silicondioxide | 60676-86-0 | 0.041 | 0.12 | | 1191 | | |
| | plastics | silicone resin | - | 0.365 | 1.07 | 1.19 | 10716 | 11907 | |
| leadfinish | noble metal | gold | 7440-57-5 | 0.124 | 0.37 | | 3652 | | |
| | non noble metal | nickel | 7440-02-0 | 0.142 | 0.42 | 0.79 | 4165 | 7817 | |
| substrate | plastics | bismaleimide triazine resin | - | 0.865 | 2.54 | | 25397 | | |
| | inorganic material | aluminiumhydroxide | 21645-51-2 | 0.952 | 2.79 | | 27937 | | |
| | inorganic material | glass fibre | - | 1.644 | 4.83 | | 48255 | | |
| | non noble metal | copper | 7440-50-8 | 5.010 | 14.71 | 24.87 | 147101 | 248690 | |
| solder | non noble metal | copper | 7440-50-8 | 0.017 | 0.05 | | 511 | | |
| | noble metal | silver | 7440-22-4 | 0.104 | 0.31 | | 3066 | | |
| | non noble metal | tin | 7440-31-5 | 3.359 | 9.86 | 10.22 | 98611 | 102188 | |
| lid attach material | organic material | carbon black | 1333-86-4 | 0.000 | 0.00 | | 4 | | |
| | inorganic material | silicondioxide | 60676-86-0 | 0.010 | 0.03 | | 294 | | |
| | plastics | silicone | - | 0.015 | 0.04 | 0.07 | 447 | 745 | |
| lid | non noble metal | zinc | 7440-66-6 | 5.868 | 17.23 | | 172279 | | |
| | non noble metal | copper | 7440-50-8 | 10.897 | 31.98 | 49.21 | 319947 | 492226 | |
| solder resists | plastics | epoxy resin | - | 0.220 | 0.65 | | 6469 | | |
| | inorganic material | bariumsulfate | 7727-43-7 | 0.338 | 0.99 | | 9927 | | |
| | plastics | acrylic resin | - | 0.391 | 1.15 | 2.79 | 11489 | 27885 | |
| *deviation | < 10% | | Sum in total: | | | 100.00 | | 1000000 | |

Important Remarks:

1. Infineon Technologies AG provides full material declaration based on information provided by third parties and has taken and continues to take reasonable steps to provide representative and accurate information.
2. Infineon Technologies AG and Infineon Technologies AG suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.
3. All statements are based on our present knowledge, are provided 'as is' and may be subject to change at any time due to technical requirements and development without notification.

This product is in compliance with EU Directive 2015/863/EU amending Annex II to EU Directive 2011/65/EU (RoHS) and does not use any exemption

| | |
|----------|--------------------------|
| Company | Infineon Technologies AG |
| Address | 81726 München |
| Internet | www.infineon.com |