

Product brief

OptiMOS™ p-channel MOSFETs 60 V family

Infineon's next generation of p-channel products

Infineon offers high-performance products with the best price/performance ratio in the industry due to cost-effective packages and a leading, reliable and mature silicon technology.

OptiMOS™ p-channel MOSFETs simplify the design complexity in medium and low power applications. Their easy interface to microcontroller unit (MCU), fast switching and avalanche ruggedness make them suitable for high quality demanding applications. OptiMOS™ p-channel MOSFETs improve efficiency at low loads due to low gate charge (Q_g). The products are available in logic and normal level featuring a wide on-resistance ($R_{DS(on)}$) range.

Infineon's next generation of p-channel products are an extension to the current product portfolio. In addition, some of these products are good alternatives or replacements to existing p-channel products.

Infineon's OptiMOS™ technology combined with the small signal and power MOSFET packages are optimized for a variety of applications and circuits, such as low voltage drives, linear battery charger, battery protection, load switches, DC-DC converters, reverse polarity protection and many more.

Infineon's new OptiMOS™ p-channel MOSFETs 60 V are available in 4 different packages:

- > Small signal packages: SOT-23 and SOT-223
- > Power packages: DPAK and D²PAK

Key features

- > $V_{BRDSS} = -60\text{ V}$
- > Available in 4 different packages
- > Wide $R_{DS(on)}$ range
- > Normal level and logic level availability

Key benefits

- > Fast switching
- > Avalanche ruggedness
- > Easy interface to MCU
- > Improved efficiency at low loads due to low Q_g
- > Reduced design complexity
- > Energy efficiency
- > Industry standard packages

Target applications

- > Battery management
- > Load switch
- > Reverse polarity protection

OptiMOS™ p-channel MOSFETs 60 V family

Infineon's next generation of p-channel products

Product portfolio

V_{BRDSS}	Package	Part number	$R_{DS(on)}$ max. @ $V_{GS} = 10\text{ V}$ [mW]	Normal level (NL) Logic level (LL)
Best fit for industrial applications				
-60 V	D ² PAK	IPB110P06LM	11	LL
		DPAK	IPD380P06NM	38
		IPD650P06NM	65	NL
		IPD900P06NM	90	NL
		IPD25DP06LM	250	LL
		IPD25DP06NM	250	NL
		IPD40DP06NM	400	NL
	SOT-223	ISP650P06NM	65	NL
		ISP12DP06NM	125	NL
		ISP25DP06LM	250	LL
		ISP25DP06NM	250	NL
		ISP75DP06LM	750	LL
	SOT-23	ISS17EP06LM	1700	LL
		ISS55EP06LM	5500	LL
Best fit for consumer applications				
-60 V	SOT-223	ISP13DP06NMS	130	NL
		ISP25DP06LMS	250	LL
		ISP26DP06NMS	260	NL

Published by
Infineon Technologies Austria AG
9500 Villach, Austria

© 2019 Infineon Technologies AG.
All Rights Reserved.

Please note!

THIS DOCUMENT IS FOR INFORMATION PURPOSES ONLY AND ANY INFORMATION GIVEN HEREIN SHALL IN NO EVENT BE REGARDED AS A WARRANTY, GUARANTEE OR DESCRIPTION OF ANY FUNCTIONALITY, CONDITIONS AND/OR QUALITY OF OUR PRODUCTS OR ANY SUITABILITY FOR A PARTICULAR PURPOSE. WITH REGARD TO THE TECHNICAL SPECIFICATIONS OF OUR PRODUCTS, WE KINDLY ASK YOU TO REFER TO THE RELEVANT PRODUCT DATA SHEETS PROVIDED BY US. OUR CUSTOMERS AND THEIR TECHNICAL DEPARTMENTS ARE REQUIRED TO EVALUATE THE SUITABILITY OF OUR PRODUCTS FOR THE INTENDED APPLICATION.

WE RESERVE THE RIGHT TO CHANGE THIS DOCUMENT AND/OR THE INFORMATION GIVEN HEREIN AT ANY TIME.

Additional information

For further information on technologies, our products, the application of our products, delivery terms and conditions and/or prices, please contact your nearest Infineon Technologies office (www.infineon.com).

Warnings

Due to technical requirements, our products may contain dangerous substances. For information on the types in question, please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by us in a written document signed by authorized representatives of Infineon Technologies, our products may not be used in any life-endangering applications, including but not limited to medical, nuclear, military, life-critical or any other applications where a failure of the product or any consequences of the use thereof can result in personal injury.