

SLC 14MCO288K2

32-bit SIM-card Controller
Optimized for Mobile Communication Applications

288 kBytes Flash
10 kBytes RAM

32-bit ARM Cortex M0 based microcontroller

ISO7816 (GSM 11.11, 11.12, 11.18)

Short Product Overview

June 2013

Edition 2013-06

**Published by
Infineon Technologies AG
81726 Munich, Germany**

**© 2013 Infineon Technologies AG
All Rights Reserved.**

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Product name	SLC 14MCO288K2
Product description	32-bit SIM-card controller
Interfaces	ISO 7816
Memory	288 kBytes Flash + 10 kBytes RAM
CPU	32-bit
Clock (int.)	1 - 32 MHz
Clock (ext.)	1 - 10 MHz
Operating voltage	1.62 V – 3.3 V
Max. sleep mode current	100 μ A (in ISO clock stop mode)
Ambient temperature	-25 to + 85 °C
Delivery forms	Module: MFC5.x, MFC1.6 Bare die
Typical applications	GSM, UICC
Certification level	–

For further information on technology, delivery forms and conditions please contact your nearest Infineon Technologies sales representative (www.infineon.com).

Infineon Technologies – innovative semiconductor solutions for energy efficiency, mobility and security.

