



TC1793-AUDO MAX family

Automotive 32-bit TriCore™ Microcontroller

The TC1793 is one of three premium derivatives of the AUDO MAX family. Its 270MHz award-winning TriCore™ CPU provides high-end microcontroller performance combined with sophisticated DSP capabilities and dedicated safety features. The new TriCore™ version 1.6 offers a significantly increased Floating Point Unit performance and an Integer Division Unit in Hardware. Furthermore memory protection is optimized and Branch prediction is enhanced by a new buffer system. Equipped with 4.0 MByte of embedded flash and a total of up to 288 KByte SRAM (which now comes with Error Code Correction), the TC1793 is one of the highest performing microcontrollers for embedded real-time automotive applications. Upgrade from the earlier AUDO Future is facilitated as TC1793 BGA416 is pin-compatible and object code is backward compatible. The comprehensive and consistent tool support known from earlier TriCore™ families will also be provided for AUDO MAX family.

Applications

- Engine and transmission control
- 4-6-8 cylinder diesel or gasoline direct injection
- Double clutch transmission
- Hybrid and electric vehicle
- Suspension systems

Features

- High performance 32-bit super-scalar TriCore™ V1.6 CPU with 6 stage pipeline
 - 270MHz/200MHz at full automotive temperature range
 - Superior real-time performance
 - Strong bit handling
 - Fully integrated DSP capabilities
 - Single precision floating point unit
- 32-bit Peripheral Control Processor with single cycle instruction (PCP2)
48Kbyte on-chip SRAM


Features

- Memories:
 - 4,0MB embedded program flash with ECC
 - 192KByte data flash
 - 288KByte on-chip SRAM
 - 16KByte Data cache (dedicated)
 - 16KByte Instruction cache (dedicated)
- 24 DMA channels
- 2 General Purpose Timer Arrays(GPTA)
- 4 Capture/Compare Units (CCU)
- 32Bit external memory unit (EBU)
- 2 FlexRay™ channels
- 2 Micro Second bus interfaces (MSC)
- 2 asynchronous/synchronous serial interfaces (ASC)
- 4 high speed synchronous serial Interfaces (SSC)
- 2 high speed Micro Link Interfaces (MLI)
- MultiCAN module with 4 CAN nodes & 128 message objects
- 4 channel fast analog-to-digital converter (FADC)
- 44 channel analog-to-digital converter (ADC)
(5/3,3V)
- 8 SENT channels
- Secure HW Extension (SHE)
- On-chip debug support (OCDS)
- Dedicated emulation device chip for multicore debugging, tracing and (ED-Device) calibration
- Core voltage 1,3V
- Extensive set of safety features
- Full automotive temperature range
-40°C to 125°C
- BGA416 package

TC1793-AUDO MAX family

Automotive 32-bit TriCore™ Microcontroller

Block Diagram



Product Summary

Type	eFlash	DataFlash	Frequency	SRAM	Package	Temp. Range
SAK-TC1793F-512F200EB	4,0 MB	192 KB*	200 MHz	288 KB	LBGA416	-40°C...+125°C
SAK-TC1793F-512F270EB	4,0 MB	192 KB*	270 MHz	288 KB	LBGA416	-40°C...+125°C

*EEPROM emulation (up to 60k w/e cycles)

Published by
 Infineon Technologies AG
 85579 Neubiberg, Germany

© 2010 Infineon Technologies AG.
 All Rights Reserved.

Visit us:
www.infineon.com

Order Number: B158-H9516-X-X-7600
 Date: 09 / 2013

ATTENTION PLEASE!

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

INFORMATION

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (www.infineon.com).

WARNINGS

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office. Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.